


Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003	
		WELL API NO. 30-025-37484		5. Indicate Type of Lease STATE ☐ FEE ☒	
		State Oil & Gas Lease No.		7. Lease Name or Unit Agreement Name TURNER	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____ b. Type of Completion: NEW ☐ WORK ☐ DEEPEN ☐ PLUG ☒ DIFF. _____ WELL OVER BACK RESVR. ☐ OTHER _____				8. Well No. 5	
2. Name of Operator Apache Corporation				9. Pool name or Wildcat Penrose Skelly, Grayburg (50350)	
3. Address of Operator 6120 South Yale, Suite 1500 Tulsa, OK 74136-4224				4. Well Location Unit Letter O : 990 Feet From The South Line and 1650 Feet From The East Line Section 29 Township 21S Range 37E NMPM Lea County	
10. Date Spudded 06/21/2006		11. Date T.D. Reached 06/28/2006		12. Date Compl. (Ready to Prod.) 10/14/2006	
13. Elevations (DF& RKB, RT, GR, etc.) 3470'		14. Elev. Casinghead		15. Total Depth 4445'	
16. Plug Back T.D. 4000' CIBP		17. If Multiple Compl. How Many Zones? 4000' CIBP		18. Intervals Drilled By X	
19. Producing Interval(s), of this completion - Top, Bottom, Name Grayburg				20. Was Directional Survey Made No	
21. Type Electric and Other Logs Run SD/DSN & DLL/MG				22. Was Well Cored No	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE		WEIGHT LB./FT.		DEPTH SET	
8-5/8"		24#		389'	
5-1/2"		17#		4445'	
HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED	
11"		280 sx / circ		850 sx / TOC 222' CBL	
7-7/8"		850 sx / TOC 222' CBL			
24. LINER RECORD		25. TUBING RECORD		26. PERFORATION RECORD (Interval, size, and number)	
SIZE		TOP		BOTTOM	
SACKS CEMENT		SCREEN		SIZE	
2-7/8"		3968'		PACKER SET	
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.		DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED	
San Andres 4038-42,47-61,69-76,83-99 & 4126-32'		4038 - 4132'		Acidize with 3000 gals 15% FeAs	
2 JSPF CIBP		3735 - 3897		Acidize with 2000 gals 15% NeFe	
Grayburg 3735-39,96-3800,36-40,75-79 & 3893-97'		3735 - 3897'		Frac with 47,250 gals gel + 100k# 20/40 sand	
2 JSPF					
28. PRODUCTION					
Date First Production 10/14/2006		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping		Well Status (Prod. or Shut-in) Producing	
Date of Test 10/31/2006		Hours Tested 24 hrs		Choke Size	
Flow Tubing Press.		Casing Pressure		Calculated 24-Hour Rate	
Oil - Bbl		Gas - MCF		Water - Bbl.	
19		202		268	
Gas - Oil Ratio		Oil Gravity - API - (Corr.)		29. Disposition of Gas (Sold, used for fuel, vented, etc.)	
10632				Test Witnessed By Apache Corporation	
30. List Attachments Deviation Report, Logs, C-102 & C-104					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature 		Printed Name Elaine Linton		Title Engineering Technician	
E-mail Address elaine.linton@apachecorp.com		Date 11/21/2006			

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2605'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2837'	T. Devonian	T. Menefee	T. Madison
T. Queen 3359'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3645'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3909'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T. Rustler 1196'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology