Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OCD-HOBBS

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5. Lease Serial No.

891038170 -	LC06572
-------------	---------

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instruc	ctions on reverse side 7. If Unit or CA/Agreement, Name as	nd/or No
1. Type of Well	Myers Langlie Mattix Unit	
Oil Well Gas Well X Other	Injection 8. Well Name and No.	
2. Name of Operator	#117	
OXY USA WTP Limited Partnership 3a. Address	192463 9. API Well No.	
P.O. Box 50250, Midland, TX 79710-0250	3b. Phone No. (include area code) 432 - 685 - 5717 30 - 025 - 10951 10 Field and Pool or Exploratory As	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	10. Field and Pool, or Exploratory Ar Langlie Mattix 7Rvr Qn-GB	
660 FSL 660 FWL SWSW(M) Sec 34 T23S R37E	Edity it interx it will the	
	11. County or Parish, State	
12 CHECK APPROPRIATE ROY(FO) TO	Lea NM	
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
X Notice of Intent Acidize	Deepen Production (Start/Resume) Water Shut-Off	
Alter Casi	ing Fracture Treat Reclamation Well Integrity	
Subsequent Report Casing Re	pair New Construction Recomplete Other	
Final Abandonment Notice Change Pl		_
Convert to		
13. Describe Proposed or Completed Operation (clearly state all pertine)	nt details, including estimated starting date of any proposed work and approximate duration the	_
following completion of the involved operations. If the operation results in a multiple completion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.) TD-3700' PBTD-3652' Perfs-3439-3564' 13" 40# csg @ 336' w/ 250sx, 15" hole, TOC-Surf-Circ 9-5/8" 34# csg @ 2540' w/500sx, 11-3/4" hole, TOC-320'-Calc 7" 24# csg @ 3435' w/100sx, 8-3/4" hole, *TOC-2820'-CBL *5/78-Perf @ 2800', cmt w/ 550sx, circ cmt to surf 4-1/2" 9.5# csg @ 3029-3700' w/ 125sx, 6-1/8" hole, TOC-3029'-Circ 1. RIH & set CIBP @ 3389', dump 4sx cmt 2. M&P 25sx cmt @ 3079-2979' 3. M&P 25sx cmt @ 3079-2979' 3. M&P 25sx cmt @ 2850-2750' 4. M&P 25sx @ 1100-1000' 6. M&P 25sx @ 136-286' WOC-Tag 7. M&P 20sx cmt @ surface 10# MLF between plugs 14. I hereby certify that the foregoing is true and correct Title		
14. I hereby certify that the foregoing is true and correct Name (Printed Typed)		
David Stewart	Sr. Regulatory Analyst	
	Date 12(8) OF APPROVED	
THIS SPACE FOR	FEDERAL OR STATE OFFICE USE	
Approved by Law Williams	Title DEC 12ag 2006	
Conditions of approval, if any, are attached. Approval of this notice does certify that the applicant holds legal or equitable title to those rights in the which would entitle the applicant to conduct operations thereon.	not warrant or	_
Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a States any false, fictitious or fraudulent statements or representations as to a	crime for any nerson knowingly and willfully to make Tracklet Life 1	ited

OXY USA WTP LP Myers Langlie Mattix Unit #117 API No. 30-025-10951

20sx Surface

25sx @ 386-286'

25sx @ 1100-1000'

25sx @ 2590-2490'

25sx @ 2850-2750'

25sx @ 3079-2979'

CIBP @ 3389' w/ 4sx



15" hole @ 336' 13" csg @ 336' w/250sx-TOC-Surf-Circ

11-3/4" hole @ 2540' 9-5/8" csg @ 2540' w/500sx-TOC-320'-Calc

*5/78-Perf @ 2800' sqz 550sx-Circ to Surf

8-3/4" hole @ 3435' 7" csg @ 3435' w/100sx-*TOC-2820'-CBL

6-1/8" hole @ 3700' 4-1/2" liner @ 3029-3700' w/125sx-TOC-3029'-Circ

Perfs @ 3439-3564'

SUNDRY NOTICE SPECIAL STIPULATIONS

1.	Approval is granted to plug this well with the following modifications to the proposed procedure:
2.	The 9.625 to 13 inch casing annulus must be cemented to the surface.
3.	All plugs at casing shoes and the tops and base of the salt must be tagged.

***All plugs below the surface plug must be at least 100' and 25 sacks of cement.

Engineering can be reached at 505-706-2779 for any variances that might be necessary.

F Wright 12/13/06