

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

OCD-HOBBS

FORM APPROVED  
OMB NO. 1004-0135  
Expires: November 30, 2000

**SUNDRY NOTICES AND REPORTS ON WELLS**

*Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.*

**SUBMIT IN TRIPLICATE - Other instructions on reverse side**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

OXY USA WTP Limited Partnership

192463

3a. Address

P.O. Box 50250, Midland, TX 79710-0250

3b. Phone No. (include area code)

432-685-5717

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

860 FNL 660 FWL NWNW(D) Sec 7 T24S T37E

5. Lease Serial No.

891038170 - NM7488

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.  
Myers Langlie Mattix Unit

8. Well Name and No.  
#205

9. API Well No.  
30-025-27448

10. Field and Pool, or Exploratory Area  
Langlie Mattix 7Rvr Qn-GB

11. County or Parish, State

Lea NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION


- |   |  |  |   |
|---|--|--|---|
| <input type="checkbox"/> Acidize              | <input type="checkbox"/> Deepen                      | <input type="checkbox"/> Production (Start/Resume) | <input type="checkbox"/> Water Shut-Off |
| <input type="checkbox"/> Alter Casing         | <input type="checkbox"/> Fracture Treat              | <input type="checkbox"/> Reclamation               | <input type="checkbox"/> Well Integrity |
| <input type="checkbox"/> Casing Repair        | <input type="checkbox"/> New Construction            | <input type="checkbox"/> Recomplete                | <input type="checkbox"/> Other          |
| <input type="checkbox"/> Change Plans         | <input checked="" type="checkbox"/> Plug and Abandon | <input type="checkbox"/> Temporarily Abandon       |   |
| <input type="checkbox"/> Convert to Injection | <input type="checkbox"/> Plug Back                   | <input type="checkbox"/> Water Disposal            |   |

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomple horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

TD-3670' PBD-3285' PERFS-3373-3573' CIBP-3325'

8-5/8" 24# csg @ 525' w/350sx, 12-1/4" hole, TOC-Surf-Circ  
5-1/2" 15.5# csg @ 3670' w/1180sx, 7-7/8" hole, TOC-Surf-Circ

1. RIH & Tag Cmt & CIBP @ 3285'
2. M&P 25sx cmt @ 2850-2750'
3. M&P 25sx cmt @ 1180-1080'
4. M&P 25sx cmt @ 575-475' WOC-Tag
5. M&P 15sx cmt Surface Plug  
10# MLF between plugs



14. I hereby certify that the foregoing is true and correct  
Name (Printed/Typed)

David Stewart

Title

Sr. Regulatory Analyst

Date

12/13/06

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Office

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FREDERICK WRIGHT  
PETROLEUM ENGINEER

BWW

OXY USA WTP LP  
Myers Langlie Mattix Unit #205  
API No. 30-025-27448


15sx Surface

25sx @ 575-475' WOC-Tag

25sx @ 1180-1080'

25sx @ 2850-2750'

5/98-CIBP @ 3325' w/ 40' cmt



12-1/4" hole @ 525'  
8-5/8" csg @ 525'  
w/350sx-TOC-Surf-Circ

7-7/8" hole @ 3670'  
5-1/2" csg @ 3670'  
w/1180sx-TOC-Surf-Circ

Perfs @ 3373-3573'

TD-3670'

### **SUNDRY NOTICE SPECIAL STIPULATIONS**

1. Approval is granted to plug this well with the following modifications to the proposed procedure:
2. All plugs below the surface plug should be tagged for casing shoes and the top and base of the salt.

**\*\*\*All plugs below the surface plug must be at least 100' and 25 sacks of cement.**

**Engineering**  
**can be reached at 505-706-2779 for any variances that might be necessary.**

**F Wright 12/13/06**