Submit 3 Copies To Appropriate District Office District I	State of New M Energy, Minerals and Nat		Form C-103 May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API	
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION	N DIVISION	30-025-03735
District III	1220 South St. Fra	ancis Dr. STAT	Type of Lease TE ☑ FEE □
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 8	77.50.5	& Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		LUG BACK TO A	me or Unit Agreement Name
1 /	Gas Well Other SWD-836	8. Well Nur	nber State T No. 002
2. Name of Operator		9. OGRID N	lumber
3. Address of Operator	ndy Corporation	10 Post	122811
	. Box 827, Tatum, NM 88267	10. Pool nar	ne or Wildcat
4. Well Location			
Unit Letter L 4,28	0feet from the South	line and 500 fee	t from the West line
Section 6	Township 16 S	Range 36 E NMPM	
	11. Elevation (Show whether DF	R, RKB, RT, GR, etc.)	County ELA
3,976 DR			
Pit or Below-grade Tank Application or Closure			
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water			
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF IN PERFORM REMEDIAL WORK TEMPORARILY ABANDON	PLUG AND ABANDON ⊠ CHANGE PLANS □	SUBSEQUENT REMEDIAL WORK COMMENCE DRILLING OPNS.[☐ ALTERING CASING ☐
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT JOB [
OTHER:	· 🗖	OTHER:	П
 Describe proposed or comp of starting any proposed we or recompletion. 	pleted operations. (Clearly state all ork). SEE RULE 1103. For Multip	ole Completions: Attach wellbore of	liagram of proposed completion
Gandy Corp. proposed to plug and a 1. Pull injection tubing and pa	bandon this well no later than July	_	
 Go in hole with work string and cement retainer, set above perforations at approximately 4,700°. Squeeze 50 sx class C cement in perforation, leaving at least 25° of cement above perforations. 			
4. Load hole with salt solution.			
5. Spot 25 sx plug at 3,000	0, - Bottom of sact	ut isaa' sis in	1 Bonna Acara Son
25 sx plug at 8 5/8	shoe 1,350'	1900 - 25 515 on 100	WHICHEVER TOPELYOR
25 sx plug at 13 3/6. 10 sx surface plug.	Approved as to	plugging of the WAN D	(E DEC 2006
7. Erect marker and clean loca	ition. Liability under h	ond is retained and	Received (
8. File final sundry notice of p	olugging. surface restoration	on is completed	Hobbs OCD
			- 350
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been will be constructed or closed according to NMOCD guidelines ageneral permit or an (attached) alternative OCD-approved plan.			
SIGNATURE CALLE C	Slevy TITLE	Presedent	DATE 12-12-06
Type or print name: Dale Gandy For State Use Only	E-mail addres	ss: Telepho	ne No. (505) 396-0522
APPROVED BY: Conditions of Approval (if any):	Sellions_TITLE_	CHIBEDING OD SCHNEDAT MANAC	DEC 2 1 2006 DATE