Energy Minerals and Natural Kesources

Oil Conservation Division

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

June 1, 2004

1220 South St. Francis Dr. Santa Fe, NM 87505

| Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes No Type of action: Registration of a pit or below-grade tank Cosure of a pit or below-grade tank | | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|-------------------------------------|
| rator: EOG RESOUTCES INC. Telephone (8 ness: Box 4362; Houston Tx 77216 ility or well name: Cimarron 18 State # 3 api #: 30-025 inty: Lea Latitude # 32 45 002 Longitude 10 2 | 977) 363-3647 e-mail address: | S _R 34E |
| B: Drilling Production Disposal Workover Emergency ed Unlined er type: Synthetic Thickness 2 mil Clay Volumebbl | Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes | |
| with to ground water (vertical distance from bottom of pit to seasonal high er elevation of ground water.) | Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more | (20 points) (10 points) (0 points) |
| ilhead protection area: (Less than 200 feet from a private domestic or source, or less than 1000 feet from all other water sources.) | Yes No | (20 points) (0 points) |
| tance to surface water: (horizontal distance to all wetlands, playas, gation canals, ditches, and perennial and ephemeral watercourses.) | Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more | (20 points) (10 points) (0 points) |
| | Ranking Score (Total Points) | 0 |
| this is a pit closure: (1) attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if our are burying in place) onsite offsite. If offsite, name of facility | | |
| | | Received 55 Hobbs |
| hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above described phosphalate tank has been/will be constructed or closed according to NMOCD guidelines [], a general permit [], or an (attached) alternative OCD approved plan []. I finited Name/Title DUS [| | |
| pproval: rinted Name/Title CHRIS WILLIAMS DIST. SURV. Signature Chies Ulliams. Date: 12/28/06 | | |

SURFACE PIT CLOSURE PLAN

PIT PARAMETERS

COMPANY: EOG Resources Inc.

WELL SITE: Cimarron 18 State #3

LEGAL DESCRIPTION: Unit G Sec 18 T18s R34e, 1650

FNL 1650 FEL, Lea co.

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 150' X 150' X 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 2200 yards. The burial cell is to be excavated and lined with a minimum 12 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cuttings will be loaded as to allow for > 36" freeboard to ground level. After the cuttings are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the edge of the burial cell. This cap will be constructed as to slope and allow for water runoff from burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed

mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.