<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe

Form C-144 June 1, 2004

office

Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes \( \subseteq \) No \( \subseteq \)

Type of action: Registration of a pit of	or below-grade tank \(\subseteq\) Closure of a pit or below-grade	le tank 🛛
Operator: B. C. Operating, Inc. Telephone: (432) 683-2950 e-mail address: kwidner@usaonline.net		
Address: P. O. Box 50820 Midland, TX 79710		
Facility or well name: Angell #1 API #: 30-0	25-37902 U/L or Qtr/Qtr <u>A</u>	Sec <u>11</u> T <u>17S</u> R <u>36E</u>
County: <u>Lea</u> Latitude	676,233,4 Longitude 811,736.8	NAD: 1927 ☑ 1983 ☐
Surface Owner: Federal  State Private  Indian		
Pit	Below-grade tank	18 A 16
Type: Drilling   Production   Disposal	Volume:bbl Type of fluid:	TAN SAN TAN SA
Workover ☐ Emergency ☐	Construction material:	
Lined 🛛 Unlined 🗌	Double-walled, with leak detection? Yes  If not, explain vity not.	
Liner type: Synthetic A Thickness 14 mil Clay		
Pit Volume 24,000bbl		Sec 11 T 17S R 36E  NAD: 1927 ☑ 1983 □  explain way not.  (20 points) XXX  (20 points) XXX
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points) (20 points)
high water elevation of ground water.) 5	50 feet or more, but less than 100 feet	(10 points) XXX
man valor clovation of ground valors,	100 feet or more	( 0 points)
77 W 1 200 C 4 C 200 C 200 C 4 C 200 C	Yes	(20 points)
Wellhead protection area: (Less than 200 feet from a private domestic	No	( 0 points) XXX
water source, or less than 1000 feet from all other water sources.)		
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	( 0 points) XXX
	Ranking Score (Total Points)	10 Points
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite offsite offsite, name of facility Sundance Disposal (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No offsite offsite, show depth below ground surface ft. and attach sample results.		
(5) Attach soil sample results and a diagram of sample locations and excavations.		
Additional Comments: Excess water will be removed. All drilling mud and liner will be excavated and hauled to Sundance Disposal. 5 bottom sample points will be analyzed		
After the pit contents are removed. The excavation will be backfilled with clean native soil. A closure report will be submitted at the end of the job.		
Work will begin on 1-11-07. NMOCD will be notified 48 hrs before any sampling.		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan .  Date:		
Approval:  Printed Name/Title L. JOHNSON - ENVIRGENER Signature Date: 1.12.07		