

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144
June 1, 2004

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes No


Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank

Operator: Cemarex Energy Telephone: (505) 628-3447 e-mail address: dorcy.rogers@adl.com
Address: 7101 Occois Rd. Carlsbad N.M. 88240
Facility or well name: Pipeline Deep D² API# 30-025-37194 U/L or Q/L or E E Sec 17 T 19S R 34C
County: Lea Co. Latitude 32°39'48.6" Longitude 103°35'41.6" NAD: 1927 1983
Surface Owner: Federal State Private Indian

Pit Type: Drilling <input type="checkbox"/> Production <input checked="" type="checkbox"/> Disposal <input type="checkbox"/> Workover <input type="checkbox"/> Emergency <input type="checkbox"/> Lined <input type="checkbox"/> Unlined <input type="checkbox"/> Liner type: Synthetic <input checked="" type="checkbox"/> Thickness <u>12</u> mil Clay <input type="checkbox"/> Pit Volume _____ bbl	Below-grade tank Volume: _____ bbl Type of fluid: _____ Construction material: _____ Double-walled, with leak detection? Yes <input type="checkbox"/> If not, explain why not: _____									
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	<table border="1"> <tr> <td>Less than 50 feet</td> <td>(20 points)</td> <td><u>150-200'</u></td> </tr> <tr> <td>50 feet or more, but less than 100 feet</td> <td>(10 points)</td> <td></td> </tr> <tr> <td><u>100 feet or more</u></td> <td>(0 points)</td> <td><u>0</u></td> </tr> </table>	Less than 50 feet	(20 points)	<u>150-200'</u>	50 feet or more, but less than 100 feet	(10 points)		<u>100 feet or more</u>	(0 points)	<u>0</u>
Less than 50 feet	(20 points)	<u>150-200'</u>								
50 feet or more, but less than 100 feet	(10 points)									
<u>100 feet or more</u>	(0 points)	<u>0</u>								
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	<table border="1"> <tr> <td>Yes</td> <td>(20 points)</td> <td></td> </tr> <tr> <td><u>No</u></td> <td>(0 points)</td> <td><u>0</u></td> </tr> </table>	Yes	(20 points)		<u>No</u>	(0 points)	<u>0</u>			
Yes	(20 points)									
<u>No</u>	(0 points)	<u>0</u>								
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	<table border="1"> <tr> <td>Less than 200 feet</td> <td>(20 points)</td> <td></td> </tr> <tr> <td>200 feet or more, but less than 1000 feet</td> <td>(10 points)</td> <td></td> </tr> <tr> <td><u>1000 feet or more</u></td> <td>(0 points)</td> <td><u>0</u></td> </tr> </table>	Less than 200 feet	(20 points)		200 feet or more, but less than 1000 feet	(10 points)		<u>1000 feet or more</u>	(0 points)	<u>0</u>
Less than 200 feet	(20 points)									
200 feet or more, but less than 1000 feet	(10 points)									
<u>1000 feet or more</u>	(0 points)	<u>0</u>								
Ranking Score (Total Points)		<u>0</u>								

If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if you are burying in place) onsite offsite If offsite, name of facility: _____ (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No Yes If yes, show depth below ground surface _____ ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations.

Additional Comments:
see attached work plan.



I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan

Date: 2/2/07
Printed Name/Title: Dorcy Rogers Dorcy Rogers Signature: [Signature]
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.

Approval:
Printed Name/Title: L. JOHNSON ENVIRO ENGR Signature: [Signature] Date: 1/5/07

New Mexico Environmental Services

Hobbs, New Mexico

Reserve Pit Remediation

SURFACE PIT CLOSURE PLAN

PIT PARAMETERS

COMPANY: Cimerex Energy.

WELL SITE: Pipeline Deep 17 Fed. #2

LEGAL DESCRIPTION: Sec.17,T19s,R34e

LAT:N32*39'48.6"LONG:W103*35'14.6"

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 120'x 120'x 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 1500 yards. The burial cell is to be excavated and lined with a 20 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cutting will be loaded as to allow for >36" freeboard to ground level. After the cutting are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the edge of the burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.

Cemarex Pipeline Deep 17 feet # 2
 1450' fuel & 1200' fuel unit E sec. 17, T19S, R34E.
 Ape# 30-025-37194 Lee Co. n.m.
 N. 32° 39' 48.6" W 103° 35' 14.6"

Go west on 600 W to 96 W and turn north on
 96 W to 081-09 W and turn east on 081-09 W to 081-09 W

Carlsbad

Hobbs

Smith Ranch Rd for 2m

mm76

Turn East for 2m.

Turn North for 1.7m

Turn East for .8 to
 location.

