

Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

May 27, 2004

WELL API NO.

3002501302

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Aztec State

8. Well Number 12

9. OGRID Number

227001

10. Pool name or Wildcat

Maljamar GB & SA

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Latigo Petroleum Inc.

3. Address of Operator

P.O. Box 10304 Midland, Texas 79702

4. Well Location

Unit Letter **B** : 660' feet from the North line and 1980' feet from the East line  
Section 7 Township 17S Range 33E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4217' GL

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type Steel Depth to Groundwater 173 Distance from nearest fresh water well 1000 Distance from nearest surface water 7100

Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:


REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 1) 5 1/2" Csg. set at 4152' O.H. to 4415'.
- 2) Set C&I.B.P. at 4100' & cap w/ 15 sx of cement.
- 3) Perforate Csg. at 3100', sqz Perforation w/ 40 sx of cement.
- 4) Tag TOC at 3000'.
- 5) Perforate Csg. at 1500', sqz Perforations w/ 40 sx of cement
- 6) Tag TOC at 1400'.
- 7) Cut Csg. at 1100', POOH w/ Csg.
- 8) Spot 60 sx Plug in & out of Csg. Stub.
- 9) Perforate 85/8" Csg. at 320', sqz Perf. 125 sx of cement.
- 10) Leave hole full of cement to Surface.
- 11) Cut off wellhead & install Dry Hole Marker.

ESTIMATED 24 HOURS PRIOR TO THE  
BEGINNING OF PLUGGING OPERATIONS.



I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE

*Howard Boatright*  
Howard Boatright

TITLE Agent

DATE 1/25/07

Type or print name

432-617-0208  
Telephone No.

For State Use Only

OC FIELD REPRESENTATIVE II/STAFF MANAGER

APPROVED BY:

*Hayden Wink*

TITLE

DATE FEB 05 2007

Conditions of Approval (if any):

# Aztec State #12 Lea Co New Mex

