<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II

1000 Rio Brazos Road, Aztac, NM 87410

District IV

1000 Rio Brazos Road, Aztac, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico **Energy Minerals and Natural Resources**

For drilling and production facilities, submit appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr.

Santa Fe, NM 87505

Pit or Below-Grade Tank Registration of Closure  Is pit or below-grade tank covered by a "general plan"? Yes No Type of action: Registration of a pit or below-grade tank. Closure of a pit or below-grade tank.		
Operator: CPmorex Energy Telephone (505) 628-34476-mil address: dorsy rights @ Ad. Com		
Address: 7101 Acros Rd. Corlsbook (	1.m. 88240	See 6 T 195 R 34e
Facility or well name: Proc Cone B 6 feed #3 API #: 30-025-380H5 WL or Qui/Qur f See 6 T 195 R 34 c  County: 60 Letitude 32041 26.5" Longitude 103 36 06.3" NAD: 1927 1983		
	3,3°41 26.5 Longitude /03	36 06.3 NAD: 1927 [] 1943 []
Surface Owner: Federal State Private Indian		
Pit /	Bolow-stude tank	
Type: Drilling Production Disposal D	Volume:bbl Type of fluid:	
Workover Emergency	Construction material:	
Lined [] Unlined []	Double-walled, with lask detection? Yes [] If not, explain why not.	
Liner type: Synthetic Thickness 12 mil Clay		
Pit Volume bbl		
	Loss than 50 foot	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)
high water elevation of ground water.)	100 feet or more	( 0 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes	(20 points)
	No.	( O points)
	Loss than 200 feet	(20 points)
Distance to surface water: (herizontal distance to all wetlands, playas,	200 first or more, but less than 1000 feet	(10 points)
irrigation canala, ditches, and percensial and ephemeral watercourses.)	1000 first or more	( O points)
	Ranking Score (Total Points)	0
If this is a nit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the ensite box if		
your are hurring in place) queste [7] offician [7] If offician remote of facility (3) Attach a consult description of consults action taken including		
remediation start date and end date. (4) Groundwater encountered: No [] Yes [] If yes, show depth below ground surface fit and attack encountered.		
(5) Affects and comple made and a finance of complete locations and manufacture		
Additional Comments:		CACAGE MINING
Seo F	thacked unch	12 Can 1911
g fill ived &		
P Receive &		
		House
		\c\c_
		·c/ <sub>10168199</sub>
I hereby certify that the information above is true and complete to the best	of any knowledge and heliaf. I further curtify that the	te above described pit or below or ale track
has been/will be constructed or closed according to NMOCD guidelines . a general permit . er an (attached) alternative OCD-approved plan .		
Date: Date:		
Printed Name/Title Signature Signature		
Your certification and NMOCD approval of this application/closure data not soliton the quantum of limbility should the content of the pit or tenk contentiants ground water or		
otherwise endanger public health or the environment. Nor door it sellege the operator of its responsibility for compliance with any other federal, state, or heal lowe and/or regulations.		
Approval: Printed Name/Title CHPIS WILLIAMS   DIST. SUF	V some Phin Illellian	2 Date: 2/22/07

P.O. Box 310 Hobbs, NM 88241-0310

## New Mexic Environmental Services Hobbs. New Mexico 505.392.8584 Cell 505.631.2442 505.392.3085

**Hobbs, New Mexico** 

Reserve Pit Remediation

## SURFACE PIT CLOSURE PLAN

## PIT PARAMETERS

**COMPANY: Cimerex Energy.** 

WELL SITE: Pipeline B 6 Fed. #3

LEGAL DESCRIPTION: Sec.6,T19s,R34e LAT:N32\*41'26.5"LONG:W103\*36'06.3"

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 120'x 120'x 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 1500 yards. The burial cell is to be excavated and lined with a 20 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cutting will be loaded as to allow for >36" freeboard to ground level. After the cutting are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the edge of the burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.

Cenarex Pepalene B 6 fed #3 2310' fal & 1980 foot walt f, Sec. 6-T195-R34e Apr+ 30-025-38045 Lea Co. n.m N 32°41'26.5" W103° 36'06.3" 1-Cell 2007071138 Smith Romen Roll for 2m Go west on 63-180 to mark and turn north on smeth Rance rol. Turn M. for 36 m.