District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office. For downstream facilities, submit to Santa Fo office

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes No Type of action: Registration of a pit or below-grade tank Colome of a pit or below-grade tank C

Λ-					
Operator: CPmarex Energy Telephone (505) 628-3447 and address: dorrungers to Ad. Com Address: 7101 North Rd. Corlsbad N.M. 88240 Facility or well name: Procline B 18 fed #7 AFT #: 30-005-38048 U/L or Quirter E Sec 18 T 195 R 34e					
			County: (00, Latitude	32° 39'45.1" In 103	°36' 23.2" NAD: 1927 □ 1983 □
			Surface Owner: Federal State Private Indian		
Pit	Balow-grade tank				
Type: Drilling Production Disposal D	Volume:bbl Type of fluid:				
Workover C Emergency C	Construction material:				
Lined [] Unlined []	Double-walled, with leak detection? Yes [] If not, explain why not.				
Liner type: Synthetic [] Thickness / 2 mil Clay []					
Pit Volume bbl					
	Long them 50 feet	(20 points)			
Depth to ground water (vertical distance from bottom of pit to seasonal					
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)			
	100 feet or more	(0 points)			
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)			
•		(O points)			
water source, or less than 1000 feet from all other water sources.)					
Distance to surface water: (horizontal distance to all wetlands, player,	Loss than 200 feet	(20 points)			
irrigation canals, ditches, and percential and ephemeral watercourses.)	200 first or more, but less than 1000 fost	(10 points)			
	1000 feet or more	(0 points)			
	Ranking Score (Total Points)	-			
If this is a nit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the easite box if					
your are burying in place) casile 🗌 offsite 🗀 If offsite, name of facility					
remediation start date and end date. (4) Groundwater encountered: No [] Yes [] If yes, show depth below ground surfaceft. and attach sample results.					
(5) Attach soil sample results and a diagram of sample locations and encous	dions.				
Additional Comments:					
See Attacked unch don't					
(2) red 2007 9					
		CED MINI E			
		© FEB 2001			
		Received &			
Thereby certify that the information above is tree and consolute to the base		Received &			
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guidelies		Received & Nobbs & OSD			
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline		Received & Nobbs & OSD			
		Received & Nobbs & OSD			
has been/will be constructed or closed according to NMOCD guideline		Received & Nobbs & OSD			
has been/will be constructed or closed according to NMOCD guidelies Date: Printed Name/Title: Your certification and NMOCD approval of the application/closure.	Signature	the above date they pit or below gradetalk native OCD approved they 799 970			
has been/will be constructed or closed according to NMOCD guideline Date: Printed Name/l'itle Your certification and NMOCD approval of this application/closure date otherwise endanger public health or the environment. Nor does it stilled.	Signature	the above date they pit or below gradetalk native OCD approved they 799 970			
has been/will be constructed or closed according to NMOCD guideline Date: Printed Name/Title: Your certification and NMOCD approval of the application/closure.	Signature	the above date they pit or below gradetalk native OCD approved they 799 970			
has been/will be constructed or closed according to NMOCD guideline. Date: Printed Name/Title Your certification and NMOCD approval of this application/closure data otherwise endanger public health or the carriemment. Nor does it said or regulations.	Signature	the above date they pit or below gradetalk native OCD approved they 799 970			
has been/will be constructed or closed according to NMOCD guidelies Date: Printed Name/Title: Your certification and NMOCD approval of the application/closure date otherwise endanger public health or the environment. Nor does it suffice regulations. Approval:	Signature Signature of liability should the contents operator of its sequentiality for compliance with	The shore-described pit or below-grad-thank stative OCD-apper and Abril 799 V Company of the pit or tank contaminate ground water or a pay other federal, state, or local laws and/or			
has been/will be constructed or closed according to NMOCD guideline. Date: Printed Name/Title Your certification and NMOCD approval of this application/closure data otherwise endanger public health or the carriemment. Nor does it said or regulations.	Signature Signature of liability should the control for operator of its responsibility for compliance with	Received Habbs Habbs OCD approximately 87997 and the pit or tank contaminate ground water or any other federal, state, or local laws and/or			

P.O. Box 310 New Mexic Hobbs, NM 88241-0310

Environmental Services 505.392.8584 Cell 505.631.2442 505.392.3085

Hobbs, New Mexico

Reserve Pit Remediation

SURFACE PIT CLOSURE PLAN

PIT PARAMETERS

COMPANY: Cimerex Energy.

WELL SITE: Pipeline B 18 Fed. #7

LEGAL DESCRIPTION: Sec. 18, T19s, R34e LAT:N32*39'45.1"LONG:W103*36'23.2"

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 120'x 120'x 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 1500 yards. The burial cell is to be excavated and lined with a 20 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cutting will be loaded as to allow for >36" freeboard to ground level. After the cutting are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the edge of the burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.

Consiex Pépelere B 18 fed #7 1980 fol & 510' fool Unit E, See. 18 - T 195- RSHe Apr # 30-025-38048 ba Co. n.m. N 32°39'45.1" W103° 36'23.2" 1-Call # 2007071135 To west on 63-180 to mm 76. Smeth Raver Ral. Ranch Rd. North for 2m |