Submit 3 Copies To Appropriate District  Office •  St	ate of New Mexico	Form C-103
District I Energy, Mi	nerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
District II 1301 W. Grand Ave., Artesia, NM 88210 OIL CON	ISERVATION DIVISION	30-041-20919 5 Indicate Type of Leges
District III 1220	South St. Francis Dr.	5. Indicate Type of Lease  STATE ☐ FEE ☒
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Sa	nta Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		0. 51410 67 64 646 25450 7 6.
SUNDRY NOTICES AND REPO	RTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		PETERSON
1. Type of Well: Oil Well Gas Well Other		8. Well Number
2. Name of Operator		9. OGRID Number
LYNX OPERATING CO., INC.		175071
3. Address of Operator 505 N. BIG SPRING ST., STE 604		10. Pool name or Wildcat PETERSON; FUSSELMAN
4. Well Location		
Unit LetterH:_2000feet	from theNorth line and	
	nship 5-S Range 33-E	NMPM County Roosevelt
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		
Pit or Below-grade Tank Application □ or Closure □	4420 GR	
Pit typeDepth to GroundwaterDistance	from nearest fresh water well Dis	stance from nearest surface water
Pit Liner Thickness: mil Below-Grade T	ank: Volumebbls; C	onstruction Material
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO		
NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK REMEDIAL WORK ALTERING CASING		
PERFORM REMEDIAL WORK  PLUG AND ABANDON  REMEDIAL WORK  ALTERING CASING  TEMPORARILY ABANDON  CHANGE PLANS  COMMENCE DRILLING OPNS. PAND A		
PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEMENT JOB		
_	_	
OTHER:  OTHER:  OTHER:  OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
		ttach wellbore diagram of proposed completion
2/2/06 TD at 8085 ft.		
2/3/06 Ran 142 jts 5-1/2", 15.5 & 17.0 lb/ft, J-55, LT&C, new casing & set at 8058.80'. Ran 23 centralizers. cemented with 420 sx Class "H" 35:65 Poz with 6% gel, ¼ lb/sx cello seal, 5 lb/sx LCM-1 & 0.5% FL-52 (mixed at 12.5		
		LCM-1, 0.3% FL-25 & 1% FL-62 (mixed at 12.5
		BBL/min. Bumped plug to 2058 psi. Plug
		s. Held ok. RD BJ. ND BOP & set slips. Jet
pits. Released rig @ 12:00 AM 02/03	_	
<b>1 1 1 1 1 1 1 1 1 1</b>	<0.4.0	21222324252623
2/7/06 Ran GR/CCL/CBL. Top of cement 4	694 ft.	(3 <sup>2</sup> ) (8)
		₹ <b>%</b> %
		8 7
		No.
		110168 19646
I hereby certify that the information above is true and o	complete to the best of my knowledge	ge and belief. I further certify that any nit or below-
and talk has been fall to the state of the s		
SIGNATURE Larry M. Lordon E. mail	TITLE_Vice President	DATE 1/7/2007
SIGNATURE TITLE Vice President DATE 1/7/2007  Type or print name Jerry M. Jordan E-mail address: Telephone No. ANACOS 0687-0084  For State Use Only APPROVED BY: DATE TITLE SUPERVISOR/GENERAL NOTE DATE  DATE DATE  DATE  TITLE SUPERVISOR/GENERAL NOTE DATE  DATE  DATE		
APPROVED BY: Chis Welliams	TITLE TRICT SUPERVISOR	DATE
Conditions of Approval (if any):	OC Disting.	FEB 2 3 2007