

Templar State #11,680' FNL, 1,980' FEL Sec 17, 21S, 35E, Eddy County, NM
API # 30 - 025 - 38015-0

Elev: 3634', KB: 19' AG

Current

9-5/8" TOC @ 800' by TS

13-3/8", 48#, J-55 @ 1425'
cement circulated sxs NA
17-1/2" hole

DV Tool @ 3790

9-5/8", 40#, N-80 LTC @ 6232'
3540 sxs, cement 1st stage
1250 sxs 2nd stage
12-1/4" hole

DV Tool @ 8400'

5-1/2", 17#, P-110 0'- 12,450'
LTC1st stage 830 sxs
2nd stage 610 sxs
7-7/8" holePBTD @ 12,366' SL
TD @ 12,450' SL

DESCRIPTION	ID	OD	Length	Depth
1 ft 2-7/8" tbg	2.440	3.688	32.00	
6' tbg sub	2.440	3.688	6'	32.00
382 fts tbg	2.440	3.688	11830.00	38.00
6' locator sub	2.440	3.688	6'	11868.00
2 fts tbg	2.440	3.688	64.00	11874.20
2.25 FN	2.250	4.500	1.82	11938.20
Baker Hornet plr	2.375	4.600	7.80	11940.00
10' sub	2.440	3.688	10.00	11947.80
2.25 FN	2.250	3.888	1.00	11957.80
10' sub	2.440	3.688	10'	11958.00
2.25 RM	2.197	3.888	1.10	11968.80
1 ft 2-7/8" tbg	2.440	3.688	32.00	11968.90
Ported under balance sub	2.440	3.688	0.95	12001.00
1 ft 2-7/8" tbg	2.440	3.688	31.00	12002.00
Mech FH w/AR	1.500	3.690	2.00	12033.00
EOT				12035.00

Morrow Perfs
12,038-12,050
6spf 60 deg phasing 66 holesCIBP @ 12,310' no cmt
12,326-12,328
6 spf 60 deg phasing 12 holes