District II 1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION 5. Indicate Type of Lease	May 27, 2004 1-10050
District II 1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION 5. Indicate Type of Lease	1-10050
1301 W. Gland Ave., Altesia, IVM 60210	
District III 1220 South St. Francis Dr. STATE F.	EE 🛚
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505 6. State Oil & Gas Lease N	
1220 S. St. Francis Dr., Santa Fe, NM 87505	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH 7. Lease Name or Unit Age MILNESAND UNIT	reement Name
PROPOSALS.) 1. Type of Well: Oil Well X Gas Well Other 8. Well Number 137	
2. Name of Operator 9. OGRID Number	
THOMPSON, J. CLEO	
3. Address of Operator P.O. BOX 12577 ODESSA, TX 79768 OCD-ARTESIA MILNESAND (SAN AN	DRES)
4. Well Location	DRES)
Unit Letter I : 1980 feet from the SOUTH line and 660 feet from the EAST line	
Section 7 Township T8S Range R35E NMPM CountyROOSEVELT	
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	
Pit or Below-grade Tank Application or Closure	
Pit type Depth to GroundwaterDistance from nearest fresh water wellDistance from nearest surface water	
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A	
PULL OR ALTER CASING	
OTHER:	П
13 Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, include	ing estimated date
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
2/9/07 MIRU RIG & EQUIPMENT 2/15/07 RIH WITH WIRELINE, TAG PLUG @ 4525'. DUMP BAIL 3 SX ON TOP. PERF CASING @ 2750'. RIH JOINTS TBG. SDFN	WITH 63
2/16/07 RIH TO 2600', SET PACKER & SQZ 80 SX CLASS C CEMENT. WOC 4 HRS. TAG PLUG @ 2625'. PU. 2100'. PERF CSG TO 2250'. SET PACKER AND SQZ 80 CLASS CEMENT. WOC OVERNIGHT.	LL UP TO
2/19/07 TAG PLUG @ 2134'. LAY DOWN TBG, PERF CSG @ 473'. PUMP 160 SX CLASS "C" CEMENT DOWN 5/8 TO SURFACE. LEAVE CEMENT AT SURFACE IN 4 1/2". CUT OFF	N 4 1/2 AND 8
WELLHEAD AND INSTALL DRY HOLE MARKER. RIG DOWN AND CLEAN LOCATION.	north Control of the
Approved as to plugging of the Well Bore.	
Liability under bond is retained until	<u> </u>
surface restoration is completed.	De la
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been will be constructed or closed according to NMOCD guidelines \boxtimes , a general permit \square or an (attached) alternative OCD-approved plan \square .	
	06/26/2007
Type or print name VONDA FREEMAN E-mail address:vfreeman@jcleo.com Telephone For State Use Only	No. (432)550-8887
APPROVED BY: Yang W. Wink TITLE DATE Conditions of Approval (if any): Output Date	JUL 1 2 200