Submit 3 Copies To Appropriate District Office District I	State of New Mexico Energy, Minerals and Natural Resources		Form C-103 May 27, 2004			
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u>	OIL CONSERVATION DIVISION		WELL API NO. 30-025-29889			
1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.		5. Indicate Type of Lease STATE FEE			
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa Fe, NM 87505		6. State Oil & Gas Lease No. LG-8962			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			7. Lease Name or Unit Agreement Name Tex-Gulf AEN State			
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other			8. Well Number 1-Y			
Name of Operator Yates Petroleum Corporation			9. OGRID Number 025575			
3. Address of Operator			10. Pool name or Wildcat			
105 S. 4 th Street, Artesia, NM 88210			Sanmal-Queen			
4. Well Location Unit Letter P: 990 feet from the South line and 330 feet from the East line						
Section 2		ange 33E	NMPM	Lea County		
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4155' GR						
Pit or Below-grade Tank Application						
Pit type <u>Steel</u> Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water						
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material						
12. Check	Appropriate Box to Indicate 1	Nature of Notice,	Report or Otl	her Data		
NOTICE OF IN PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	CHANGE PLANS	SUBS REMEDIAL WORK COMMENCE DRING CASING/CEMENT	K [LLING OPNS.[REPORT OF: ALTERING CASI P & A	NG □	
OTHER:		OTHER:				
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions. BE NOTIFIED 24 HOURS PRIOR BEGINNING OF PLUGGING OPE. Yates Petroleum Corporation plans to plug and abandon this well as follows:						
 Set a CIBP at 3700' with 35' cement on top. Perforate sqeeze holes at 1597'. Circulate hole with mud laden fluid. Set a 100' cement plug from 1597'-1497', inside and outside the casing. WOC and tag. 						
3. Spot a 10 sx cement plug at surface. A Install dry hole marker and alean legation.						
JSPOT 100 PEMBUT PLUG F7 400-300 (FRESH WATER PLUG)						
- John Committee						
NOTE: Yates Petroleum Corporation will use steel pits and no earth pits Region 18 18 18 18 18 18 18 18 18 18 18 18 18						
I hereby certify that the information above is true and complete to the best of my knowledge and believe further certify that any pit or below-						
grade tank has been/will be constructed of closed according to NMOCD guidelines , a general permit or an office of alternative OCD-approved plan .						
SIGNATURE ()	ritle Res	gulatory Compliance	Supervisor	DATE March 27, 2	2007	
Type or print name Tina Huer	ta E-mail address:	tinah@ypcnm.co	om Telephon	ne No. <u>505-748-147</u>	1	
For State Use Only APPROVED BY Conditions of Approval (if my): E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471 DATE 3 0 2007						
APPROVED BY Conditions of Approval (if my):	WIND TITLE	RESENTATIVE IVS	• • •	<u> </u>	97	

Casing Program Well Name: Tex-Gulf AEN State No. 1-Y Field: Sanmal Size/Wt/Grade/Conn Location: 990' FSL & 330' FEL Sec. 2-17S-33E Lea Co, NM Depth Set GL: 4155.1' Zero: _____AGL: _____ KB: 4163.6' 8 5/8" 24# J55 1547' Spud Date: 4-9-87 Completion Date: 5 1/2" 15.5# J55 3900' Comments: **CURRENT CONFIGURATION** 8 5/8" csg @ 1547'. Cmtd w/ 700 sx. Cmt circ. TOPS: Rustler 1512' Salado 1626' 2622' Tansill 2814' Yates 2912' 7 Rivers 3748' Queen TOC 2961' by CBL Queen perfs 3768-73' 5 1/2" csg @ 3900'. Cmtd w/ 250 sx.

SKETCH NOT TO SCALE

TD 3900' PBTD 3820'

DATE: 12/18/03

Casing Program				
Size/Wt/Grade/Conn	Depth Set			
8 5/8" 24# J55	1547'			
5 1/2" 15.5# J55	3900'			

10 sack cement plug at surface.

PROPOSED CONFIGURATION

 $8\,5/8"$ csg @ 1547'. Cmtd w/ 700 sx. Cmt circ. Perforate @ 1597'. Place 100' cement plug inside and outside casing from 1597'-1497'

TOPS:
Rustler 1512'
Salado 1626'
Tansill 2622'
Yates 2814'
7 Rivers 2912'
Queen 3748'

TOC 2961' by CBL

CIBP @ 3700' + 35' cement

TD 3900' PBTD 3820' Queen perfs 3768-73'

5 1/2" csg @ 3900'. Cmtd w/ 250 sx.

DATE: 12/18/03

SKETCH NOT TO SCALE