| Submit 3 Copies To Appropriate District Office State of New Mexico | Form C-103 |
|--|---|
| District I Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240 | Revised May 08, 2003 WELL API NO. |
| District II 1301 W. Grand Avc., Artesia, NM 88210 OIL CONSERVATION DIVISION | 30-025-36255 |
| District III 1220 South St. Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 | 5. Indicate Type of Lease STATE FEE |
| District IV Santa Fe, NM 8/505 | 6. State Oil & Gas Lease No. |
| 1220 S. St. Francis Dr., Santa Fe, NM 87505 | |
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A | 7. Lease Name or Unit Agreement Name |
| DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH | Laguna Deep Unit |
| PROPOSALS.) 1. Type of Well: | 8. Well Number |
| Oil Well Gas Well Other | 007 |
| 2. Name of Operator Matador Operating Company | 9. OGRID Number 14245 |
| 3. Address of Operator 8340 Meadow Road #150, Dallas, TX 75231 | 10. Pool name or Wildcat Gem; Morrow, East (Gas) |
| 4. Well Location | |
| Unit Letter E: 1980 feet from the North line and 950 feet from the West line | |
| Section 36 Township 19S Range 33E | NMPM County Lea |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3590 GR | |
| 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data | |
| | UBSEQUENT REPORT OF: |
| PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL W | ORK ALTERING CASING |
| TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT | |
| PULL OR ALTER CASING MULTIPLE CASING TES COMPLETION CEMENT JOI | |
| OTHER: OTHER: | |
| 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. | |
| 7-29-03 RAN 317 JOINTS OF 5 1/2" 20.0 # P-110 LT&C CSG. TOTAL PIPE = 13,639.92' SET AT 13,617'. SHOE JOINT = 45.06'. TOP OF COLLAR AT 13,571.94'. TOP OF DV TOOL = 8,787' RIG DN CSG CREW; | |
| CIRC CSG; CMT 1ST STAGE WITH 275 SX OF INTERFILL "H" (11.9 PPG, 2.45 FT3/SACK, 14.12 GPS) & | |
| 500 SACKS OF SUPER "H" MODIFIED W/ 0.4% CFR-3, 0.5%HALAD-344, 0.3% HR7, 1 PPS SALT (13.0 PPG, 1.66 FT3/SACK, 8.69 GPS) / FULL RETURNS THROUGHOUT, BUMPED PLUG W/ 2010 PSI - 500 PSI OVER | |
| FCP, FLOATS HELD. CMT SECOND STAGE WITH 750 SX OF INTERFILL "H" (11.9 PP, 2.45 FT3/SX, 14.12 | |
| GPS) AND 100 SX OF PREMIUM "H" - NEAT (15.6 PPG, 1.17 FT3/SX, 5.22 GPS). FULL RETURNS | |
| THROUGHOUT - BUMPED PLUG AND CLOSED DV TOOL W/ 3,130 PSI OVER 1,770 PSI FCP - HELD RELEASE RIG @ 15:00 ON 07/30/2003 | |
| | · · |
| | |
| **As information - Tom Brown, Inc. (023230) took over operations 7/1/0 | 3. Currently WO Op Change from OCD ** |
| I hereby certify that the information above is true and complete to the best of my knowledge and belief. | |
| Pagulatan Pan | |
| M. Alband | |
| (This space for State use) | |
| APPPROVED BY January OC FIELD REPRESENTATIVE II/STAFF MANAGER TITLE DATE P 1 1 2003 Conditions of approval, if any: | |
| Conditions of approval, it airy. | |

٠..