Office Submit 3 Copies To Appropriate District	State of New Me			Form C-103
District I	Energy, Minerals and Natu	ral Resources		May 27, 2004
1625 N. French Dr., Hobbs, NM 88240	A		WELL API NO.	
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION		30-025-05244	
District III	1220 South St. Francis Dr.		5. Indicate Type of	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		STATE STATE FEE 6. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM 87505	. ,= :		E-2344	Lease IV.
	CES AND REPORTS ON WELLS		7. Lease Name or	Unit Agreement Name
	SALS TO DRILL OR TO DEEPEN OR PLU CATION FOR PERMIT" (FORM C-101) FO		State "A"	
1. Type of Well: Oil Well	Gas Well Other		8. Well Number	1
2. Name of Operator Saber Resources, LLC			9. OGRID Number	er 236378
3. Address of Operator			10. Pool name or	Wildcat
400 W. Illinois - Suite 950 - Midle	and, Tx., 79701		Denton - Devoniar	
4. Well Location	MATA.			
1	:1980feet from the	_South li	ne and660	feet from the
Westline		_		
Section 2	Township 15 S 11. Elevation (Show whether DR,		NMPM	Lea County
	11. Elevation (Snow whether DR, 3820' DF	KKB, RI, GK, etc.)		
Pit or Below-grade Tank Application 🗆 c				· · · · · · · · · · · · · · · · · · ·
Pit typeDepth to Groundw	aterDistance from nearest fresh w	arer well Dista	nce from neurost surfa	ce water
Pit Liner Thickness: mil	Below-Grade Tank: Volume	bble; Con	Struction Material	
12. Check A	Appropriate Box to Indicate Na	ature of Notice, F	Report or Other I	Data
NOTICE OF IN	TENTION TO:	elibe	COLCUT DEC	ソヘロエ ヘに
NOTICE OF IN			SEQUENT REF	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK		ALTERING CASING 🔲
PERFORM REMEDIAL WORK TEMPORARILY ABANDON		REMEDIAL WORK	. ⊠ / LING OPNS.□ I	ALTERING CASING 🔲
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT	LING OPNS.	ALTERING CASING P AND A
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze	LING OPNS. I	ALTERING CASING ☐ P AND A ☐
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING OTHER: 13. Describe proposed or compost of starting any proposed we	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze pertinent details, and	LING OPNS.	ALTERING CASING P AND A S, including estimated date
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING OTHER:	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL Detect operations. (Clearly state all p	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze pertinent details, and	LING OPNS.	ALTERING CASING P AND A S, including estimated date
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compost of starting any proposed we or re-completion.	PLUG AND ABANDON CHANGE PLANS C	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze ertinent details, and e Completions: Atta	LING OPNS. JOB cmt cssg give pertinent dates tch wellbore diagran	ALTERING CASING P AND A S, including estimated date
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compostarting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the	PLUG AND ABANDON CHANGE PLANS C	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976'	LING OPNS. D JOB D cmt cssg give pertinent dates the wellbore diagram ch wellbore diagram	ALTERING CASING PAND A STATEMENT PAND A
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compostarting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—	PLUG AND ABANDON CHANGE PLANS C	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976'	LING OPNS. D JOB D cmt cssg give pertinent dates the wellbore diagram ch wellbore diagram	ALTERING CASING PAND A STATEMENT PAND A
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compof starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casin	PLUG AND ABANDON CHANGE PLANS C	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze ertinent details, and e Completions: Atta 1,416'; 9981'; 9976' Class "H" cement u	LING OPNS. D JOB D cmt cssg give pertinent dates the wellbore diagram ch wellbore diagram	ALTERING CASING PAND A STATEMENT PAND A
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING DULL OR ALTER CASING THER: 13. Describe proposed or compof starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casin 2/19/07-2/23/07 Drill out w/ a 4 5/8 2/27/07 Acidize Devonian OH intersections.	PLUG AND ABANDON CHANGE PLANS (Clearly state all park). SEE RULE 1103. For Multiple 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi – held good. bit from 12,500' to original TD of val (12,500' – 12,682') with 3000 grades of the square of the	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'.	LING OPNS. D JOB D cmt cssg give pertinent dates ich wellbore diagran '; & 9973'. inder a cement retain	ALTERING CASING PAND A Solution PAND A Solutio
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compostarting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casing 2/19/07-2/23/07 Drill out w/ a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF	PLUG AND ABANDON CHANGE PLANS (Clearly state all park). SEE RULE 1103. For Multiple 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi - held good. bit from 12,500' to original TD of val (12,500' - 12,682') with 3000 ge HCL acid.	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'. als of 15% NeFe HO	LING OPNS. D JOB D cmt cssg give pertinent dates ich wellbore diagran ch wellbore diagran	ALTERING CASING PAND A Solution PAND A Solutio
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compost of starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casing 2/19/07-2/23/07 Drill out w/ a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL Detect operations. (Clearly state all park). SEE RULE 1103. For Multiples 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi – held good. bit from 12,500' to original TD of val (12,500' – 12,682') with 3000 ge HCL acid. p holes (9981',9976', & 9973') leak	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'. als of 15% NoFe HC ting-squeeze broke of	LING OPNS. D JOB D cmt cssg give pertinent dates ich wellbore diagran '; & 9973'. inder a cement retain L' acid. Acidize De	ALTERING CASING PAND A Solution PAND A Solution Part and Part Part Part Part Part Part Part Part
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compost of starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casing 2/19/07-2/23/07 Drill out w/ a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks with the start of the	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL Detect operations. (Clearly state all park). SEE RULE 1103. For Multiples 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi – held good. bit from 12,500' to original TD of val (12,500' – 12,682') with 3000 ge HCL acid. p holes (9981',9976', & 9973') leak	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'. als of 15% NoFe HC ting-squeeze broke of	LING OPNS. D JOB D cmt cssg give pertinent dates ich wellbore diagran '; & 9973'. inder a cement retain L' acid. Acidize De	ALTERING CASING PAND A Solution PAND A Solution Part and Part Part Part Part Part Part Part Part
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compostarting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casing 2/19/07-2/23/07 Drill out w/ a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks wis squeeze held good.	PLUG AND ABANDON CHANGE PLANS C	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'. als of 15% NeFe HC sing-squeeze broke of tement. Drill out cere	LING OPNS. D JOB D cmt cssg give pertinent dates ich wellbore diagran ch wellbore diagran	ALTERING CASING PAND A Solution PAND A Solution Part Part (11,814' - 11,814'
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compost of starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casing 2/19/07-2/23/07 Drill out w/ a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks with the start of the	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL Detect operations. (Clearly state all park). SEE RULE 1103. For Multiples 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi – held good. bit from 12,500' to original TD of val (12,500' – 12,682') with 3000 ge HCL acid. pholes (9981',9976', & 9973') leak th 500 gals of Flowguard & 75 sxs onent – 343 jnts of 2 7/8" tubing with	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'. als of 15% NoFe HC completions: Drill out cert the 1750 bpd sub pur	LING OPNS. D JOB D cmt cssg give pertinent dates ich wellbore diagran '; & 9973'. Inder a cement retain L' acid. Acidize De down. Inder tetainer & cement retain ment retainer & cement ap. SN @ 10,942'.	ALTERING CASING PAND A Solution PAND A Solution Particular Particu
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compof starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casing 2/19/07-2/23/07 Drill out w/ a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks wis squeeze held good. 3/9/07 RIH with production equips	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL Detect operations. (Clearly state all park). SEE RULE 1103. For Multiples 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi – held good. bit from 12,500' to original TD of val (12,500' – 12,682') with 3000 ge HCL acid. pholes (9981',9976', & 9973') leak th 500 gals of Flowguard & 75 sxs onent – 343 jnts of 2 7/8" tubing with	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'. als of 15% NoFe HC completions: Drill out cert the 1750 bpd sub pur	LING OPNS. D JOB D cmt cssg give pertinent dates ich wellbore diagran '; & 9973'. Inder a cement retain L' acid. Acidize De down. Inder tetainer & cement retain ment retainer & cement ap. SN @ 10,942'.	ALTERING CASING PAND A Solution PAND A Solution Particular Particu
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING TOTHER: 13. Describe proposed or compost of starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casing 2/19/07-2/23/07 Drill out w/ a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks with squeeze held good. 3/9/07 RIH with production equipmed 4/20/07 RIH with cement retainer & 1/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL Detect operations. (Clearly state all park). SEE RULE 1103. For Multiples 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi – held good. bit from 12,500' to original TD of val (12,500' – 12,682') with 3000 ge HCL acid. pholes (9981',9976', & 9973') leak th 500 gals of Flowguard & 75 sxs onent – 343 jnts of 2 7/8" tubing with	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'. als of 15% NoFe HC completions: Drill out cert the 1750 bpd sub pur	LING OPNS. D JOB D cmt cssg give pertinent dates ich wellbore diagran '; & 9973'. Inder a cement retain L' acid. Acidize De down. Inder tetainer & cement retain ment retainer & cement ap. SN @ 10,942'.	ALTERING CASING PAND A Solution PAND A Solution Particular Particu
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compost of starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casing 2/19/07-2/23/07 Drill out w/a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks wis squeeze held good. 3/9/07 RIH with production equipm 4/20/07 RIH with cement retainer & squeeze. I hereby certify that the information	PLUG AND ABANDON CHANGE PLANS DIMENTIPLE COMPL DIMENTIPLE COMPL DIMENTAL SEE RULE 1103. For Multiple 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi — held good. bit from 12,500' to original TD of val (12,500' — 12,682') with 3000 ge HCL acid. pholes (9981',9976', & 9973') leak th 500 gals of Flowguard & 75 sxs of the casing (12,500') and the casing (13,500') and the casing (13,500') above is true and complete to the beside of the casing (13,500') above is true and complete to the beside of the casing (13,500') above is true and complete to the beside of the casing (13,500') above is true and complete to the beside of the casing (13,500') above is true and complete to the beside of the casing (13,500') and the casing (13,500') are the casing (13,500') and the casing (13,500') are the casing (13,500') a	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682', als of 15% NeFe HC completions: Attain 12,682', als of 15% NeFe HC	LING OPNS. D JOB D cmt cssg give pertinent dates the wellbore diagran ch wellbore diagran	ALTERING CASING PAND A STATEMENT PAND A
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compof starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casin 2/19/07-2/23/07 Drill out w/ a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks wis squeeze held good. 3/9/07 RIH with production equipm 4/20/07 RIH with cement retainer & squeeze.	PLUG AND ABANDON CHANGE PLANS DIMENTIPLE COMPL DIMENTIPLE COMPL DIMENTAL SEE RULE 1103. For Multiple 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi — held good. bit from 12,500' to original TD of val (12,500' — 12,682') with 3000 ge HCL acid. pholes (9981',9976', & 9973') leak th 500 gals of Flowguard & 75 sxs of the casing (12,500') and the casing (13,500') and the casing (13,500') above is true and complete to the beside of the casing (13,500') above is true and complete to the beside of the casing (13,500') above is true and complete to the beside of the casing (13,500') above is true and complete to the beside of the casing (13,500') above is true and complete to the beside of the casing (13,500') and the casing (13,500') are the casing (13,500') and the casing (13,500') are the casing (13,500') a	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682', als of 15% NeFe HC completions: Attain 12,682', als of 15% NeFe HC	LING OPNS. D JOB D cmt cssg give pertinent dates the wellbore diagran ch wellbore diagran	ALTERING CASING PAND A STATEMENT PAND A
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING THER: 13. Describe proposed or compost of starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casing 2/19/07-2/23/07 Drill out w/a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks wis squeeze held good. 3/9/07 RIH with production equipm 4/20/07 RIH with cement retainer & squeeze. I hereby certify that the information	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL leted operations. (Clearly state all park). SEE RULE 1103. For Multiple 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi - held good. "bit from 12,500' to original TD of val (12,500' - 12,682') with 3000 gie HCL acid. p holes (9981',9976', & 9973') leak th 500 gals of Flowguard & 75 sxs of the following state of the second case of the casing (all the casing (all the case) according to NMOCD guidelines.	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682', als of 15% NeFe HC completions: Attain 12,682', als of 15% NeFe HC	LING OPNS. D JOB D cmt cssg give pertinent dates ich wellbore diagran c; & 9973'. Inder a cement retain L acid. Acidize De down. Inder a cement retain pertinent dates diown. Inder a cement retain and belief. I further r an (attached) alternat	ALTERING CASING PAND A STATEMENT PAND A
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING DULL OR ALTER CASING THER: 13. Describe proposed or composed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casing 2/19/07-2/23/07 Drill out w/ a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks wis squeeze held good. 3/9/07 RIH with production equipmed 4/20/07 RIH with cement retainer & squeeze. I hereby certify that the information grads tank has been/will be constructed or SIGNATURE	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL leted operations. (Clearly state all park). SEE RULE 1103. For Multiple 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi - held good. "bit from 12,500' to original TD of val (12,500' - 12,682') with 3000 ge HCL acid. p holes (9981',9976', & 9973') leak th 500 gals of Flowguard & 75 sxs of the following state of the second according to NMOCD guidelines. TITLE	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'. als of 15% NeFe HC completions broke of the cement. Drill out cert as 1750 bpd sub pur 29981', 9976', & 9 st of my knowledge l, a general permit [] on	LING OPNS. D JOB D cmt cssg give pertinent dates ich wellbore diagran c; & 9973'. Inder a cement retain L acid. Acidize De down. Inder a cement et ain pp. SN @ 10,942'. 973' with 200 sxs c and belief. I further an (attached) alternat DATE	ALTERING CASING PAND A Solution PAND A Solution Set in a set and set of proposed completion of proposed (11,814' — ment. Test casing to 860# seement. Drill out & test of certify that any pit or below-tive OCD-approved plan
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING TOTHER: 13. Describe proposed or compost starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casin 2/19/07-2/23/07 Drill out w/a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks wis squeeze held good. 3/9/07 RIH with production equipmed 4/20/07 RIH with cement retainer & squeeze. I hereby certify that the information grads tank has been/will be constructed or SIGNATURE	PLUG AND ABANDON CHANGE PLANS C	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'. als of 15% NeFe HC completions by the cement. Drill out cert at 1750 bpd sub pur age 9981', 9976', & 9 st of my knowledge la general permit [] on	LING OPNS. D JOB D cmt cssg give pertinent dates uch wellbore diagran c; & 9973'. Inder a cement retain L acid. Acidize De down. ment retainer & cen mp. SN @ 10,942'. 973' with 200 sxs c and belief. I further r an (attached) alternat DATE DATE ne No. 432-685-016	ALTERING CASING PAND A Solution PAND A Solution Set in a set and set of proposed completion of proposed (11,814' — ment. Test casing to 860# seement. Drill out & test of certify that any pit or below-tive OCD-approved plan
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING DULL OR ALTER CASING THER: 13. Describe proposed or composed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casing 2/19/07-2/23/07 Drill out w/ a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks wis squeeze held good. 3/9/07 RIH with production equipmed 4/20/07 RIH with cement retainer & squeeze. I hereby certify that the information grads tank has been/will be constructed or SIGNATURE	PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL leted operations. (Clearly state all park). SEE RULE 1103. For Multiple 5 ½" casing @ 11,606'; 11,593'; 1 squeeze off casing leaks w/ 200 sxs to 600 psi - held good. "bit from 12,500' to original TD of val (12,500' - 12,682') with 3000 ge HCL acid. p holes (9981',9976', & 9973') leak th 500 gals of Flowguard & 75 sxs of the following state of the second according to NMOCD guidelines. TITLE	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'. als of 15% NeFe HC completions by the cement. Drill out cert at 1750 bpd sub pur age 9981', 9976', & 9 st of my knowledge la general permit [] on	LING OPNS. D JOB D cmt cssg give pertinent dates uch wellbore diagran c; & 9973'. Inder a cement retain L acid. Acidize De down. ment retainer & cen mp. SN @ 10,942'. 973' with 200 sxs c and belief. I further r an (attached) alternat DATE DATE ne No. 432-685-016	ALTERING CASING PAND A Solution PAND A Solution of proposed completion of proposed plan Solution
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING TOTHER: 13. Describe proposed or compost starting any proposed we or re-completion. 1/12/07 RUPU & locate holes in the 1/24/07 Set 5 ½" RBP @ 11,660'—out retainer & cement. Tested casin 2/19/07-2/23/07 Drill out w/a 4 5/8 2/27/07 Acidize Devonian OH inter 12,440') with 5000 gals of 15% NeF 3/1/07 Test 5 ½" casing — found to 3/2/07 Squeeze off casing leaks wis squeeze held good. 3/9/07 RIH with production equipmed 4/20/07 RIH with cement retainer & squeeze. I hereby certify that the information grads tank has been/will be constructed or SIGNATURE	PLUG AND ABANDON CHANGE PLANS C	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT OTHER: Squeeze Pertinent details, and the Completions: Attain 1,416'; 9981'; 9976' Class "H" cement us 12,682'. als of 15% NeFe HC completions by the cement. Drill out cert at 1750 bpd sub pur age 9981', 9976', & 9 st of my knowledge la general permit [] on	LING OPNS. D JOB D cmt cssg give pertinent dates uch wellbore diagran c; & 9973'. Inder a cement retain L acid. Acidize De down. ment retainer & cen mp. SN @ 10,942'. 973' with 200 sxs c and belief. I further r an (attached) alternat DATE DATE ne No. 432-685-016	ALTERING CASING PAND A Solution PAND A Solution Set in a set and set of proposed completion of proposed (11,814' — ment. Test casing to 860# seement. Drill out & test of certify that any pit or below-tive OCD-approved plan