

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.	30-025-21948
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	OG-530
7. Lease Name or Unit Agreement Name	State DG
8. Well Number	1
9. OGRID Number	
10. Pool name or Wildcat	Bagley, Lower Penn, No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-901) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Prime Operating Company

3. Address of Operator

3300 N. "A" St., Bldg. 1-238, Midland, TX 79705

4. Well Location

Unit Letter F : 1980 feet from the North line and 1980 feet from the West line
Section 16 Township 11-S Range 33-E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
4297' RKB

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

P&A operations are planned for the second quarter of 2007
Procedure:

- Appropriate cement and plug mud will be utilized.
- Spot 25 sks cement plug from 9000 ft. to 8753 ft.
- WOC and tag.
- Spot 25 sks cement plug from 6253 ft. to 6006 ft.
- Cut and pull 5 1/2" casing at 3900 ft. (50 ft. below the 8 5/8" casing shoe)
- Spot cement plug from 3950 ft. to 3800 ft. (50 ft. inside 5 1/2" csg. stub to 50 ft. above 8 5/8" csg. shoe) woc & tag
- Spot 100 ft. cement plug from 1800 ft. to 1700 ft. (Top of salt plug)
- Cut and pull 8 5/8" casing from 450 ft.
- Spot cement plug from 500 ft. to 350 ft. (50 ft. inside 8 5/8" csg. stub to 50 ft. above 13 3/8" csg shoe.)
- Spot 60 ft. cement plug at the surface.
- Cut casing 3 ft. below ground level and weld on steel plate with required information.

THE OIL CONSERVATION DIVISION
BE NOTIFIED 24 HOURS PRIOR
BEGINNING OF PLUGGING OPERATIONS.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE _____ TITLE _____ District Manager _____ DATE 4/17/2007

Type or print name Earl Levea E-mail address: elevea@primcenergy.com Telephone No. (432)682-5770
For State Use Only

APPROVED BY: GARY W. WINK OC FIELD REPRESENTATIVE II/STAFF MANAGER

Conditions of Approval (if any):

OC FIELD REPRESENTATIVE II/STAFF MANAGER

DATE MAY 15 2007

Subject:

Date:

Page:

File:

STATE DG #1

By:

1980' RWL & 1980' RWL
SEC. 16, T11S, R33E
LEA COUNTY, NEW MEXICO

60' CMT PLUG
Q SURFACE

CMT PLUG FROM
500' TO 350'

100' CMT PLUG
(TOP OF SALT)

CMT PLUG FROM
3950' TO 3800'

25' 3/4" CMT PLUG

25' 3/4" CMT PLUG

PRIME OIL CO.

3300 N "A" ST, BLDG 1-238

MIDLAND, TX 79705

P8TD 10,187'

TD 10,268'

13 3/8" 48-48" @ 400'
CMT TO SURFACE

8 5/8" C90 CUT AT 450'

8 5/8" 24-32" @ 3851'

5 1/2" C90 CUT @ 3900'

PERFS: 9060-67, 9075-82, 9110-14,
9136-38, 9145-51, 9201-04, 9230-32,
9344-54, 9446, 9470-79, 9482-90,
9527-29, 9553-55, 9561-66, 9594-97,
9607-12, 9622-26, 9640-43, 9650-55,
9706-08, 9712-14, 9730-32, 9752,
9775, 9784, 9854, 9878-90, 9904,
9928-38, 9972-86, 10010-16,
10022-26, 10044-54, 10058-68,
10083-98, 10104-110'

5 1/2" 15.5-17" @ 10,268'