## Form 3160-5 (February 2005)

## **OCD-HOBBS**

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB No. 1004-0137 Expires: March 31, 2007

5. Lease Serial No. LC 064118

6. If Indian, Allottee or Tribe Name

## **SUNDRY NOTICES AND REPORTS ON WELLS**

	Orm for proposals to di Use Form 3160-3 (APD)		s	
SUBMIT IN TRIPLICATE - Other instructions on page 2.			7. If Unit of CA	/Agreement, Name and/or No.
I. Type of Well  ☑ Oil Well ☐ Gas W	Vell Other	Received 3	8. Well Name ar Eva Blinebry F	
2. Name of Operator Latigo Petroleum, Inc.	7.7	Hobbs ed	9. API Well No. 3002510963	
3a. Address P.O. Box 10340, Midland, Texas	33.	Phone No. (include area 200	Langlie-Mattix	
4. Location of Well <i>(Footage, Sec., T.,</i> 1980 FNL 1980 FWL - CH & Letter F Sec 35 T-23-s R-37-E	र शहाभाष्ट्रा है।		11. Country or Parish, State Lea, New Mexico	
12. CHE	CK THE APPROPRIATE BOX(E	S) TO INDICATE NATURI	E OF NOTICE, REPORT OR	OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat New Construction	Production (Start/Resu Reclamation Recomplete	water Shut-Off  Well Integrity  Other
Subsequent Report Final Abandonment Notice	Casing Repair Change Plans Convert to Injection	✓ Plug and Abandon ✓ Plug Back	Temporarily Abandon Water Disposal	
PUH w/ Tbg to 2,400', spot 35 2) RIH w/ Tbg, tag cement at 2,1 Tbg, tag cement at 1157'. PO 3) RIH w/ 7" Packer to 440', pres sqz 80 sx, displaced to 250, W cement at 300'. 4) Nipple down BOP. Mix & circle	275'. Mixed & circulated 9.5 # S is x cement. PUH to 1,900', SV 85'. POOH w/ Tbg to 1,322'. If OH w/ Tbg, load casing to Surf test below Packer, 1500 F VOC for 4 hours. Opened well, ulate 60 sx of cement 300' to S cement at 40'. Cut off wellhea	VI & WOC. Mix & spot 35 sx cement. face. Pressure test to 600 PSI, test good. Found hol pressure test to 1300 PS curface.	POOH w/ Tbg,WOC for 4 PSI, bled to 300 PSI,SWI e in casing at 410'. Set Pa I, test good. POOH w/ Pa RIH to 40', circulate 20 sx  APPROVED WELL BOR	hours. RIH w/ I 300 PSI. acker at 157', cker, RIH & tag  cement to Surface.  DASTO PLUGGING OF THIS  IE. LIABILITY LINDER POUR
14. I hereby certify that the foregoing is Name ( <i>Printed/Typed</i> ) Howard Boatright	true and correct.	Title Agent	IS HETAINED U	INTIL SURFACE RESTORATION AS COMPLETED
Signature HBC	oa)	Date 04/19/2		
<u> </u>	THIS SPACE FO	R FEDERAL OR ST	ATE OFFICE USE	
Conditions of approval, if any, are attach- that the applicant holds legal or equitable entitle the applicant to conduct operation	title to those rights in the subject less thereon.	Title  warrant or certify ase which would  Office	ETROLEUM ENGINE	Date MAY Z 3 ZUU/
Title 18 U.S.C. Section 1001 and Title 4 fictitious or fraudulent statements or rep			and willfully to make to any de	epartment or agency of the United States any false

(Instructions on page 2)