	UNITED STATES PARTMENT OF THE IN EAU OF LAND MANA		5 1 0	Oł	DRM APPROVED MB No. 1004-0137 ires: March 31, 2007	
			NM-0	245247	· · · · · · · · · · · · · · · · · · ·	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to reperter an abandoned well. Use Form 3160-3 (APD) for such proposals.			n	6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on page 2. 1. Type of Well				7. If Unit of CA/Agreement, Name and/or No.		
Oil Well ☐ Gas W	Vell Other	-5-9 	McE	ll Name and No. vain # 8		
2. Name of Operator McElvain Oil & Gas Properties, Inc.			9. AP 30-0	[Well No. 2 5-38012		
1050 - 17th Street, Suite 1800 Denver, Colorado 80265		 p. Phone No. (include area cod 303) 893-0933 		10. Field and Pool or Exploratory Area EK Delaware		
Location of Well <i>(Footage, Sec., T.,</i> 60' FWL & 1905' FSL (NWSW) Section 30, T1		11. Country or Parish, State Lea County, New Mexico				
12. CHEC	K THE APPROPRIATE BOX((ES) TO INDICATE NATURI	E OF NOTICE, RE	PORT OR OTHE	R DATA	
TYPE OF SUBMISSION		TY	PE OF ACTION			
Notice of Intent	Acidize	Deepen Fracture Treat	Production Reclamation	Start/Resume)	Water Shut-Off Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete		Casing & Cer	
Final Abandonment Notice	Change Plans	Plug and Abandon Plug Back	Water Dispo		Design	
oot Bone Spring test. McElvain wo and the wellpad dimensions have no	ed operations. If the operation Abandonment Notices must be : r final inspection.) received an approved permit uld now like to amend this per-	results in a multiple completio filed only after all requirement t to drill the McElvain # 8 we armit to drill only to 6,000 fe	on or recompletion ts, including reclan ell on July 13, 200 et and test the D	n a new interval, ation, have been 6. The original laware formatio	a Form 3160-4 must be fi completed and the operato permit was approved a n. The proposed acces	led once or has s a 10,50
Attach the Bond under which the v following completion of the involv testing has been completed. Final determined that the site is ready fo McElvain Oil & Gas Properties, Inc. foot Bone Spring test. McElvain wo and the wellpad dimensions have no The amended casing and cement d Preset 80 feet of 14" conductor and MIRU Drilling Rig (rig company to b Drill an 11" hole 25-50 feet into the I Run fluid caliper for hole volume Run & Set approximately 1700' of 8 NU & test BOP equipment Drill 7.875" hole to TD Log open hole (including hole volum Run & Set approximately 6,000' of 5 RDMO Drilling Rig	red operations. If the operation Abandonment Notices must be : r final inspection.) received an approved permit uld now like to amend this per ot changed. sesign are as follows: cement to surface e determined) Rustler anhydrite formation p STC Leod .625", 32#, J55 surface casim ne log) .5", 17#, J55 casing and cem	results in a multiple completion filed only after all requirement t to drill the McElvain # 8 we ermit to drill only to 6,000 fe $\mathcal{I}_U d \qquad \mathcal{O} \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$	on or recompletion ts, including reclan ell on July 13, 200 et and test the Do FW/depu d PPP $FW/depu d PPP FW/depu d PPPFW/depu d PPPFW/depu d PPP FW/depu d PPPFW/depu d PPPFW/depu$	in a new interval, ation, have been 16. The original plaware formatic 10, 1, 20, 0, 10, 10, 10, 10, 10, 10, 10, 10, 10	a Form 3160-4 must be fi completed and the operator permit was approved a on. The proposed access and a second second by a second second second second by a second	led once or has s a 10,50 ss road
Attach the Bond under which the v following completion of the involv testing has been completed. Final determined that the site is ready fo McElvain Oil & Gas Properties, Inc. foot Bone Spring test. McElvain wo and the wellpad dimensions have no The amended casing and cement de Preset 80 feet of 14" conductor and MIRU Drilling Rig (rig company to b Drill an 11" hole 25-50 feet into the Run fluid caliper for hole volume Run & Set approximately 1700' of 8 VU & test BOP equipment Drill 7.875" hole to TD Log open hole (including hole volume Run & Set approximately 6,000' of 5 RDMO Drilling Rig Run cement bond log prior to start of the the foregoing is t Name (Printed/Typed)	red operations. If the operation Abandonment Notices must be : r final inspection.) received an approved permit uld now like to amend this per ot changed. esign are as follows: cement to surface e determined) Rustler anhydrite formation p $STC \ Lcock$.625", 32#, J55 surface casin he log) $LTC \ Leock$.55", 17#, J55 casing and cent of completion operations	results in a multiple completion filed only after all requirement t to drill the McElvain # 8 we ermit to drill only to 6,000 fe $N_u d$ $O_{-}1700$ P 1700 - 3700 $d3700 - 6000$ $Cprior to setting surface casin2 o d 230 g \times 1.43 yand cement to surface with1 375 g \times 35.165^{-1}ment with an estimated 850750$	on or recompletion ts, including reclan ell on July 13, 200 et and test the Do FW/depu d PPP $FW/depu d PPP FW/depu d PPPFW/depu d PPPFW/depu d PPP FW/depu d PPPFW/depu d PPPFW/depu$	n a new interval, ation, have been 6. The original blaware formatic 10, 1 p 9, 0 10, 1 p 9, 3 p 9, 3 p 5, 7/200 so 50 sacks Class $309 y /d 12$, to approximatel 5 s x 50	a Form 3160-4 must be fi completed and the operator permit was approved a on. The proposed access PPg Eg Eg Eg Cg Cg Cg Cg Cg Cg Cg C	led once or has s a 10,50 ss road
Attach the Bond under which the v following completion of the involv testing has been completed. Final determined that the site is ready fo McElvain Oil & Gas Properties, Inc. foot Bone Spring test. McElvain wo and the wellpad dimensions have no The amended casing and cement de Preset 80 feet of 14" conductor and MIRU Drilling Rig (rig company to b Drill an 11" hole 25-50 feet into the Run fluid caliper for hole volume Run & Set approximately 1700' of 8 NU & test BOP equipment Drill 7.875" hole to TD Log open hole (including hole volume Run & Set approximately 6,000' of 5 RDMO Drilling Rig Run cement bond log prior to start co 4. I hereby certify that the foregoing is t Name (Printed/Typed)	red operations. If the operation Abandonment Notices must be : r final inspection.) received an approved permit uld now like to amend this per ot changed. esign are as follows: cement to surface e determined) Rustler anhydrite formation p $STC \ Lcock$.625", 32#, J55 surface casin he log) $LTC \ Leock$.55", 17#, J55 casing and cent of completion operations	results in a multiple completion filed only after all requirement t to drill the McElvain # 8 we ermit to drill only to 6,000 fe $N_u d$ $O_{-}1700$ P 1700 - 3700 $d3700 - 6000$ $Cprior to setting surface casin2 o d 230 g \times 1.43 yand cement to surface with1 375 g \times 35.165^{-1}ment with an estimated 850750$	on or recompletion ts, including reclan ell on July 13, 200 et and test the Do EW/apud mit Britse Cut Drime g Id 14.8 7 ith an estimated f $Poz C I, Bsacks of POZ/CTo// 37Operations Engine$	n a new interval, ation, have been 6. The original blaware formatic 10, 1 20 10, 20 1	a Form 3160-4 must be fi completed and the operator permit was approved a on. The proposed access PPg Eg Eg Eg Cg Cg Cg Cg Cg Cg Cg C	led once or has s a 10,50 ss road
Attach the Bond under which the v following completion of the involv testing has been completed. Final determined that the site is ready for McElvain Oil & Gas Properties, Inc. foot Bone Spring test. McElvain wo and the wellpad dimensions have no The amended casing and cement de Preset 80 feet of 14" conductor and MIRU Drilling Rig (rig company to b Drill an 11" hole 25-50 feet into the I Run fluid caliper for hole volume Run & Set approximately 1700' of 8 NU & test BOP equipment Drill 7.875" hole to TD Log open hole (including hole volum Run & Set approximately 6,000' of 5 RDMO Drilling Rig Run cement bond log prior to start co Mame (Printed/Typed) E. Reed Fischer	red operations. If the operation Abandonment Notices must be : r final inspection.) received an approved permit uld now like to amend this pe- ot changed. esign are as follows: cement to surface e determined) Rustler anhydrite formation p 5TC L c .625", 32#, J55 surface casim the log) 5.5", 17#, J55 casing and cent of completion operations rue and correct.	results in a multiple completion filed only after all requirement to drill the McElvain # 8 we ermit to drill only to 6,000 fe 1700 - 3700 + 1700 + 1700 - 3700 - 6000 - 0 prior to setting surface casin 200 + 230 + 35 + 1.43 + 35 or and cement to surface with a strategies of 250 + 1.43 + 35 + 1655 ment with an estimated 850 - 750 Title Senior C	on or recompletion ts, including reclan ts, including reclan ts, including reclan ts, including reclan ts, including reclan ts, including reclan $F_{M}/S_{PU} d mn$ $F_{M}/S_{PU} d mn$ $F_$	n a new interval, ation, have been 16. The original plaware formatic 10, 1 p 10,	a Form 3160-4 must be fi completed and the operator permit was approved a on. The proposed access PPg g g 1.34	led once or has s a 10,50 ss road
Attach the Bond under which the v following completion of the involv testing has been completed. Final determined that the site is ready for McElvain Oil & Gas Properties, Inc. foot Bone Spring test. McElvain wo and the wellpad dimensions have no The amended casing and cement de Preset 80 feet of 14" conductor and MIRU Drilling Rig (rig company to b Drill an 11" hole 25-50 feet into the Run fluid caliper for hole volume Run & Set approximately 1700' of 8 NU & test BOP equipment Drill 7.875" hole to TD Log open hole (including hole volum Run & Set approximately 6,000' of 5 RDMO Drilling Rig Run cement bond log prior to start c	red operations. If the operation Abandonment Notices must be : r final inspection.) received an approved permit uld now like to amend this pe- ot changed. esign are as follows: cement to surface e determined) Rustler anhydrite formation p 5TC L c .625", 32#, J55 surface casim the log) 5.5", 17#, J55 casing and cent of completion operations rue and correct.	results in a multiple completion filed only after all requirement t to drill the McElvain # 8 we ermit to drill only to 6,000 fe 1/00 - 3700 + 3700 + 3700 - 6000 + 00000 + 0000 + 00000 + 0000 + 00	on or recompletion ts, including reclan ts, including reclan ts, including reclan ts, including reclan ts, including reclan ts, including reclan $F_{M}/S_{PU} d mn$ $F_{M}/S_{PU} d mn$ $F_$	n a new interval, ation, have been 16. The original blaware formatic 10, 1 9, 0 10, 1 9 9, 3 9 5, 7 200 39 50 sacks Class 30 9 y /d 12, to approximatel 25 37 50 er USE	a Form 3160-4 must be fi completed and the operator permit was approved a on. The proposed access PPg g g 1.34	led once or has s a 10,50 ss road
Attach the Bond under which the v following completion of the involv testing has been completed. Final determined that the site is ready for McElvain Oil & Gas Properties, Inc. foot Bone Spring test. McElvain wo and the wellpad dimensions have no The amended casing and cement de Preset 80 feet of 14" conductor and MIRU Drilling Rig (rig company to b Drill an 11" hole 25-50 feet into the Run fluid caliper for hole volume Run & Set approximately 1700' of 8 NU & test BOP equipment Drill 7.875" hole to TD Log open hole (including hole volum Run & Set approximately 6,000' of 5 RDMO Drilling Rig Run cement bond log prior to start of Name (<i>Printed/Typed</i>) E. Reed Fischer	red operations. If the operation Abandonment Notices must be in r final inspection.) received an approved permit uld now like to amend this per- ot changed. esign are as follows: cement to surface e determined) Rustler anhydrite formation p STC L c 625", 32#, J55 surface casin the log) STC L coord STC STC L coord STC L coord STC STC L coord STC	results in a multiple completion filed only after all requirement t to drill the McElvain # 8 we ermit to drill only to 6,000 fe U = U = U = 0.000 ($U = 0.000$) U = 0.000 ($U = 0.000$) orior to setting surface casin z = 0.0000 ($Z = 3000$) ($Z = 0.0000$) orior to setting surface casin z = 0.0000 ($Z = 0.0000$) orior to setting surface casin z = 0.0000 ($Z = 0.0000$) ($Z = 0.00000$ ($Z = 0.00000$) Title Senior ($U = 0.000000$) Date 05/22/20 OR FEDERAL OR ST.	on or recompletion ts, including reclan ts, including reclan ts, including reclan ts, including reclan ts, including reclan ts, including reclan $F_{M}/S_{PU} d mn$ $F_{M}/S_{PU} d mn$ $F_$	n a new interval, ation, have been 16. The original blaware formatic 10, 1 20 10,	a Form 3160-4 must be fi completed and the operator permit was approved a un. The proposed access g g g g g g g g g g g g g g g g g g	led once or has s a 10,50 ss road
Attach the Bond under which the v following completion of the involv testing has been completed. Final determined that the site is ready for McElvain Oil & Gas Properties, Inc. foot Bone Spring test. McElvain wo and the wellpad dimensions have no The amended casing and cement de Preset 80 feet of 14" conductor and MIRU Drilling Rig (rig company to b Drill an 11" hole 25-50 feet into the Run fluid caliper for hole volume Run & Set approximately 1700' of 8 NU & test BOP equipment Drill 7.875" hole to TD Log open hole (including hole volum Run & Set approximately 6,000' of 5 RDMO Drilling Rig Run cement bond log prior to start of Name (<i>Printed/Typed</i>) E. Reed Fischer	red operations. If the operation Abandonment Notices must be in r final inspection.) received an approved permit uld now like to amend this per- ot changed. esign are as follows: cement to surface e determined) Rustler anhydrite formation p STC Le e determined THIS SPACE FO THIS SPACE FO L Approval of this notice does no itle to those rights in the subject le thereon. U.S.C. Section 1212, make it a critical states of the section of the sect	results in a multiple completio filed only after all requirement t to drill the McElvain # 8 we ermit to drill only to 6,000 fe U = U = U = U = U = U = U U = U = U = U = U = U U = U = U = U = U U = U = U = U = U U = U U = U U = U = U U = U	n or recompletion ts, including reclan ell on July 13, 200 et and test the Do Ew/Japu d mile Brine Cut Brine g Jd 14, 8 7, ith an estimated f Poz C J, 8 sacks of POZIC To, // 37 Operations Engine	n a new interval, ation, have been 16. The original plaware formatic 10, 1 9, 0 10, 1 9 9, 3 9 5, 7 200 99 50 sacks Class 30 9 y /d 12, to approximatel 5 5 5 5 50 er USE	a Form 3160-4 must be fi completed and the operator permit was approved a on. The proposed access g g g g g g g g g g g g g g g g g g	led once or has s a 10,50 ss road