

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-38158

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Cimarex Energy Co.

3. Address of Operator

PO Box 140907; Irving, TX 75014-0907

4. Well Location

Unit Letter L : 2235 feet from the South line and 660 feet from the West line
Section 13 Township 15S Range 37E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3776' GR

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☒ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

02-03-07 Spudded.
02-05-07 Ran 13-3/8" 48# H-40 STC to 606.' Cemented with lead of 300 sx Halliburton Light Premium Plus + 1% CaCl + 0.125# Poly-E-Flake + 5# Gilsonite (wt 12.5, yld 1.98) and tail of 220 sx Premium Plus + 2% CaCl (wt 14.8, yld 1.98). Circulated 100 sx to surface.
02-06-07 Pressure tested casing to 500 psi for 30 minutes. WOC total of 23 hours.
02-14-07 Ran 8-5/8" 32# J-55 LTC to 4515.'
02-15-07 Cemented with lead of 1000 sx Interfill C + 0.125% Poly-E-Flake (wt 11.9, yld 2.45) and tail of 200 sx Premium Plus C + 1% CaCl (wt 14.8, yld 1.33). No sx circulated to surface. Ran 1" and tagged up @ 752.' Performed 1" top job w/ 350 sx Neat (wt 14.8, yld 1.18). Circulated 14 sx to surface and observed that cement did not drop.
02-16-07 Pressure tested casing to 1000 psi for 30 minutes. WOC total of 35.5 hours.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Natalie Krueger TITLE Reg Analyst I DATE May 29, 2007

Type or print name Natalie Krueger email address: nkrueger@cimarex.com Telephone No. 469-420-2723

For State Use Only

APPROVED BY: Harry W. Wink TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE _____

Conditions of Approval (if any):

JUN 04 2007