District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144 June 1, 2004

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Pit or Below-Gra	de Tank Regi	stration or (Closure

Is pit or below-grade tank covered by a "general plan"? Yes X No Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank X				
7 2002				
Operator: Read & Stevens, Inc. Telephone: 505.396.5391 e-mail address: readnandstevensinc@leaco.net Address: PO Box 1719 Lovington, NAC 1882.66				
Facility or well name: Manry Elliott #2 API #: 30-005-27946 1980' FNL x 990' FEL Sec 22 Twp 11-S Rge 31-E				
County: _Eddy Latitude _33.35155' N Longitude _103.803641' W_ NAD:				
Surface Owner: Federal State Private Pindian X				
<u>Pit</u>				
Type:				
Pit Type: Drilling X Production Disposal Workover Emergency Lined X Unlined Linet type: Synthetic X Thickness: 12 mil Type: Drilling X Production COO Sqoot				
Drilling X Production Disposal Workover Emergency Lined X Unlined Linet type: Synthetic X Thickness: 12 mil Clay Original Disposal Samples are to be obtained and the				
Disposal Compaction of the Disposal Compaction o				
Workover Emergency Square Square				
Lined X Unlined \(\begin{array}{cccccccccccccccccccccccccccccccccccc	ponieżay	3 . 3 .		
Liner type: Synthetic X 30 100 GS SUCK-filling				
Thickness: 12 mil	<i>\$</i> . 9€ .	û		
Clay \(\begin{array}{cccccccccccccccccccccccccccccccccccc				
Thickness: 12 mil Clay Pit Volume 10,000 bbl				
Depth to ground water - Encountered no and water while	Less than 50 feet	(20 points)		
drilling and setting conductor pipe at 84'	50 feet or more, but less than 100 feet	(10 points)		
	100 feet or more	(0 points)		
	Yes	(20 points)		
Wellhead protection area: Over 1900' to nearest water well.		(20 points)		
	No	(0 points)		
Distance to surface water: No wetlands, playas, irrigation canals,	Less than 200 feet	(20 points)		
ditches, or watercourses in area.	200 feet or more, but less than 1000 feet	(10 points)		
	1000 feet or more	(0 points)		
	Ranking Score (Total Points)			
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if				
your are burying in place) onsite offsite X If offsite, name of facility Gand				
remediation start date and end date. (4) Groundwater encountered: No X Yes Tif yes, show depth below ground surface ft. and attach sample results.				
(5) Attach soil sample results and a diagram of sample locations and excavations.				
Additional Comments: DISPOSITION OF THE COMMENTS.				
Cuttings disposed of in accredited tend farm facility. Location will be cleaned and will contour to the lay of the land. The area will be re-seeded.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above described pit or below-grade tank				
has been/will be constructed or closed according to NMOCD guidelines X, a general permit [], or an (attached) alternative OCD-approved plan [X].				
		9		
Date: June 6, 2007				
Printed Name/Title William V. Palmer - Superintendent				
Signature Verrorifordia ad NOCCO and a Chical Control of the Control of the Chical Cont				
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or				
Approval:				
Printed Name/Title LJOHLSON - EN URZ ENER Signature Signature Date: 6.12.07				
Timiled Ivanice Time Colliford - Colliford - Signature S				
4500 - OCE TO A COLL TO DEPORT				
SUBMITTAL OF FINALC: (41 W/ DOCUMENTION OF DICCS OF CITIEN IN DIRECTION				
SAMPLING OF CHURIDE TO 250 PPM OR LESS & REMOVAL OF ANY LABOVE 250.				

Read & Stevens, Inc

Manry Elliott #2

Site Diagram

06Jun07 - WVP

