

Submit 3 Copies To Appropriate District Office  
District I  
1625 N French Dr., Hobbs, NM 88240  
District II  
1301 W Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-025-24995
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name:  Davenport
8. Well No. 1
9. Pool name or Wildcat Sawyer

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Manhattan Petroleum, Inc.

3. Address of Operator

P. O. Box 35888, Tulsa, OK 74153-0888

4. Well Location

Unit Letter H : 1980 feet from the North line and 660 feet from the East line

Section 17 Township 9S Range 38E NMPM Lea County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3955' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Proposed P&A Procedure: (Wellbore diagram attached)

Plug #1 - Set CIBP at 4796 ft. - 90 ft. above San Andres perfs. (4886-4920 ft.). Spot 25 sx cmt on top of CIBP with 9.5ppg SW mud.

Plug #2 - Perforate 4 shots @ 2200 ft. (100 ft above top of salt). Squeeze 12.5 sx cement outside perfs and bring 12.5 sx cement up to 2150 ft. inside casing using with 9.5ppg SW mud to displace with. WO cement and tag top of plug.

Plug #3 - Spot 25 sx cement through tubing at 414 ft. with 9.5ppg SW mud. WOC cement and tag at or above 314 ft.

Plug #4 - Spot 10 sx cement at 150 ft. Fill casing w/ 9.5 SW mud.

→ PERF + SQZ F/414'-TAG @ 314'  
Set dry hole marker accordingly and clean up location.

**THE OIL CONSERVATION DIVISION MUST  
BE NOTIFIED 24 HOURS PRIOR TO THE  
BEGINNING OF PLUGGING OPERATIONS.**

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE CSwan TITLE Regulatory Administrator DATE 6/13/07

Type or print name Connie Swan CSSwan@manhattanpetroleum.com Telephone No. (918) 621-6533

(This space for State use)

APPROVED BY Hay W. Wink TITLE OC FIELD REPRESENTATIVE / STAFF MANAGER DATE JUN 20 2007

Conditions of approval, if any:

# MANHATTAN PETROLEUM WELL DATA SHEET

WELL NAME : Davenport NUMBER: 1 FIELD: Sawyer ( San Andres)  
 LOCATION : Letter H, 1,980' FNL 660' FEL of Sec 17, T9S, R38E, Lea Co. New Mexico  
 ELEVATION : 3,960' GL  
 API NUMBER 30 - 025 - 24995

Surface Casing: 8 5/8"; 24#  
 Set @ 364'  
 Cement w/ 250 sks  
Class C w/ 2% CaCl.

Date Completed: 7/10/1975  
by Flag-Redfern.

TOC : Surface - circ.

Yates Top 2,895'  
 San Andres 4,154'

Perfs: 4,886' to 4,887' (4 holes)  
 Perfs: 4,892' to 4,902' (20 holes)  
 Perfs: 4,906' to 4,920' (28 holes)

P.B.T.D.: 4,990'

Production Csg: 4 1/2" 10.6#  
 Set @ 5,000'  
 Cemented w/ 250 sks  
Class Poz C w/ 2% gel;  
8#/sk salt; 0.75% CFR-2.

TOC : est. 3,600'

HOLE SIZE	<u>7 7/8"</u>
TOTAL DEPTH	<u>5,000'</u>

Prepared by:

rlw

Date

6/11/2007