

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N French Dr., Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S St Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-105 Revised June 10, 2003 WELL API NO. 30-025-38113 5. Indicate Type of Lease STATE ☐ FEE ☒ State Oil & Gas Lease No.
WELL COMPLETION OR RECOMPLETION REPORT AND LOG		
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐		7 Lease Name or Unit Agreement Name East Blinebry Drinkard Unit
b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. ☐ WELL OVER BACK RESVR ☐ OTHER ☐		
2 Name of Operator Apache Corporation		8. Well No. 60
3. Address of Operator 6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224		9. Pool name or Wildcat Eunice; Bli-Tu-Dri, North
4. Well Location Unit Letter B : 1270 Feet From The North Line and 2310 Feet From The East Line Section 14 Township 21S Range 37E NMPM Lea County		
10 Date Spudded 05/05/2007	11 Date T.D Reached 05/13/2007	12 Date Compl (Ready to Prod.) 05/31/2007
13 Elevations (DF& RKB, RT, GR, etc) 3416'		14 Elev. Casinghead 4537.89'
15 Total Depth 6875'	16 Plug Back T.D. 6828'	17 If Multiple Compl How Many Zones? 3
18 Intervals Drilled By X		19 Cable Tools No
19 Producing Interval(s), of this completion - Top, Bottom, Name 5624' - 6766' Eunice; Blinebry-Tubb-Drinkard, North (22900)		20 Was Directional Survey Made No
21. Type Electric and Other Logs Run DLL/MG, SD/DSN, LSS		22. Was Well Cored No
23. CASING RECORD (Report all strings set in well)		
CASING SIZE	WEIGHT LB./FT.	DEPTH SET
8-5/8"	24#	1312'
5-1/2"	17#	6875'
24. LINER RECORD		25. TUBING RECORD
SIZE	TOP	SIZE
		2-7/8"
BOTTOM	SACKS CEMENT	DEPTH SET
		6796'
26 Perforation record (interval, size, and number) Dri: 6656-60, 6721-25, 6762-66 2 JSPF Tu: 6097-6101, 6138-42, 6300-04, 20-26, 63-67 2 JSPF Bli: 5624-28, 52-56, 84-88, 5760-66, 5806-10 2 JSPF		27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 6656 - 6766' 3Kgals 15%NEFE, 39Kgals gel & 62K# 20/40 6097 - 6367' 3Kgals 15%NEFE, 32Kgals gel & 58K# 20/40 5624 - 5810' 3Kgals 15%NEFE, 36Kgals gel & 82K# 20/40
28. PRODUCTION		
Date First Production 05/31/2007		Production Method (Flowing, gas lift, pumping - Size and type pump) Rod Pump - Pumping
Date of Test 06/20/2007		Well Status (Prod. or Shut-in) Producing
Hours Tested 24 hours	Choke Size	Prod'n For Test Period
		Oil - Bbl 40
Flow Tubing Press.	Casing Pressure	Gas - MCF 158
		Water - Bbl. 26
	Calculated 24-Hour Rate	Gas - MCF
		Water - Bbl.
		Oil Gravity - API - (Corr.) 37.5
29 Disposition of Gas (Sold, used for fuel, vented, etc) Sold		Test Witnessed By Apache
30. List Attachments Deviation Report, C-102, C-103, C-104		
31 I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief		
Signature <i>Sophie Mackay</i> Email Address sophie.mackay@apachecorp.com		Printed Name Sophie Mackay Title Engineering Tech Date 06/25/2007

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2606'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2840'	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3733'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3996'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5227'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry 5673'	T. Gr. Wash	T. Morrison	T.
T. Tubb 6172'	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6558'	T. Bone Springs	T. Entrada	T.
T. Abo 6834'	T. Rustler 1303'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology