

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N French Dr., Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-105 Revised June 10, 2003 WELL API NO. 30-025-38268 5. Indicate Type of Lease STATE ☒ FEE ☐ State Oil & Gas Lease No. BO-1557-0002
WELL COMPLETION OR RECOMPLETION REPORT AND LOG		
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐ b. Type of Completion. NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. ☐ WELL OVER BACK RESVR. ☐ OTHER ☐		7. Lease Name or Unit Agreement Name State C Tract 12
2. Name of Operator Apache Corporation		8 Well No. 33
3. Address of Operator 6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224		9 Pool name or Wildcat Eunice; Bli-Tu-Dri, North
4. Well Location Unit Letter F : 1330 Feet From The North Line and 2440 Feet From The West Line Section 16 Township 21S Range 37E NMPM County		
10. Date Spudded 04/27/2007	11. Date T.D Reached 05/07/2007	12. Date Compl. (Ready to Prod.) 05/30/2007
13. Elevations (DF& RKB, RT, GR, etc) 3483'		14. Elev Casinghead
15. Total Depth 6892'	16. Plug Back T D 6846'	17. If Multiple Compl. How Many Zones? 3
18. Intervals Drilled By X		19. Producing Interval(s), of this completion - Top, Bottom, Name 5624' - 6644' Eunice; Blinbry-Tubb-Drinkard, North (22900)
20. Was Directional Survey Made No		21. Type Electric and Other Logs Run DLL/MG, SD/DSN, LSS
22. Was Well Cored No		
23. CASING RECORD (Report all strings set in well)		
CASING SIZE	WEIGHT LB./FT.	DEPTH SET
8-5/8"	24#	1322'
5-1/2"	17#	6892'
24. LINER RECORD		25. TUBING RECORD
SIZE	TOP	SIZE
		2-7/8"
BOTTOM	SACKS CEMENT	DEPTH SET
		6765'
26. Perforation record (interval, size, and number) Dri: 6422-26, 54-58, 6563-69, 86-90, 6602-06, 20-24, 40-44 2 SPF Tu: 6090-94, 6116-20, 6206-10, 32-36, 74-80, 6300-04 2 SPF Bli: 5624-28, 54-58, 5788-92, 5810-16, 5930-34 2 SPF		27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 6422 - 6644' 3Kgals 15%NEFE, 39Kgals gel & 62K# 20/40 6090 - 6304' 3Kgals 15%NEFE, 36Kgals gel & 82K# 20/40 5624 - 5934' 3Kgals 15%NEFE, 36Kgals gel & 82K# 20/40
28. PRODUCTION		
Date First Production 05/30/2007		Production Method (Flowing, gas lift, pumping - Size and type pump) Rod Pump - Pumping
		Well Status (Prod. or Shut-in) Producing
Date of Test 06/26/2007	Hours Tested 24 hours	Choke Size
		Prod'n For Test Period
		Oil - Bbl 53
		Gas - MCF 700
		Water - Bbl. 18
		Gas - Oil Ratio 13208
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate
		Oil - Bbl.
		Gas - MCF
		Water - Bbl.
		Oil Gravity - API - (Corr.) 35.5
29 Disposition of Gas (Sold, used for fuel, vented, etc) Sold		Test Witnessed By Apache
30. List Attachments Deviation Report, C-102, C-103, C-104		
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief		
Signature <i>Sophie Mackay</i>		Printed Name Sophie Mackay
E-mail Address sophie.mackay@apachecorp.com		Title Engineering Tech
		Date 06/27/2007

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2664'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2882'	T. Devonian	T. Menefee	T. Madison
T. Queen 3446'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3740'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3998'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5190'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry 5648'	T. Gr. Wash	T. Morrison	T.
T. Tubb 6106'	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6438'	T. Bone Springs	T. Entrada	T.
T. Abo 6747'	T. Rustler 1285'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology