<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Buzzos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

### State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fo

Form C-144 June 1, 2004

office

Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes No X

Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank X

Marker and and	(505)393-5905	
Address: Box 5270 Hobbs NM 8824	A SOLUTION OF THE BUILDING	
Facility or well manner Pleasant Kidge 6 St. Con# LAM #: 3	1-025-38/8/ W. or OtriOtr B	Sec 6 T215 R35E
County: Lea	N32'30'12.3" Logid W103'.	24' 19.6" NAD: 1927 🗆 1983 🗖
Surface Owner: Federal   State   Private   Indian		
	Below-grade task	
Pit Type: Drilling M Production Disposal D	Volume: bbl Type of fluid:	
Workover   Emergency	Construction material:	
Line	Double-walled, with lack detection? Yes [Hi not, explain why not.	
Lines type: Synthetic X Thickness /2 mil Clay		
Pit Volumebbl		
LA VOISING DOF	Less then 50 feet	(20 points)
Dopth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)
high water elevation of ground water.)	100 feet or more // 00'	( O points)
		( Upwins)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1600 fact from all other water sources.)	(No)	( 0 points)
Distance to surface water: (horizontal distance to all wetlands, playes, imigation canals, disches, and perennial and ephement watercourses.)	Loss than 200 feet	(20 points)
	200 feet or more, but less than 1000 feet	(10 points)
	1000 fact or more	( Opoints)
	To the Control of the	
	Ranking Score (Total Points)	
Additional Comments: Refer to A HACKED pit Closure Plan.  DEEP BURY - PROLIDE ZO MU FIT LINER W GOOD FAD  **A GENTER LINER ON WALLS.		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines/El, a general permit [], or an (attacked) alternative OCD-approved plan [].		
Date: 7/23/07  Printed Name/Title Dis Sh. L. (Son) Field Septical Signature  Your certification and NMOCD approval of this application/closure does not relieve the application of the recommendation for the content of the pit or task content inste ground water or otherwise cardenger public health or the carvironance. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
Approval:  Printed Name/Title T. JOHNSON . ENV ( P.D. ENGR. Signature College Signat		
State of Sta		

P.O. Box 310 Hobbs, NM 88241-0310

# Hobbs, New Mexico Cell 505.392.8584 Services Hobbs, New Mexico

Reserve Pit Remediation

# **SURFACE PIT CLOSURE PLAN**

# PIT PARAMETERS

COMPANY: Mewbourne Oil Co.

WELL SITE: Pheasant Ridge 6 State Com #1

LEGAL DESCRIPTION: Unit B Sec 6 T21s R35e, 990

FSL 2310 FEL, Lea co.

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 150' X 150' X 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 1800 yards. The burial cell is to be excavated and lined with a minimum 12 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cuttings will be loaded as to allow for > 36" freeboard to ground level. After the cuttings are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the

edge of the burial cell. This cap will be constructed as to slope and allow for water runoff from burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.

### **LOCATION DIAGRAM**

Mewbourne Oil, Pheasant Ridge 6 State com #1 API #30-025-38181 V-DOOR west

