

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N French Dr., Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S St Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003	
		WELL API NO. 30-025-38317		5. Indicate Type of Lease STATE ☒ FEE ☐	
				State Oil & Gas Lease No. BO-5553	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____			7. Lease Name or Unit Agreement Name North Monument G/SA Unit		
b. Type of Completion. NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF WELL OVER BACK RESVR. ☐ OTHER					
2. Name of Operator Apache Corporation			8. Well No. 363		
3. Address of Operator 6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224			9. Pool name or Wildcat Eunice Monument; Grayburg-San Andres		
4. Well Location Unit Letter I 2630 Feet From The South Line and 130 Feet From The East Line Section 30 Township 19S Range 37E NMPM Lea County					
10. Date Spudded 05/24/2007	11. Date T.D. Reached 05/28/2007	12. Date Compl (Ready to Prod.) 06/20/2007	13. Elevations (DF& RKB, RT, GR, etc.) 3,615' GR	14. Elev. Casinghead	
15. Total Depth 4060'	16. Plug Back T.D. 3860' (CIBP)	17. If Multiple Compl How Many Zones? N/A	18. Intervals Drilled By X	Rotary Tools	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name Eunice Monument; Grayburg-San Andres 3826' - 3852'				20. Was Directional Survey Made NO	
21. Type Electric and Other Logs Run Acoustic Cement Bond / Compensated Neutron				22. Was Well Cored NO	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	395'	11"	400 sx / circ	
5-1/2"	17#	4060'	7-7/8"	1050 sx / TOC 60' CIBP	
24. LINER RECORD			25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE
					2-7/8"
					DEPTH SET
					3,841'
					PACKER SET
26. Perforation record (interval, size, and number) G/SA 3922-48 (2 JSPF) CIBP @ 3910 G/SA 3864-94 (2 JSPF) CIBP @ 3860 G/SA 3826-52 (2 JSPF)			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 3922-3948 1000 gals 15% HCl 3864-3894 1000 gals 15% HCl 3826-3852 1000 gals 15% HCl		
28. PRODUCTION					
Date First Production 06/20/2007		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping		Well Status (Prod. or Shut-in) Producing	
Date of Test 07/10/2007	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 15	Gas - MCF 1
				Water - Bbl 46	Gas - Oil Ratio 67
Flow Tubing Press	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.
					Oil Gravity - API - (Corr) 31.3
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold					Test Witnessed By Apache
30. List Attachments Deviation Report, Logs, C-102, C-103, C-104					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature <i>S. Mackay</i>		Printed Name Sophie Mackay		Title Engineering Tech	
E-mail Address sophie.mackay@apachecorp.com				Date 07/17/2007	

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen 3320'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3618'	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T. Penrose 3425'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology