


Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N French Dr., Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003	
		WELL API NO. 30-025-38414		5. Indicate Type of Lease STATE ☒ FEE ☐	
				State Oil & Gas Lease No. BO-0085-0015	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____			7. Lease Name or Unit Agreement Name STATE DA		
b. Type of Completion. NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER					
2. Name of Operator Apache Corporation			8. Well No. 25		
3. Address of Operator 6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224			9. Pool name or Wildcat Eunice; Bli-Tu-Dri, North		
4. Well Location Unit Letter L : 1510 Feet From The South Line and 1280 Feet From The West Line Section 16 Township 21S Range 37E NMPM Lea County					
10. Date Spudded 06/23/2007	11. Date T D Reached 07/01/2007	12. Date Compl. (Ready to Prod.) 07/26/2007	13. Elevations (DF& RKB, RT, GR, etc) 3453'	14. Elev. Casinghead	
15. Total Depth 6850'	16. Plug Back T.D. 6803'	17. If Multiple Compl. How Many Zones? 3	18. Intervals Drilled By	Rotary Tools X	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name 5910' - 6676' Eunice; Blinbry-Tubb-Drinkard, North (22900)					20. Was Directional Survey Made No
21. Type Electric and Other Logs Run DLL/MG, SD/DSN				22. Was Well Cored No	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	1273'	12-1/4"	575 sx / circ	
5-1/2"	17#	6850'	7-7/8"	1300 sx / TOC 186' CBL	
24. LINER RECORD			25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE
					DEPTH SET
					2-7/8"
					6752'
					PACKER SET
26. Perforation record (interval, size, and number) Dri: 6568-72, 86-90, 6610-16, 44-50, 72-76 2 SPF Tu: 6236-40, 54-58, 6296-6302, 6326-30 2 SPF Bli: 5910-14, 34-40, 93-97, 6044-48 2 SPF			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 6568 - 6676' 3Kgals 15%HCl, 42Kgals gel & 62K# 20/40 sd 6236 - 6330' 3Kgals 15%HCl, 40Kgals gel & 62K# 20/40 sd 5910 - 6048' 3Kgals 15%HCl, 30Kgals gel & 50K# 20/40/sd		
28. PRODUCTION					
Date First Production 07/26/2007		Production Method (Flowing, gas lift, pumping - Size and type pump) Rod Pump - Pumping		Well Status (Prod. or Shut-in) Producing	
Date of Test 08/05/2007	Hours Tested 24 hours	Choke Size	Prod'n For Test Period	Oil - Bbl 28	Gas - MCF 186
				Water - Bbl. 21	Gas - Oil Ratio 6643
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold				Test Witnessed By Apache	
30. List Attachments Inclination Report, C-102, C-103, C-104					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature 		Printed Name Sophie Mackay		Title Engineering Tech	
E-mail Address sophie.mackay@apachecorp.com		Date 08/09/2007			

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2638'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2860'	T. Devonian	T. Menefee	T. Madison
T. Queen 3411'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3676'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3976'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5174'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry 5649'	T. Gr. Wash	T. Morrison	T.
T. Tubb 6126'	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6459'	T. Bone Springs	T. Entrada	T.
T. Abo 6717'	T. Rustler 1235'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology