| Submit 3 Copies To Appropriate District Office District 1  State of New Mexico Energy, Minerals and Natural R |                            |                                   | Form C-10<br>May 27, 20  |           |
|---|----------------------------|-----------------------------------|--|-----------|
| <u>District I</u><br>1625 N French Dr , Hobbs, NM 88240   | Ellergy, willierars an     | na Naturai Resources              | WELL API NO.   | ~~        |
| District II   | OIL CONSERVA               | ATION DIVISION                    | 30-041-20325   |           |
| 1301 W Grand Ave, Artesia, NM 88210<br>District III   |                            | St. Francis Dr.                   | 5. Indicate Type of Lease  |           |
| 1000 Rio Brazos Rd., Aztec, NM 87410  |                            | NM 87505                          | STATE S FEE 6. State Oil & Gas Lease No.   |           |
| District IV<br>1220 S. St. Francis Dr., Santa Fe, NM<br>87505   |                            |                                   | K-4128   |           |
|   |                            | N OR PLUG BACK TO A               | 7. Lease Name or Unit Agreement Name   | 3         |
| PROPOSALS)  |                            | e for a coorr                     | State "CO"  8. Well Number  1  |           |
|   | Gas Well Other             |                                   |  |           |
|   | d Operating, Inc.          |                                   | 9. OGRID Number  |           |
| 3. Address of Operator 505 N. Big   | Spring, Suite 204, Midland | d, Texas 79701-4347               | 10. Pool name or Wildcat Bluitt (San Andres) Assoc.  |           |
| 4. Well Location  |                            | ,                                 |  |           |
|   | 1,980 feet from the        | South line and                    | 660 feet from the West line  |           |
| Section 16  | Township 8-S               | Range 38-E                        | NMPM Roosevelt County  |           |
|   |                            | ther DR, RKB, RT, GR, et<br>95 DF | (c.)   | llin S. A |
| Pit or Below-grade Tank Application 🛛 o   |                            | )) DI                             | ja asulut op die enzembalische Statische Ausbelle in Gert  |           |
| Pit typeSTEELDepth to Groundwater   | Distance from neare        | st fresh water well> 1 mi         | ile Distance from nearest surface water> 1 mile  | 2         |
| Pit Liner Thickness: STEEL mi   | il Below-Grade Tank: Vo    | lume 180 bbls;                    | Construction Material STEEL  |           |
| 12. Check A   | appropriate Box to Ind     | icate Nature of Notice            | e, Report or Other Data  |           |
| NOTICE OF IN  | TENTION TO                 | l SU                              | BSEQUENT REPORT OF:  |           |
| PERFORM REMEDIAL WORK   |                            | □ REMEDIAL WC                     |  |           |
| TEMPORARILY ABANDON 🔲   |                            | _ :                               | RILLING OPNS.□ P AND A [   | コ         |
| PULL OR ALTER CASING  | MULTIPLE COMPL             | CASING/CEME                       | NT JOB   | _         |
| OTHER:  | lated apprations (Clarry)  | OTHER:                            | Land give pertinent dates, including estimated   | doto      |
|   |                            |                                   | Attach wellbore diagram of proposed comple   |           |
| 85/8" 24# csg @ 449' w/ 300 sx circ;  | 4½" 9.5# csg @ 4,844' w/   | 350 sx, TOC 3,700' by             | $\Gamma$ S, open perforations 4,789' $-$ 4,814'  |           |
| 1. Set CIBP @ 4,739'. Circula   | ate hole w/ mud and pump   | 15 sx C cmt on CIBP.              |  |           |
| 2. Perforate & squeeze 35 sx C  | C cmt 2,700 – 2,600'. base | of salt plug WOC 7                | TAG  TAG  TO THE |           |
| 3. Perforate & squeeze 35 sx 0  |                            |                                   | 10 272   |           |
| 4. Perforate & squeeze 50 sx C  |                            |                                   |  | 15.       |
| •   |                            | TAG surjuce cusing she            | e ping Se  | 32        |
| 5. Circulate 15 sx C cmt 50' to   |                            |                                   | 12 08 NO. 120  | 2         |
| 6. Cut off wellhead & anchors   | , install dry hole marker. |                                   | \c_  | S/ S      |
|   |                            |                                   | Tes.   | 7         |
|   |                            |                                   | 15.05.62.82  |           |
|   |                            |                                   |  |           |
| I hereby certify that the information a grade tank has been/will be constructed or                            | ibove is true and complete | to the best of my knowled         | lge and belief. I further certify that any pit or bel<br>☐ or an (attached) alternative OCD-approved plan [  | ow-       |
|   |                            | 2.3, a Gonerar per mire (         | _ or un (armened) arect native oes approved plan [   | ٠.        |
| SIGNATURE T   | <u> </u>                   | TLEEngineer                       | DATE08/22/07   |           |
|   | ewman, P.E. E-             | -mail address: jim@tripl          | enservices.com Telephone No. 432-687-1   | 994       |
| For State Use Only  | 1, , ,                     |                                   |  |           |
| APPROVED BY Laugh   | ). Wink TI                 | TLE                               | DATE   |           |
| Conditions of Approval (if arty):   | ^^                         | ATASSAMILL                        | IME Warms  |           |
|   |                            | STO REPRESENTED                   | à ban  |           |

## CURRENT WELLBORE SKETCH McDonnold Operating

| RKB @<br>DF @<br>GL @  | 3,995 |  | Lease & Well No                      | State "CO" no. 1   |
|--|-------|--|--------------------------------------|--|
|  |       |  | Legal Description  County Field      | UL L 1,980' FSL & 660' FWL, Sec 16, T8S, R38E  Roosevelt State New Mexico  Bluitt (San Andres) Assoc |
|  |       | 12-1/4" Hole   | Date Spudded<br>API Number<br>Status | Rig Released<br>30-041-20325<br>Current  |
| Telegraphic Control of the Control o |       | 8-5/8" 24# @ 449' cmt'd w/ 300 sx circ to surface                                  |                                      |  |
|  |       | Top of salt @ 2,300  |                                      |  |
|  |       | Base of salt @ 2,700   |                                      |  |
|  |       | 7-7/8" Hole<br>TOC @ 3,700 by TS   |                                      |  |
|  |       | perfs<br>4,789 - 4,814<br><b>4-1/2" 9.5# @ 4844' cmt'd w/ 350 sx</b><br>7-7/8 hole |                                      |  |
| PBTD<br>TD   | 4844  | , no note  |                                      |  |

## PROPOSED PLUGGED WELLBORE SKETCH McDonnold Operating

|                          | IVI  | CDOMINION OPERALI    | ''y  |                             |  |  |  |  |
|--------------------------|--|----------------------|--|-----------------------------|--|--|--|--|
| В@                       |  |                      |  | Date <u>August 22, 2007</u> |  |  |  |  |
| F @ 3,995                |  |                      |  |                             |  |  |  |  |
| L@                       |  | Lease & Well No      | State "CO" no. 1 UL L 1,980' FSL & 660' FWL.                                     | C 40 TOC D39F               |  |  |  |  |
|                          |  | Legal Description    | ULL 1,980 FSL & 660 FVVL   | Sec. 10, 103, K30E          |  |  |  |  |
| 1/2//////                | 15 sx C cmt 50' to surface   | County               | Roosevelt State  | New Mexico                  |  |  |  |  |
|                          |  | Field                | Bluitt (San Andres) Assoc  |                             |  |  |  |  |
|                          |  | Date Spudded         |  | Released                    |  |  |  |  |
|                          |  | API Number<br>Status | 30-041-20325<br>PROPOSED PLUGGED   |                             |  |  |  |  |
|                          |  | Status               | 11107 00257 200025   |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          | 12-1/4" Hole   |                      |  |                             |  |  |  |  |
| <b>2</b> //// <b>X</b> 4 | 8-5/8" 24# @ 449' cmt'd w/ 300 sx circ to surface  |                      |  |                             |  |  |  |  |
|                          | Perf/sqz 35 sx C cmt 509 - 409' WOC & TAG  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  | - T                  | TAIPLE N   |                             |  |  |  |  |
|                          |  | 4                    | LAJ SERVICES INC<br>MIDLANG, TX  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      | PROPOSED PLUGGI  | IG PROCEDURE                |  |  |  |  |
|                          |  |                      | 1) Set CIBP @ 4,739'   |                             |  |  |  |  |
|                          |  |                      | 2) 15 sx C cmt 4,739 -4,52   | 2'                          |  |  |  |  |
|                          |  |                      | <ol> <li>Perf/sqz 35 sx C cmt 2,</li> </ol>                                      | 700 - 2,600'                |  |  |  |  |
|                          |  |                      |  | 800 - 2,200' WOC & TAG      |  |  |  |  |
|                          |  |                      | <ul><li>5) Perf/sqz 35 sx C cmt 50</li><li>6) 15 sx C cmt 50' to surfa</li></ul> |                             |  |  |  |  |
|                          |  |                      | -,   |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  | L                    |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          | Top of salt @ 2,300  |                      |  |                             |  |  |  |  |
| <b>2</b> /// <b>X</b> 2  | Perf/sqz 35 sx C cmt 2,300 - 2,200' W  | OC & TAG             |  |                             |  |  |  |  |
| 11 11                    |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          | Base of salt @ 2,700 Perf/sqz 35 sx C cmt 2,700 - 2,600'   |                      |  |                             |  |  |  |  |
| 4///4                    | Petroque de de contra per la c |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          | 7-7/8" Hole  |                      |  |                             |  |  |  |  |
|                          | TOC @ 3,700 by TS  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
| 1///                     |  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          | 45 av C amt 4 730 4 533  |                      |  |                             |  |  |  |  |
| K//A                     | 15 sx C cmt 4,739 -4,522'<br>Set CIBP @ 4,739'   |                      |  |                             |  |  |  |  |
|                          | perfs  |                      |  |                             |  |  |  |  |
|                          | 4,789 - 4,814  |                      |  |                             |  |  |  |  |
| ПП                       | • •  |                      |  |                             |  |  |  |  |
|                          |  |                      |  |                             |  |  |  |  |
|                          | 4-1/2" 9.5# @ 4844' cmt'd w/ 350 sx  |                      |  |                             |  |  |  |  |
|                          | 7-7/8 hole   |                      |  |                             |  |  |  |  |

PBTD TD 4844