

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003	
		WELL API NO. 30-025-38397		5. Indicate Type of Lease STATE ☐ FEE ☒	
		State Oil & Gas Lease No. N/A		7. Lease Name or Unit Agreement Name Blankenship	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____ b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER _____				8. Well No 4	
2. Name of Operator Apache Corporation				9. Pool name or Wildcat House; Blinebry S / House; Tubb	
3. Address of Operator 6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224				4. Well Location Unit Letter L : 2310 Feet From The South Line and 990 Feet From The West Line Section 12 Township 20S Range 38E NMPM Lea 293031-123456 County AA	
10. Date Spudded 06/10/2007		11. Date T.D Reached 06/18/2007		12. Date Compl. (Ready to Prod.) 08/08/2007	
13. Elevations (DF& RKB, RT, GR, etc.) 3,563'		14. Elev. Casinghead 2526'		15. Total Depth 7330'	
16. Plug Back T.D. 6919' RBP		17. If Multiple Compl. How Many Zones? 2		18. Intervals Drilled By X	
19. Producing Interval(s), of this completion - Top, Bottom, Name 6034-6316' (House; Blinebry S) / 6608-6797' (House; Tubb)				20. Was Directional Survey Made No	
21. Type Electric and Other Logs Run SD/DSN, DLL-MG, Long Spaced Sonic				22. Was Well Cored No	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	1,575'	12-1/4"	800 sx / circ	
5-1/2"	17#	7,330'	7-7/8"	1,350 sx / TOC 1200' EST	
24. LINER RECORD			25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	PACKER SET
26. Perforation record (interval, size, and number) Blinebry: 6034-38, 88-92, 6129-33, 76-80, 6238-42, 6312-16 (2 JSPF) Tubb: 6608-12, 31-35, 52-56, 6715-19, 47-51, 93-97 (2 JSPF)			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 6034-6316 2Kgal 15%HCl, 42Kgal SS-25 + 82K# 20/40 6608-6797 2Kgal 15%HCl, 38Kgal SS-25 + 82K# 20/40		
28. PRODUCTION					
Date First Production 08/08/2007		Production Method (<i>Flowing, gas lift, pumping - Size and type pump</i>) Pumping - Rod Pump		Well Status (<i>Prod. or Shut-in</i>) Producing	
Date of Test 08/09/2007	Hours Tested 24 hours	Choke Size	Prod'n For Test Period	Oil - Bbl 20	Gas - MCF 68
Water - Bbl. 176	Gas - Oil Ratio 3400	Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil Gravity - API - (Corr.) 36.6
29. Disposition of Gas (<i>Sold, used for fuel, vented, etc</i>) Sold					Test Witnessed By Apache Corporation
30. List Attachments Deviation Report, Logs, C-102's, C-103's, C-104's					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature <i>[Signature]</i> E-mail Address sophie.mackay@apachecorp.com		Printed Name Sophie Mackay		Title Engineering Tech Date 08/16/2007	

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2865'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 3088'	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4258'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5605'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry 6034'	T. Gr. Wash	T. Morrison	T.
T. Tubb 6536'	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6856'	T. Bone Springs	T. Entrada	T.
T. Abo 7102'	T. Rustler 1530'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology