Submit 3 copies to Appropriate District Office	State of	New Mexico		Form C-103			
DISTRICT I 1625 N. French Dr., Hobbs NM 88240	Energy, Minerals and Natural Resources		WELL API NO.	Revised March 25, 1999			
DISTRICT II 1301 W. Grand Avenue, Artesia NM 88210	OIL CONSERVATION BUY (ICION			22602			
DISTRICT III	1220 South St. Francis Dr.		5. Indicate Type of Lease				
1000 Rio Brazos Rd., Aztec NM 87410	Santa Fe, New Mexico 87504-2088		STATE X F	STATE X FEE			
DISTRICT IV 1220 S. St. Francis Dr., Santa Fe, NM 87505			6. State Oil & Gas Lease				
SUNDRY NOTICES AND REPORTS ON WELLS			VA-50				
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Lease Name of Onit A	greement Name			
1. Type of Well:			Treat AS.	J State			
Oil Well X Gas Well Other							
2. Name of Operator		****	8. Well No.				
Yates Petroleum Corporation			1	1			
3. Address of Operator	South 4th Str., Artesia,	NM 88210	9. Pool Name or Wildcat Wildcat Bone				
4. Well Location		14101 00210	VVIIdcat Boll	e oprings			
Unit Letter B: 660	feet from the North	line and 1980	feet from the East	line			
	Township 21S Range		County	Lea			
	evation <i>(Show whether DF, RI</i> 3580' GR						
11. Check Appropriate Box		ce, Report, or Other Data					
NOTICE OF IN	TENTION TO:	SUBSEQUE	ENT REPORT OF:				
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING				
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT				
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB	Ħ				
OTHER:	COMPLETION	OTHER:					
12 Describe proposed or complet	ted operations (Clearly state at	l pertinent details, and give pertinent	datas including actimated data				
		le Completions: Attach wellbore diag		е			
Propose to P&A as follow	rs:						
1) MIRU and install BOP.							
2) Set CIBP @ 7650' and dump 35' cement on plug.							
3) Perforate squeeze holes @ 5780'. Set 100' plug 5780-5680' inside and outside casing. WOC and tag							
4) Perforate squeeze holes @ 3684'. Set 100' plug 3684-3584' inside and outside casing. Woodand tag.							
		00' plug 2045-1945' inside an	- / 15				
		0' plug 517-417' inside and oเ	- ,	-			
7) Spot 60' plug @		o plag of the molac and oc	itolde casing. VVOC and	lag.			
8) Install marker a		THE COMMISSION MUST B	ENOTIFIED 24	2012			
· ·	ind clean location.	HOURS PRIOR TO THE BE PLUGGING OPERATIONS F TO BE APPROVED.	GINNING OF \6.				
Thereby certify that the information	n above a true and complete to	the best of my knowledge and belief		······································			
SIGNATURE	TITL			10/9/03			
	ni Davis		Telephone No	05;748-1471			
(This space for State use) APPROVED BY Conditions of approval, if any:	1 W. Wink TITL	E OC DISTRICT SUPERVISOR,	GENERAL MANAGER	607 1 6 Mark			

well name:	Treat ASJ State	No. 1 Field	U. San Simon No	rtheast	
Location:	660' FNL & 1980' FE	L Sec. 34-21S-35E Lea Co	, NM		
GL: <u>3550'</u>	Zero:	AGL:	KB:	3596.5'	
Spud Date:	Completion Date:				
Comments:					

Casing Program				
Size/Wt/Grade/Conn	Depth Set			
13 3/8" 54.5#	467'			
9 5/8° 36 & 40# L80 & J55	5730'			
7° 26# L80 & S95	10400'			

17 1/2" hole 12 1/4" hole 7 7/8" hole CIBP @ 7650" + 35' cement CIBP @ 10350'+ 35' cement 58 sx plug 11550-850'

TD 12930'

60' cement plug @ surface.

13 3/8" csg @ 467'. Cmtd w/ 450 sx. Cmt circ. Perf @ 517'. 100' cement plug 517'-417'

Perf @ 1995'. 100' cement plug 2045'-1945'. WOC & tag

Perf @ 3684'. 100' cement plug 3684'-3584'. WOC & tag

DV tool @ 4180'

9 5/8" csg @ 5730'. Cmtd w/ 3000 sx. Cmt circ.

Perf @ 5780'. 100' cement plug 5780'-5680'. WOC and tag.

PROPOSED CONFIGURATION

1865"

Salt 1995' Base Salt 35841 Yates 3823' Reef 4191' Delaware 5563' Bone Spring 7515' Wolfcamp 10348 Strawn 11088 Atoka 11565' 12251' Morrow

Tops:

Rustler

TOC 7008' by CBL

Bone Spring perfs 7692'-7718'

7" csg @ 10400'. Cmtd w/ 575 sx.

OH Wolfcamp completion 10400'-11550'

SKETCH NOT TO SCALE

DATE: 10/8/03