New Mexico Oil Conservation Division, District I

1625 N. French Drive Hobbs, NM 88240

Form 3160-5

UNITED STATES

FORM APPROVED

(April 2004)	DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT			Expire	No 1004-0137 s March 31, 2007	
CHND	BUREAU OF LAND MAN		/ELLS	5 Lease Senal No NM 05	559817 6559817	
Do not use	this form for proposals t well. Use Form 3160-3 (to drill or to r	e-enter an	6 If Indian, Allot	tee or Tribe Name	
				7 If Unit or CA/A	greement, Name and/or No	
	TRIPLICATE- Other inst	ructions on rev	rerse side.		.b. someth, I take a law of I to	
l Type of Well ✓ Oil Well	Gas Well Other	8 Well Name and				
2. Name of Operator Chevr	on Midcontinent, L.P.	Federal "17" 9 API Well No.				
3a Address		lude area code)	30-041-2031	5		
	Aidland, Texas 79705 Sec , T., R., M , or Survey Description)	432-561-8600			, or Exploratory Area ndres Associated	
660' FSL & 810' FEL	sec, 1., re, m, or survey bescription	11 County or Par	ish, State			
UL-P, Sec. 17-R08S-T38	E			Roosevelt, N	ew Mexico	
12. CHECK	APPROPRIATE BOX(ES) TO) INDICATE NAT	URE OF NOTICE,	, REPORT, OR OT	HER DATA	
TYPE OF SUBMISSION	TYPE OF SUBMISSION TYPE OF ACTION					
Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construct Plug and Aband Plug Back	on Reclamatio	e Uy Abandon	Water Shut-Off Well Integrity Other	
determined that the site is TOP OF CEMENT NO INDICATION 1. Notify BLI 2. RIH and so 3. Displace ho 4. Spot 25sx o *** 5. Spot 25sx o *** 6. Spot 40sx o 7. Install dry *** A. BASE OF	d Final Abandonment Notices shall be ready for final inspection. THAT CEMENT CMINATOMINAT	CING IS UNIFICULATED or to MI&RI spot 25sx of crine w/25 gel 2,600° (B.Sal 2,200° (T. sal urface (shoe/I	KNOWN, SE CONDI cement from 4 p/bbl. t est.) WOC & t est.) WOC & Fresh Water/s	:E AI IACH ITIONS OF 4,575'-4,325' (P & TAG. & TAG.	erfs). **TAGE SEPTEMBER **TA	
***** PERF A	ND SQUEEZE PL	UE,				
Name <i>(Printed/Type)</i> M. Lee Roa	'	Tıt	e Agent			
Signature	Su Kimal	Da	te	09/02/2007		
	THIS SPACE FOR	FEDERAL O	R STATE OFF	ICE USE		
Approved by /S/ A	LEXIŚ C. SWOI	BODA 1	PETROLEUN	ENGINEER	SEP 0 7 2007	
Approved by Conditions of approval, if any	, are attached Approval of this notic			Daic	V 8 <u>-</u>	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Office

(Instructions on page 2)

which would entitle the applicant to conduct operations thereon

certify that the applicant holds legal or equitable title to those rights in the subject lease

Federal 17A #2

Location: 660' FSL & 810' FEL, Sec 17, T8S, R38E, Roosevelt County, New Mexico

ASSET GROUP: North Permian

FIELD: Bluitt San Andres Associated

LEASE/UNIT: Federal 17A

COUNTY: Roosevelt

DATE CHKD: BY:

May. 06, 1997 J. W. King

WELL:

STATE:

New Mexico

SPUD DATE: 04/19/71

COMP. DATE: 05/12/71 CURRENT STATUS: Producer

KB = 12' AGL

Elevation = 3969.5' GL TD = 4796'

ETD = 4785'

API = 30-041-20315

8-5/8" 24# J-55 csg. @ 355'. Cmt w/175 sx. Circ.

Perforations:

4768-74 w/1 JSPF (7 holes); 4747-62 w/1 JSPF (16 holes); 4749, 50, 52, 55, 59, 60, 61 w/1 JSPF (7 holes)

Perf'd the following intervals (05/06/93):

4619-38, 45-60, 82-91, 96-4705, 11-19 w/2 JSPF (125 holes).

TUBING DETAIL:

4681.48	149 jts	2-3/8" 4 7# J-55 8rd EUE tbg
3 12		anchor catcher
63.20	2 jts	2-3/8" 4.7# J-55 8rd EUE tbg
1.10		SN
4.05		perf sub
12 12		mud anchor
7.00		BKDB
4,772.07		FHD

Rods: 188 3/4"

Pump: Axelson RHBC 2" x 1-1/4" x 12', 13 SPM, 24" stroke length

Perfs: 4619' - 4774'

4-1/2" 9.5# K-55 csg @ 4796'. Cmt w/300 sx. Circ. TD 4796' PBTD 4785'

> **BLUITT XLS** Aug. 30, 2007

· :'