## **OCD-HOBBS**

Form 3160-5 (August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No 1004-0137 Expires: July 31, 2010

BUREAU OF LAND MANAGEMENT  SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.					5 Lease Serial No NM-0245247 6 If Indian, Allottee or Tribe Name			
1 Type of Well  ☑ Oil Wel! ☐ Gas Well ☐ Other					8 Well Name and No McElvain # 9			
Name of Operator McElvain Oil & Gas Properties, Inc.					9 API Well No 30-025-38481			
3a Address       3b. Phone No (include area code)         1050 - 17th Street, Suite 1800 Denver, Colorado 80265       (303) 893-0933 xtn 330					10 Field and Pool or Exploratory Area EK Delaware			
4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 1980' FNL & 1980' FWL (SENW) Section 25, T18S-R33E N M P M					11. Country or Parish, State Lea County, New Mexico			
12 CHEC	CK THE APPROPRIATE BOX(E	ES) TO IND	ICATE NATURE	OF NOTIC	CE, REPORT OR OTHE	ER DATA		
TYPE OF SUBMISSION		TYPE OF ACTION						
Notice of Intent  ✓ Subsequent Report	Alter Casing		en ure Treat Construction and Abandon	Reco	Production (Start/Resume) Reclamation Recomplete Temporarily Abandon		Water Shut-Off Well Integrity Other Spud & Surface Casing Set	
Final Abandonment Notice	Convert to Injection	Plug	Back	☐ Wate	r Disposal	****		
After setting 80' of 14" conductor pip September 5, 2007 with United Drilli fresh water zones nor any lost circul determination before running 43 join added throughout the string BJ cer the LEAD cement followed by 200 s completed with full returns at 6:00 A were shut down to WOC before instreasing commenced at 6:00 P.M on	ing, Inc's Rig # 28. An 11" sulation zones Maximum inclinats of 8.625", 32#, J55, ST&C mented the surface casing with acks of Premium Plus 'C' cemM on September 8, 2007 aftalling an 11"x3M wellhead, ins	rface casin ation throu casing. Th h 425 sack nent with ac er returning stalling a 'C	g hole was drilled gh the surface ho ne shoe joint and s of Premium Pludditives mixed at g 16 bbls of lead b' spool and doub	d 25 feet in ple was 0.7 next 2 join is 'C' cement to cement to le ram pre	nto the Russler Anhyo 75 degrees. A fluid ca the series of the series of the ent with additives mix and 1.34 Yield for the surface. There was eventer and testing the g)	drite There aliper was ru and 7 addition ed at 13.5 properties at 13.5 properties at 25 pro	was no indicat in for cement v nal centralizers pg and 1.7 Yie nt. The job wa all back. Open	tion of volume s were eld for is rations
14 I hereby certify that the foregoing is tr	are and correct				\	0, 18	好是	2
Name (Printed/Typed)  E. Reed Fischer	de and confect		Title Senior Op	erations E	Engineer	Of Of Class	·	1101,0
Signature 2 Res	mel		Date 09/10/200	7		- J	-वाकार-	
ACCEPTED O	R RETHIS SPACE FO	R FEDE	RAL OR STA	TE OFF	ICE USE			
Approved by /S/DAVI  Conditions of approval, if aby, are attached that the applicant holds legal or equitable to					D	ate		
entitle the applicant to conduct operations to Title 18 U.S.C. Section 100D and thirties of fictitious or flaudulem statements of lepter	U.S/GSSection 1212, make it a crim	ne for any pe	rson knowingly and	willfully to	make to any department	or agency of t	he United States	any false,

(Instructions on page 2)

