

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD-HOBBS

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

OXY USA WTP Limited Partnership

192463

3a. Address

P.O. Box 50250, Midland, TX 79710-0250

3b. Phone No. (include area code)

432-685-5717

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

238 FNL 1274 FWL NWNW(D) Sec 5 T24S R37E

5. Lease Serial No.

891038170 - NM7488

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No
Myers Langlie Mattix Unit

8. Well Name and No

269

9. API Well No.

30-025-32556

10. Field and Pool, or Exploratory Area
Langlie Mattix 7Rvr Qn-GB

11. County or Parish, State

Lea

NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent☐ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION


☐ Acidize☐ Alter Casing☐ Casing Repair☐ Change Plans☐ Convert to Injection☐ Deepen☐ Fracture Treat☐ New Construction☒ Plug and Abandon☐ Plug Back☐ Production (Start/Resume)☐ Reclamation☐ Recomplete☐ Temporarily Abandon☐ Water Disposal☐ Water Shut-Off☐ Well Integrity☐ Other _____

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomple horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

TD-3775' PBD-3416' Perfs-3466-3708' CIBP-3416'

8-5/8" 24# csg @ 426' w/260sx, 12-1/4" hole, TOC-Surf-Circ
5-1/2" 15.5# csg @ 3775' w/900sx, 7-7/8" hole, TOC-Surf-Circ

1. RIH & Tag CIBP @ 3416', M&P 25sx cmt
2. M&P 25sx cmt @ 2900-2800'
3. M&P 25sx cmt @ 1200-1100' WOC-Tag
5. M&P 75sx cmt @ 476'-Surface
10# MLF between plugs

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

David Stewart

Title

Sr. Regulatory Analyst

Date

9/5/07

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

GWW

OXY USA WTP LP - Proposed
Myers Langlie Mattix Unit #269
API No. 30-025-32556

75sx @ 476'-Surface

12-1/4" hole @ 426'
8-5/8" csg @ 426'
w/260sx-TOC-Surf-Circ

25sx @ 1200-1100' WOC-Tag


25sx @ 2900-2800'

25sx @ 3416-3316'

11/00-CIBP @ 3416'

7-7/8" hole @ 3775'
5-1/2" csg @ 3775'
w/900sx-TOC-Surf-Circ

Perfs @ 3466-3708'



TD-

OXY USA WTP LP - Current
Myers Langlie Mattix Unit #269
API No. 30-025-32556

12-1/4" hole @ 426'
8-5/8" csg @ 426'
w/260sx-TOC-Surf-Circ

11/00-CIBP @ 3416'

7-7/8" hole @ 3775'
5-1/2" csg @ 3775'
w/900sx-TOC-Surf-Circ

Perfs @ 3466-3708'

TD-