Form 3160-5 (September 2001)

UNITED STATES 1625 N. French Dr. DEPARTMENT OF THE INTERIOR NM 88240 BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires January 31, 2004

OLUMBI				I	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on reverse side			LC-032096-A 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or No.		
					I. Type of Well A Oil Well Gas Well
2. Name of Operator APACHE CORPORATION				LOCKHART A-17 #6	
3a. Address TWO WARREN PL., SUITE 1500 3b. Phone No. (include area code)			30-025-36101		
6120 S. YALE, TULSA, OK 74136-4224 (918) 491-4900 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			10. Field and Pool, or Exploratory Area PENROSE SKELLY; GRAYBURG		
1330' FNL, 990' FEL				11. County or Parish, State	
SEC. 17, T21S-R				ــــــــــــــــــــــــــــــــــــــ	NEW MEXICO
12. CHECK A	PPROPRIATE BOX(ES) TO	INDICATE NATU	RE OF NOTICE, I	REPORT, OI	R OTHER DATA
TYPE OF SUBMISSION		T	YPE OF ACTION		
Notice of Intent	Alter Casing	Deepen Fracture Treat New Construction	Production (Sta	rt/Resume)	□ Water Shut-Off □ Well Integrity □ Other SPUD; SET SURF
Subsequent Report	Casing Kepan				
Subsequent Report Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	Temporarily A Water Disposal		CSG; TD; SET PROD
Final Abandonment Notice 3. Describe Proposed or Comple If the proposal is to deepen di Attach the Bond under which following completion of the ir	Change Plans Convert to Injection ted Operation (clearly state all pertin rectionally or recomplete horizontally the work will be performed or provivolved operations. If the operation Final Abandonment Notices shall be by for final inspection.) MIRU, SPUD WELL 18-5/8" 24# J55 @	Plug Back nent details, including est y, give subsurface locati ride the Bond No. on file results in a multiple con e filed only after all requ 1/13/03 1600 401'. CEMEN	Water Disposal timated starting date of a cons and measured and to e with BLM/BIA. Requipletion or recompletion irrements, including recommendation of the best of	any proposed wrue vertical deprimed subsequen in a new interdamation, have 12-1/4" CLASS C	CSG. ork and approximate duration thereof. the of all pertinent markers and zones. It reports shall be filed within 30 days val, a Form 3160-4 shall be filed once been completed, and the operator has HOLE TO 401'. SET + 2% CACL + 0.125
Final Abandonment Notice 3. Describe Proposed or Comple If the proposal is to deepen di Attach the Bond under which following completion of the ir testing has been completed. I determined that the site is read	Change Plans Convert to Injection ted Operation (clearly state all pertinrectionally or recomplete horizontally the work will be performed or provivolved operations. If the operation Final Abandonment Notices shall be by for final inspection.) MIRU, SPUD WELL 18-5/8" 24# J55 @ #/SX CELLO FLAKE=	Plug Back nent details, including est y, give subsurface locati ide the Bond No. on file results in a multiple con e filed only after all requ 1/13/03 1600 401'. CEMEN =78 BBLS 14.8 RC 87 SX CEME	Water Disposal timated starting date of a cons and measured and to be with BLM/BIA. Requipiletion or recompletion direments, including recommendation with the wind of the with BLM/325 SX B PPG SLURRY WATER TO PIT. WE	any proposed we rule vertical depired subsequent in a new interlamation, have 12-1/4" CLASS C W/1.35 C OC.	CSG. ork and approximate duration thereof. the of all pertinent markers and zones. It reports shall be filed within 30 days val, a Form 3160-4 shall be filed once been completed, and the operator has HOLE TO 401'. SET + 2% CACL + 0.125
Final Abandonment Notice 3. Describe Proposed or Comple If the proposal is to deepen di Attach the Bond under which following completion of the ir testing has been completed. I determined that the site is read 1/14/03	Change Plans Convert to Injection Ted Operation (clearly state all pertine rectionally or recomplete horizontally the work will be performed or provisolved operations. If the operation is Final Abandonment Notices shall be by for final inspection.) MIRU, SPUD WELL 8-5/8" 24# J55 @ #/SX CELLO FLAKE=PLUG & HELD. CINDRILL & SURVEY 7-RAN LOGS. RIH W/W/475 SX 50:50 PC 0.125 #/SX CELLO	Plug Back nent details, including est y, give subsurface locati ide the Bond No. on file results in a multiple con e filed only after all requ 1/13/03 1600 401'. CEMEN =78 BBLS 14.8 RC 87 SX CEME -7/8" HOLE FR /5-1/2" 17# J OZ:CLASS C W/ FLAKE=207 BB :50 POZ:CLASS G SLURRY W/1.	Water Disposal timated starting date of a cons and measured and the with BLM/BIA. Requipiletion or recompletion direments, including recipies. HRS. DRILL TED W/325 SX PPG SLURRY WAS PPG SLURRY	any proposed we rule vertical depiried subsequent in a new interlamation, have 12-1/4" CLASS C W/1.35 C OC. 150'. SET AT 4 003 GPS SLURRY W + 5% SAL LD. BUM1	CSG. Ork and approximate duration thereof. this of all pertinent markers and zones. It reports shall be filed within 30 days val, a Form 3160-4 shall be filed once been completed, and the operator has HOLE TO 401'. SET + 2% CACL + 0.125 F/SX YIELD. BUMPED 150'. CEMENTED FP-6L + 5% SALT + /2.44 CF/SX YIELD. T + 0.003 GPS FP-6L PED PLUG & HELD.
Final Abandonment Notice 3. Describe Proposed or Comple If the proposal is to deepen di Attach the Bond under which following completion of the ir testing has been completed. I determined that the site is read 1/14/03 1/15/03-1/18/03 1/19/03	Change Plans Convert to Injection ted Operation (clearly state all pertin rectionally or recomplete horizontally the work will be performed or provivolved operations. If the operation Final Abandonment Notices shall be by for final inspection.) MIRU, SPUD WELL 8-5/8" 24# J55 @ #/SX CELLO FLAKE=PLUG & HELD. CINDRILL & SURVEY 7-RAN LOGS. RIH W/W/475 SX 50:50 PC 0.125 #/SX CELLO TAIL W/250 SX 50:=58 BBLS 14.2 PPC CIRC 35 SX CEMENT	Plug Back nent details, including est y, give subsurface locati ide the Bond No. on file results in a multiple con e filed only after all requ 1/13/03 1600 401'. CEMEN =78 BBLS 14.8 RC 87 SX CEME -7/8" HOLE FR /5-1/2" 17# J OZ:CLASS C W/ FLAKE=207 BB :50 POZ:CLASS G SLURRY W/1.	Water Disposal timated starting date of a cons and measured and the with BLM/BIA. Requipiletion or recompletion direments, including recipies. HRS. DRILL TED W/325 SX PPG SLURRY WAS PPG SLURRY	any proposed we rule vertical depiried subsequent in a new interlamation, have 12-1/4" CLASS C W/1.35 C OC. 150'. SET AT 4 003 GPS SLURRY W + 5% SAL LD. BUM1	CSG. Ork and approximate duration thereof. this of all pertinent markers and zones. It reports shall be filed within 30 days val, a Form 3160-4 shall be filed once been completed, and the operator has HOLE TO 401'. SET + 2% CACL + 0.125 F/SX YIELD. BUMPED 150'. CEMENTED FP-6L + 5% SALT + /2.44 CF/SX YIELD. T + 0.003 GPS FP-6L PED PLUG & HELD.
Final Abandonment Notice 3. Describe Proposed or Comple If the proposal is to deepen di Attach the Bond under which following completion of the ir testing has been completed. I determined that the site is read 1/14/03	Change Plans Convert to Injection ted Operation (clearly state all pertin rectionally or recomplete horizontally the work will be performed or provivolved operations. If the operation Final Abandonment Notices shall be by for final inspection.) MIRU, SPUD WELL 8-5/8" 24# J55 @ #/SX CELLO FLAKE=PLUG & HELD. CINDRILL & SURVEY 7-RAN LOGS. RIH W/W/475 SX 50:50 PC 0.125 #/SX CELLO TAIL W/250 SX 50:=58 BBLS 14.2 PPC CIRC 35 SX CEMENT	Plug Back nent details, including est y, give subsurface locati ide the Bond No. on file results in a multiple con e filed only after all requ 1/13/03 1600 401'. CEMEN =78 BBLS 14.8 RC 87 SX CEME -7/8" HOLE FR /5-1/2" 17# J OZ:CLASS C W/ FLAKE=207 BB :50 POZ:CLASS G SLURRY W/1.	Water Disposal timated starting date of a cons and measured and the with BLM/BIA. Requipiletion or recompletion direments, including recipies. HRS. DRILL TED W/325 SX PPG SLURRY WAS PPG SLURRY	any proposed wrue vertical depuired subsequen in a new interlamation, have 12-1/4" CLASS C W/1.35 C OC. 150'. SET AT 4 003 GPS SLURRY W + 5% SAL' LD. BUM1 /19/03 0	CSG. Ork and approximate duration thereof, this of all pertinent markers and zones. It reports shall be filed within 30 days val, a Form 3160-4 shall be filed once been completed, and the operator has HOLE TO 401'. SET + 2% CACL + 0.125 F/SX YIELD. BUMPED 150'. CEMENTED FP-6L + 5% SALT + /2.44 CF/SX YIELD. T + 0.003 GPS FP-6L PED PLUG & HELD. 200 HRS.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Title

Office

(Instructions on reverse)

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Approved by