Submit 3 Copies To Appropriate District State of New Me	exico Form C-103
District 1 Energy, Minerals and Natu	Iral Resources Revised May 08, 2003
1625 N. French Dr., Hobbs, NM 88240 District II	WELL API NO. 30-025-33574
District III OIL CONSERVATION 1301 W. Grand Ave., Artesia, NM 88210 District III 1220 South St. Fra:	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 8	
1220 S. St. Francis Dr., Santa Fe, NM 87505	V-4297
SUNDRY NOTICES AND REPORTS ON WELLS	6
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PL DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) F PROPOSALS.)	OR SUCH Coriander AOC State
1. Type of Well: Oil Well 🔲 Gas Well 🛄 Other Plug & Abandon	8. Well Number 2
2. Name of Operator Yates Petroleum Corporation	9. OGRID Number 025575
3. Address of Operator 105 So. 4th St Artesia, NM 882	10. Pool name or Wildcat Red Tank Delaware, West/RT Bone Sp
4. Well Location	
Unit Letter H : 1650 feet from the North	n line and 330 feet from the East line
Section 1 Township 23S R	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3731' GR	
12. Check Appropriate Box to Indicate N	
	SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS	
PULL OR ALTER CASING MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB
OTHER:	OTHER:
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
9-27-29-2003 - Moved in and rigged up pulling unit and plugging equipment. Nippled down wellhead and oppled up wellhead. Rigged up floor and tubing equipment. Shut down for night. 9-30-2003 - Tallied and picked up 2-3/8" workstring. RIH and tagged up at 7000'. Pulled up hole to next collar at 6990'. Shut well in for night. 10-1-2003 - Circulated hole with plugging mud. Spotted 10 sacks Class C Neat cement on top of CIBP at 7000'. Pulled up hole to 4840'. Spotted 25 sacks Class C Neat cement. POOH with 60 joints of tubing. Shut well in for night. WOC	
10-2-2003 - RIH with tubing and tagged plug at 4830'. Spotted 25 sacks Class C Neat cement. POOH with 60 joints. WOC 4 hours. RIH with tubing and tagged plug at 4677'. Pulled up hole to 2650'. Spotted 25 sacks Class C Neat cement from 2650-2403'. POOH with tubing. Shut well in for night. WOC. 10-3-2003 - Rigged up wireline. RIH and perforated 5-1/2" casing at 1285'. POOH and rigged down wireline. RIH with packer and tubing to 986'. Squeezed with 60 sacks Class C Neat cement. WOc 4 hours. RIH with	
I hereby certify that the information above is true and complete to the b	est of my knowledge and belief.
SIGNATURE Alana Clack TITLE REGULATORY COMPLIANCE DATE 10-22-03	
Type or print name DONNA CLACK	Telephone No505-748-1471
(This space for State use) OC DISTRICT SL	PERVISOR/GENERAL MANAGER
APPPROVED BY DATE	
Conditions of approval, if any:	Approved as to plugging of the Well Borc. Liability under bond is retained until

.

surface restoration is completed.

YATES PETROLEUM CORPORATION Coriander AOC State #2 Section 1-T23S-R32E Lea County, New Mexico

## SUNDRY NOTICE CONTINUED:

wireline – did not tag. POOH and rigged down wireline. Squeezed with 60 sacks Class C Neat cement. Shut well in for night. WOC.

10-4-6-2003 - RIH with tubing and tagged pluga t 1074'. POOH with tubing. Rigged upwireline. RIH and perforated 5-1/2" casing at 400'. POOH and rigged down wireline. Rigged down floor and tubing equipment. Nippled down BOP. Installed 5-1/2" X 2" swedge with valve. Circulated 120 sacks Class C Neat cement down 5-1/2" casing and up to surface of 8-5/8" casing. Shut well in for night. WOC.

10-7-2003 – Cement at surface. Dug out cellar. Cut off wellhead. Rigged down pulling unit and plugging equipment. Installed regulation abandonment marker. PLUGGED AND ABANDONED – FINAL REPORT. Plugging completed 10-6-2003.

Aanna Clack mg15,200<sup>3</sup>