WELL LOGS

κz API number: 30-005-00871 CELERO ENERGY II LP OGRID: Operator: # 42 Property: **ROCK QUEEN UNIT** T 13S R 31E ULSTR: H 26 surface 1980 FNL 660 FEL T 13S R 31E ULSTR: Н 26 BH Loc 660 FEL 1980 FNL KB: 4418 4408 DF: na Ground Level: 3090 TD: KB Datum: Completion Date: (1) Land: STATE Date Logs Received: 10/22/2007 Date Due in: (2) Date out: Confidential: NO Confidential period: 90 Days for State & Fee, 1 Year for federal Date Due In: (1) is equal to Completion Date (1) + 20 days Depth interval Logs 3052 Dual Spaced Compensated Neutron CNL/GR 2600 3020 Radial Bond Gamma Ray 2600 **OCD TOPS** Κz Rustler NL Strawn Atoka Tansill NL Yates NL 7 rvrs Austin NL Queen Penrose Grayburg San Andres Glorieta Blinebry Tubb Drinkard Abo Wolfcamp



API Well Number Banner

Report Description

This report shows a Well's API Number in Barcode format for purposes of scanning. The Barcode format is Code 39.



30025008710000

30 25 871

SWEENEY FEDERAL No.001

YATES PETROLEUM CORPORATION

Office	of New Mex		Form C-103			
District I Energy, Minera	als and Natura	al Resources	May 27, 2004			
1625 N. French Dr., Hobbs, NM 88240			WELL API NO. 30-005-00871			
District II 1301 W. Grand Ave., Artesia, NM 88210 OIL CONSE	RVATION I	DIVISION	5. Indicate Type of Lease			
District III 1220 Sou	istrict III 1220 South St. Francis Dr.					
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa	Fe, NM 875	505	STATE FEE 6. State Oil & Gas Lease No.			
1220 S. St. Francis Dr., Santa Fe, NM	District IV					
87505 SUNDRY NOTICES AND REPORTS	ONWELLS		7. Lease Name or Unit Agreement Name			
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO D DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (F		Rock Queen Unit				
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other			8. Well Number 42			
2. Name of Operator		9. OGRID Number				
Celero Energy II, LP			247128			
3. Address of Operator			10. Pool name or Wildcat			
400 W. Illinois, Ste 1601, Midland, TX 79701			Caprock Queen			
4. Well Location						
Unit Letter H: 1980 feet from the						
	ip 13S	Range 31E				
11. Elevation (Show	www.www.www.www.www.www.www.www.www.ww	RKB, RT, GR, etc.)				
Pit or Below-grade Tank Application or Closure						
Pit type Depth to Groundwater Distance from			ince from nearest surface water			
Pit Liner Thickness: mil Below-Grade Tank:			nstruction Material			
12. Check Appropriate Box to	Indicate Na	ture of Notice, I	Report or Other Data			
NOTICE OF INTENTION TO:		SHR	SEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABAND		REMEDIAL WORK				
TEMPORARILY ABANDON CHANGE PLANS						
PULL OR ALTER CASING MULTIPLE COMPL		CASING/CEMENT				
	_					
OTHER:			e-activate			
OTHER: 13. Describe proposed or completed operations. (Clean	arly state all pe	ertinent details, and	give pertinent dates, including estimated date			
OTHER: 13. Describe proposed or completed operations. (Cleor of starting any proposed work). SEE RULE 1103	arly state all pe	ertinent details, and	give pertinent dates, including estimated date			
OTHER: 13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 1103 or recompletion.	arly state all pe	ertinent details, and	give pertinent dates, including estimated date			
OTHER: 13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007	early state all pe 3. For Multiple	ertinent details, and Completions: Att	give pertinent dates, including estimated date ach wellbore diagram of proposed completion			
OTHER: 13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 1103 or recompletion.	early state all pe 3. For Multiple 34" bit, bit sub	ertinent details, and Completions: Att	give pertinent dates, including estimated date ach wellbore diagram of proposed completion Tag @ 3031'. Clean out to 3077'. Drilled			
OTHER: 13. Describe proposed or completed operations. (Clessof starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4	arly state all pe 3. For Multiple 3/4" bit, bit sub 1/2" tapper mill	ertinent details, and completions: Att 3 1/8" DC's & tbg. 3 1/8" DC's & tbg	give pertinent dates, including estimated date ach wellbore diagram of proposed completion Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH.			
OTHER: 13. Describe proposed or completed operations. (Clessof starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guidents.	arly state all pe 3. For Multiple 3/4" bit, bit sub: 1/2" tapper mill de (2.10'); 1 t.	ertinent details, and completions: Att 3 1/8" DC's & tbg. 3 1/8" DC's & tbg	give pertinent dates, including estimated date ach wellbore diagram of proposed completion Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH.			
OTHER: 13. Describe proposed or completed operations. (Cless of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2%	arly state all pe 3. For Multiple 3" bit, bit sub; 3" tapper mill de (2.10'); 1 t. 4 3022'. 6 FL52A & .2%	ertinent details, and c Completions: Att 3 1/8" DC's & tbg. , 3 1/8" DC's & tbg 4" 9.5# J-55 UFL c	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. ssg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru			
OTHER: 13. Describe proposed or completed operations. (Clessof starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @	arly state all pe 3. For Multiple 3" bit, bit sub; 3" tapper mill de (2.10'); 1 t. 4 3022'. 6 FL52A & .2%	ertinent details, and c Completions: Att 3 1/8" DC's & tbg. , 3 1/8" DC's & tbg 4" 9.5# J-55 UFL c	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. ssg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru			
OTHER: 13. Describe proposed or completed operations. (Clessof starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000#	arly state all persons. For Multiple 3. For Multiple 3. For Multiple 1/2" tapper mill de (2.10'); 1 t. 3022'. 6 FL52A & .2% tension. Drille	ertinent details, and completions: Attended of the Completions: Attended of the Completions: Attended of the Completions: Attended of the Completion of the	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. ssg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru in to 3022'.			
OTHER: 13. Describe proposed or completed operations. (Clessof starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2	arly state all persons. For Multiple 34" bit, bit sub 1½" tapper mill de (2.10'); 1 t. 4 3022'. 6 FL52A & .2% tension. Drille 2700'. Found to	ertinent details, and Completions: Attached Atta	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. ssg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru ar to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4			
OTHER: 13. Describe proposed or completed operations. (Clean of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2 holes @ 2800'. POOH w/ csg gun. RU & squeeze perfs @	arly state all persons are all persons. For Multiple 34" bit, bit sub 1/2" tapper mill de (2.10'); 1 t. 4 3022'. 6 FL52A & .2% tension. Drille 2700'. Found to 2800' as follows.	ertinent details, and Completions: Attached Atta	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. ssg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru ar to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 POZ mix w/ .2% FL52A and .2% SMS. Tail			
OTHER: 13. Describe proposed or completed operations. (Clessof starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2	arly state all persons are all persons. For Multiple 3/4" bit, bit sub 1/2" tapper mill de (2.10'); 1 t. 4 3022'. 6 FL52A & .2% tension. Drille 2700'. Found to 2800' as follows. SITP 1060	ertinent details, and a Completions: Attach at 1/8" DC's & tbg., 3 1/8" DC's & tbg. 4" 9.5# J-55 UFL completed at 2828'. 6 SMS. Tail w/ 60 and cont & float collar cop of cmt @ 2828'. 2 pws: Lead w/ 50/50 psi. POOH w/ tbg	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. ssg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru ar to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 POZ mix w/ .2% FL52A and .2% SMS. Tail g. & pkr. RIH w/ bit, bit sub & tbg. Tag cmt			
OTHER: 13. Describe proposed or completed operations. (Cles of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2 holes @ 2800'. POOH w/ csg gun. RU & squeeze perfs @ w/ 60 sx Class C w/ 2% CACL. Did not circ thru 5 1/2" cs @ 2722'. Drilled cmt to 2820'. Circ. hole clean. RIH to 3	arly state all persons are all	ertinent details, and a Completions: Attach at 1/8" DC's & tbg. 3 1/8" DC's & tbg. 4" 9.5# J-55 UFL completed at 2828'. 6 SMS. Tail w/ 60 and cont & float collar cop of cmt @ 2828'. 5 ows: Lead w/ 50/50 psi. POOH w/ tbg. 4 hrs. RIH to 3088	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. seg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru ar to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 POZ mix w/ .2% FL52A and .2% SMS. Tail g. & pkr. RIH w/ bit, bit sub & tbg. Tag cmt '.			
OTHER: 13. Describe proposed or completed operations. (Cles of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2 holes @ 2800'. POOH w/ csg gun. RU & squeeze perfs @ w/ 60 sx Class C w/ 2% CACL. Did not circ thru 5 1/2" cs @ 2722'. Drilled cmt to 2820'. Circ. hole clean. RIH to 3 RIH w/ logging tools. Ran CBL/CCL/GR log s from 3025	arly state all person of the s	ertinent details, and a Completions: Attach at 1/8" DC's & tbg. 3 1/8" DC's & tbg. 4" 9.5# J-55 UFL completions of cont & float collar op of cont @ 2828'. bows: Lead w/ 50/50 psi. POOH w/ tbg. 4 hrs. RIH to 3088 DC @ 2790'. (Squeen)	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. seg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru ar to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 POZ mix w/ .2% FL52A and .2% SMS. Tail & pkr. RIH w/ bit, bit sub & tbg. Tag cmt '. seezed holes @ 2800'). RIH w/ 4" nickel			
OTHER: 13. Describe proposed or completed operations. (Cles of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2 holes @ 2800'. POOH w/ csg gun. RU & squeeze perfs @ w/ 60 sx Class C w/ 2% CACL. Did not circ thru 5 1/2" cs @ 2722'. Drilled cmt to 2820'. Circ. hole clean. RIH to 3 RIH w/ logging tools. Ran CBL/CCL/GR log s from 3025 plated AS-1 pkr w/ 1.5 F nipple, on/off tool, 91 jts. 2 3/8".	arly state all person of the s	ertinent details, and a Completions: Attach at 1/8" DC's & tbg. 3 1/8" DC's & tbg. 4" 9.5# J-55 UFL c 6 SMS. Tail w/ 60 6 cd cmt & float collar op of cmt @ 2828'. ows: Lead w/ 50/50 psi. POOH w/ tbg. 4 hrs. RIH to 3088 OC @ 2790'. (Squeet @ 2967'. Set pk.	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. ssg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru ar to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 POZ mix w/ .2% FL52A and .2% SMS. Tail g. & pkr. RIH w/ bit, bit sub & tbg. Tag cmt '. sezed holes @ 2800'). RIH w/ 4" nickel cr @ 2967'. ND BOP. Flange up WH. Tested			
OTHER: 13. Describe proposed or completed operations. (Cles of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2 holes @ 2800'. POOH w/ csg gun. RU & squeeze perfs @ w/ 60 sx Class C w/ 2% CACL. Did not circ thru 5 1/2" cs @ 2722'. Drilled cmt to 2820'. Circ. hole clean. RIH to 3 RIH w/ logging tools. Ran CBL/CCL/GR log s from 3025	arly state all person of the s	ertinent details, and a Completions: Attach at 1/8" DC's & tbg. 3 1/8" DC's & tbg. 4" 9.5# J-55 UFL c 6 SMS. Tail w/ 60 6 cd cmt & float collar op of cmt @ 2828'. ows: Lead w/ 50/50 psi. POOH w/ tbg. 4 hrs. RIH to 3088 OC @ 2790'. (Squeet @ 2967'. Set pk.	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. seg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru ar to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 pOZ mix w/ .2% FL52A and .2% SMS. Tail g. & pkr. RIH w/ bit, bit sub & tbg. Tag cmt ar weezed holes @ 2800'). RIH w/ 4" nickel cr @ 2967'. ND BOP. Flange up WH. Tested			
OTHER: 13. Describe proposed or completed operations. (Cless of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4. RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2 holes @ 2800'. POOH w/ csg gun. RU & squeeze perfs @ w/ 60 sx Class C w/ 2% CACL. Did not circ thru 5 1/2" cs @ 2722'. Drilled cmt to 2820'. Circ. hole clean. RIH to 3. RIH w/ logging tools. Ran CBL/CCL/GR log s from 3025 plated AS-1 pkr w/ 1.5 F nipple, on/off tool, 91 jts. 2 3/8" csg to 580 psi. Held ok. Put well on injection.	arly state all persons arranged to the state all persons are all persons are arranged to the state all persons are arranged to the state all persons are arranged to the state are are arranged to the state are are arranged to the state are are are are arranged to the state are are are are are are are are are ar	ertinent details, and a Completions: Attach at 1/8" DC's & tbg. 3 1/8" DC's & tbg. 4" 9.5# J-55 UFL c 6 SMS. Tail w/ 60 6 cd cmt & float collar op of cmt @ 2828'. ows: Lead w/ 50/50 psi. POOH w/ tbg 4 hrs. RIH to 3088 OC @ 2790'. (Squeet @ 2967'. Set pk	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. ssg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru at to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 POZ mix w/ .2% FL52A and .2% SMS. Tail g. & pkr. RIH w/ bit, bit sub & tbg. Tag cmt sezed holes @ 2800'). RIH w/ 4" nickel cr @ 2967'. ND BOP. Flange up WH. Tested co - 55') stand belief. I further certify that any pit or below-			
OTHER: 13. Describe proposed or completed operations. (Cless of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4. RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2 holes @ 2800'. POOH w/ csg gun. RU & squeeze perfs @ w/ 60 sx Class C w/ 2% CACL. Did not circ thru 5 1/2" cs @ 2722'. Drilled cmt to 2820'. Circ. hole clean. RIH to 3 plated AS-1 pkr w/ 1.5 F nipple, on/off tool, 91 jts. 2 3/8" csg to 580 psi. Held ok. Put well on injection.	arly state all persons arranged to the state all persons are all persons are arranged to the state all persons are arranged to the state all persons are arranged to the state are are arranged to the state are are arranged to the state are are are are arranged to the state are are are are are are are are are ar	ertinent details, and a Completions: Attach at 1/8" DC's & tbg. 3 1/8" DC's & tbg. 4" 9.5# J-55 UFL c 6 SMS. Tail w/ 60 6 cmt & float collar 7 op of cmt @ 2828'. 7 ows: Lead w/ 50/50 7 psi. POOH w/ tbg. 8 thrs. RIH to 3088 9 C @ 2790'. (Squeet @ 2967'. Set play 9 of my knowledge, a general permit 1 of	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. Tag (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru at to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 POZ mix w/ .2% FL52A and .2% SMS. Tail g. & pkr. RIH w/ bit, bit sub & tbg. Tag cmt "." Tag (2967'. ND BOP. Flange up WH. Tested (20-55) and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan			
OTHER: 13. Describe proposed or completed operations. (Clean of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2 holes @ 2800'. POOH w/ csg gun. RU & squeeze perfs @ w/ 60 sx Class C w/ 2% CACL. Did not circ thru 5 1/2" cs @ 2722'. Drilled cmt to 2820'. Circ. hole clean. RIH to 3 plated AS-1 pkr w/ 1.5 F nipple, on/off tool, 91 jts. 2 3/8" csg to 580 psi. Held ok. Put well on injection.	arly state all personal person	ertinent details, and a Completions: Attach at 1/8" DC's & tbg. 3 1/8" DC's & tbg. 4" 9.5# J-55 UFL completions at 1/8" DC's & tbg. 4" 9.5# J-55 UFL complete at 2828'. 6 SMS. Tail w/ 60 and could be a count & float collar collar collar count at 2828'. 6 SMS. Tail w/ 60 and count & float collar col	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. seg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru ar to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 POZ mix w/ .2% FL52A and .2% SMS. Tail & pkr. RIH w/ bit, bit sub & tbg. Tag cmt '. sezed holes @ 2800'). RIH w/ 4" nickel ar @ 2967'. ND BOP. Flange up WH. Tested and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan			
OTHER: 13. Describe proposed or completed operations. (Clean of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2 holes @ 2800'. POOH w/ csg gun. RU & squeeze perfs @ w/ 60 sx Class C w/ 2% CACL. Did not circ thru 5 1/2" cs @ 2722'. Drilled cmt to 2820'. Circ. hole clean. RIH to 3 plated AS-1 pkr w/ 1.5 F nipple, on/off tool, 91 jts. 2 3/8" csg to 580 psi. Held ok. Put well on injection.	arly state all person of the s	ertinent details, and a Completions: Attach at 1/8" DC's & tbg. 3 1/8" DC's & tbg. 4" 9.5# J-55 UFL completions at 1/8" DC's & tbg. 4" 9.5# J-55 UFL complete at 2828'. 6 SMS. Tail w/ 60 and could be a count & float collar collar collar count at 2828'. 6 SMS. Tail w/ 60 and count & float collar col	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. seg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru ar to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 POZ mix w/ .2% FL52A and .2% SMS. Tail & pkr. RIH w/ bit, bit sub & tbg. Tag cmt '. sezed holes @ 2800'). RIH w/ 4" nickel ar @ 2967'. ND BOP. Flange up WH. Tested and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan			
OTHER: 13. Describe proposed or completed operations. (Clean of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2 holes @ 2800'. POOH w/ csg gun. RU & squeeze perfs @ w/ 60 sx Class C w/ 2% CACL. Did not circ thru 5 1/2" cs @ 2722'. Drilled cmt to 2820'. Circ. hole clean. RIH to 3 plated AS-1 pkr w/ 1.5 F nipple, on/off tool, 91 jts. 2 3/8" csg to 580 psi. Held ok. Put well on injection.	arly state all person of the s	ertinent details, and a Completions: Attach at 1/8" DC's & tbg. 3 1/8" DC's & tbg. 4" 9.5# J-55 UFL completions at 1/8" DC's & tbg. 4" 9.5# J-55 UFL complete at 2828'. 6 SMS. Tail w/ 60 and could be a count & float collar collar collar count at 2828'. 6 SMS. Tail w/ 60 and count & float collar col	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. seg (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru ar to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 POZ mix w/ .2% FL52A and .2% SMS. Tail & pkr. RIH w/ bit, bit sub & tbg. Tag cmt '. sezed holes @ 2800'). RIH w/ 4" nickel ar @ 2967'. ND BOP. Flange up WH. Tested and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan			
OTHER: 13. Describe proposed or completed operations. (Clean of starting any proposed work). SEE RULE 1103 or recompletion. 8-27-07 thru 9/11/2007 MIRU Well service. NU BOP. POOH w/ tbg. RIH w/ 3 from 3077' to 3090'. Circ. hole clean. POOH; RIH w/ 4 RIH w/ 4" 9.5# UFJ csg as follows: 2 ½" x 4 ½" taper guid 9.5# J-55 UFJ csg (3013.20'); Landed csg in 4 ½" liner @ Cmt csg as follows: Lead w/ 50 sx 50/50 POZ mix w/ .2% cmt job. Did not circ cmt. Set slips on 4" csg w/ 35000# RIH w/ logging tools. Ran GR/CBL/CCL from 3022' to 2 holes @ 2800'. POOH w/ csg gun. RU & squeeze perfs @ w/ 60 sx Class C w/ 2% CACL. Did not circ thru 5 1/2" cs @ 2722'. Drilled cmt to 2820'. Circ. hole clean. RIH to 3 plated AS-1 pkr w/ 1.5 F nipple, on/off tool, 91 jts. 2 3/8" csg to 580 psi. Held ok. Put well on injection.	arly state all person of the s	ertinent details, and a Completions: Attach at 1/8" DC's & tbg. 3 1/8" DC's & tbg. 4" 9.5# J-55 UFL completions at 1/8" DC's & tbg. 4" 9.5# J-55 UFL complete at 2828'. 6 SMS. Tail w/ 60 and could be a count & float collar collar collar count at 2828'. 6 SMS. Tail w/ 60 and count & float collar col	Tag @ 3031'. Clean out to 3077'. Drilled g. Tag top of liner @ 3022'. POOH. Tag (44.10'); 4" Float collar (1.60'); 68 jts. 4" sx Class C w/ 2% CACL. Had good circ thru at to 3022'. RIH w/ 2 ½" slick gun on wireline, perf 4 POZ mix w/ .2% FL52A and .2% SMS. Tail g. & pkr. RIH w/ bit, bit sub & tbg. Tag cmt "." Tag (2967'. ND BOP. Flange up WH. Tested (20-55) and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan			

INJECTION WELL DATA SHEET

OPERATOR: Cele	ro Energy II, L P						
WELL NAME & NU	JMBER: ROCK QUEEN UNIT #42		, i a				
WELL LOCATION:		Н	26	T-13-S	R-31-E		
	FOOTAGE LOCATION	UNIT LETTER	SECTION	TOWNSHIP	RANGE		
	WELLBORE SCHEMATIC (See Attached)		WELL CONSTR Surface C	RUCTION DATA Casing			
		Hole Size:		Casing Size: 8 5/8"	24#		
		Cemented with: 175	SX	or	ft ³		
		Top of Cement: SURI	FACE	Method Determined	<u>[:</u>		
			Intermediate Casing				
		Hole Size:		Casing Size:			
		Cemented with:	sx.	or	ft ³		
		Top of Cement:		Method Determined	l:		
`		Production Casing					
-		Hole Size: 8 5/8"		Casing Size: 5 1/2"	14#		
		Cemented with: 125 sx	ζ.	_ or	ft ³		
		Top of Cement: 2790'		Method Determined	l:		
		Total Depth: 3090'		_			

Injection Interval 3057-3061'

(Perforated or Open Hole; indicate which)

INJECTION WELL DATA SHEET

Tubi	ng Size:	2 3/8"/ 4.7#/ J-55	Lining Material: IPC		
Type of Packer: AS-1					
Packer Setting Depth: 2967'					
Other Type of Tubing/Casing Seal (if applicable): 4 ½" 9.5# Liner set @ 3067 & 4" 9.5# UFJ Liner from surface to 3022' Cmt w/ 220 sx Class C					
Additional Data					
1.	Is this a	new well drilled for injection?	YesXNo		
	If no, for what purpose was the well originally drilled? Primary depletion oil producer				
	_Drilled in 4/1955 as oil well. Converted to water injection 5/1961.				
2.	Name of the Injection Formation: Queen				
3.	. Name of Field or Pool (if applicable): <u>Caprock</u>				
4.	Has the well ever been perforated in any other zone(s)? List all such perforated intervals and give plugging detail, i.e. sacks of cement or plug(s) used. NO				
5. Give the name and depths of any oil or gas zones underlying or overlying the proposed injection zone in this area: None					

(2) 5/2/61 CONVERTED TO WATER INJECTION. CEMENTED 45.26' OF 41/2" 9.5 LINER @ 3067' W/35 SX + 29. HA-5 RAN 23/8" TOG W/51/2 PKR, SET PKR@ 2988', PERFS 3057-3061'. LAST INJECT.

CELERO ENERGY DATE: Oct. 19, 2007 BY: **JEA** Caprock FIELD: WELL: 42 LEASE/UNIT: **Rock Queen** STATE: **New Mexico COUNTY:** Chaves KB = 4418'Location: 1990' FNL & 660' FEL, Sec 26H, T13S, R31ECM GL = 4,408'SPUD: 4/55 COMP: 4/55 API = 30-005-00871CURRENT STATUS: Active Injector Original Well Name: Levick State #1 t Workover 8-5/8" 24# @ 306' cmt'd. w/ 175 sx 2 3/8" 4.7# J-55 IPC injection tubing and AS-1 packer @ 2967' TOC @ 2790' 4" 9.5# UFJ liner 3022' - surface cmt'd w/ 220 sx in two attempts 5-1/2" 14# @ 3060' cmt'd. w/ 125 sx (DNC) Top of Queen @ 3060': Queen perfs: 3057' - 3061' (05-61) 4-1/2" 9.5# liner 3022' - 3067' cmt'd w/ 35 sx PBTD - 3088' TD - 3090'



