

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-11408
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-11302
7. Lease Name or Unit Agreement Name New Mexico BM State
8. Well Number 003
9. OGRID Number 004378
10. Pool name or Wildcat (North) Justis Blinbry

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,126' DF

Pit or Below-grade Tank Application ☐ or Closure ☒

Pit type steel Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: steel mil Below-Grade Tank: Volume 180 bbls; Construction Material steel

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Nadel and Gussman Permian, L.L.C.

3. Address of Operator
601 North Marienfeld, Suite 508, Midland, Texas 79701

4. Well Location
Unit Letter P : 915 feet from the South line and 330 feet from the East line
Section 2 Township 25-S Range 37-E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,126' DF

Pit or Below-grade Tank Application ☐ or Closure ☒

Pit type steel Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: steel mil Below-Grade Tank: Volume 180 bbls; Construction Material steel

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SEE ATTACHED PLUGGED WELLBORE DIAGRAM

10/18 - 10/19/07 MIRU Triple N rig #24, set pit. Rods parted. NU BOP, fished tubing & rods out of east-side. SD for weekend.

10/22/07 Contacted NMOCD, Buddy Hill. Displaced 2 7/8" w/ brine & pumped 100 sx C cmt, some returns up 4 1/2" casing. SI casings & WOC. Tagged cmt @ 3,006' in 2 7/8" (west-side), tagged cmt @ 4,830' in 4 1/2" (east-side). RIH w/ tubing in east-side to 4,800', circulated hole w/ mud. PUH and pumped 25 sx C cmt @ 3,550'. PUH, SDFN.

10/23/07 NMOCD, Buddy Hill on location. Tagged cmt @ 3,096' on east-side. Cut & pulled 4 1/2" casing (east-side) from 2,211'. Cut & pulled 2 7/8" casing (west-side) from 2,190'. ND wellhead, SDFN.

10/24/07 NU BOP. RIH w/ tubing to 2,278'. Pumped 75 sx C cmt w/ CaCl₂ @ 2,278'. WOC and tagged cmt @ 2,048'. Perforated casing @ 1,000'. RIH w/ packer and squeezed 80 sx C cmt w/ CaCl₂ @ 1,000'. SDFN.

10/25/07 Pressure-tested sqz to 700 psi, held. Tagged cmt @ 890'. NMOCD Buddy Hill ok'd tag. Perforated csg @ 269'. RIH w/ packer and sqz'd 125 sx C cmt @ 269'. WOC, tagged cmt @ 160'. RIH w/ tbq, circulated 30 sx C cmt 60' to surface, POOH. RDMO.

Cut off wellhead & anchors, installed dry hole marker.

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE [Signature] TITLE engineer, Triple N Services, Inc. DATE 10/28/07

Type or print name: James F. Newman, P.E.

E-mail address: jim@triplenservices.com Telephone No. 432-687-1994

For State Use Only

APPROVED BY: [Signature]

OC FIELD REPRESENTATIVE U/STAFF MANAGER
TITLE _____ DATE _____

NOV 01 2007

Conditions of Approval (if any):

Nadel and Gussman Permian PLUGGED WELLBORE SKETCH

Date October 28, 2007

RKB @
DF @ 3,126
GL @

Lease & Well No
Legal Description

New Mexico Bm State #3

1,980' FSL & 660' FEL, Sec 26, T20S, R23E

County
Field
Date Spudded
API Number
Status

Eddy State New Mexico
Wildcat B Morrow Rig Released
30-015-34739
PLUGGED 10/25/07

12-1/2" Hole

30 sx C cmt 60' to surface

13-3/8" 48# @ 219' cmt'd w/ 250 sx, circ
Perf/sqz'd 125 sx C cmt 269 -160' TAGGED

Perf/sqz'd 80 sx C cmt 1,000 - 890' TAGGED
Top of Salt @ 1000

2-7/8" (West String)

9-5/8" TOC @ 2,000' by TS
Base of Salt @ 2,200

75 sx C cmt 2,278 - 2,048' TAGGED
Cut/pulled 2 1/4" csg from 2,190'

2-7/8" TOC @ 2,800' by TS

sqz'd 100 sx C cmt, TAGGED @ 3,006'

9-5/8" 32.3# H-40 @ 3,455' cmt'd w/ 500 sx

8-7/8 hole

Upper Blinberry perms 4976-5122'
communicated to 4-1/2" casing

2-7/8" CIBP @ 5,130'
Blinberry Perfs 5,198-5,379'

2-7/8" CIBP @ 7,000'

2-7/8" 6.4# J55 @ 7,353' cmt'd w/ 1400 sx

4-1/2" (East String)

Cut/pull 4 1/2" csg fl 2,211'

25 sx C cmt 3,505 - 3,096' TAGGED

TAGGED 2-7/8" SQZ @ 4,830'

4-1/2" CIBP @ 5,180'

4-1/2" CIBP @ 7,000'

4-1/2" CIBP @ 7,300'
Montoya Perfs 7,315 - 7,580'

4-1/2" CIBP @ 7,900', 18' cmt
McKee Perfs 8,083 - 8,187'

4-1/2" 11.6# J55 @ 8,278'

PBTD 8460'
TD 8870'



PLUGS SET 10/18/07 thru 10/25/07

WEST STRING (2-7/8")

1) sqz'd 100 sx C cmt, TAGGED @ 3,006'

EAST STRING (4-1/2")

- 2) TAGGED cmt fl 2-7/8" @ 4,830', circulated mud
- 3) 25 sx C cmt 3,505 -3,096' TAGGED
- 4) Cut and pull 2-7/8" csg from 2,190'
- 5) Cut and pull 4-1/2" csg from 2,211'

9-5/8" CASING

- 6) 75 sx C cmt 2,278 - 2,048' TAGGED
- 7) Perf/sqz 80 sx C cmt 1,000 - 890' TAGGED
- 8) Perf/sqz 125 sx C cmt 269 -160' TAGGED
- 9) 30 sx C cmt 60' to surface

Capacities

2-7/8" 6 5# csg	30 77 ft/ft3	0 0325 ft3/ft
4-1/2" 11 6# csg	11 468 ft/ft3	0 0872 ft3/ft
9-5/8" 32 3# csg	2 304 ft/ft3	0 434 ft3/ft
8-3/4" openhole	2 3947 ft/ft3	0 4176 ft3/ft
12-1/2" openhole	1 3864 ft/ft3	0 7213 ft3/ft