Office	State of New Mexico	Form C-103
District I	Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
<u>District II</u> 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-025-38299
District III	1220 South St. Francis Dr.	5. Indicate Type of Lease STATE  FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	,	o. State on te das Bease No.
87505	TICES AND REPORTS ON WELLS	7 Loggo Name of Huit Agreement Name
	POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APP	LICATION FOR PERMIT" (FORM C-101) FOR SUCH	Pyramid
PROPOSALS.)  1. Type of Well: Oil Well	Gas Well  Other	8. Well Number
1. Type of Well. Off Well	Gas wen Other	001
2. Name of Operator		9. OGRID Number
Cimarex Energy Co.		215099
3. Address of Operator	14 0007	10. Pool name or Wildcat
PO Box 140907; Irving, TX 750	14-0907	Denton Wolfcamp East
4. Well Location		
	2210 feet from the South line and 43	
Section 31	Township 14S Range 3E NMPI	
	11. Elevation (Show whether DR, RKB, RT, GR, etc.	
Pit or Below-grade Tank Application	3791' GR	
	Distance from nearest fresh water well	Distance from magnest application
Pit Liner Thickness:Below-Grade Tank: Volumebbls; Construction Material  12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:  13. Describe proposed or constarting any proposed wo recompletion.  06-30-07 Spudded 17-1/ (wt 12.5, yld 1) CaCl, circ. 66 07-01-07 Pressure tested	INTENTION TO:  PLUG AND ABANDON CHANGE PLANS	ILLING OPNS PAND A DATE OF THE P
07-13-07 Cement kick o 07-28-07 in 12-1/4" hole 2.45) + 0.125 I	bit became stuck @ 1853'  ff plug w/600sx Premium Plus (wt 16.5#,) + 0.75% e ran 4748' 8-5/8" 32# J-55 LTC. Cemented with le Poly-E-Flake and tail with 250 sx Premium Plus C ( sx to surface. WOC 26 hours. Pressure test 8-5/8"	ad of 1450 sx interfill C (wt 11.9 #, yield wt 14.8 #, yield 1.33) + 1% CaCl2.
07-13-07 Cement kick o 07-28-07 in 12-1/4" hole 2.45) + 0.125 I Circulated 305	ff plug w/600sx Premium Plus (wt 16.5#,) + 0.75% e ran 4748' 8-5/8" 32# J-55 LTC. Cemented with le Poly-E-Flake and tail with 250 sx Premium Plus C (a sx to surface. WOC 26 hours. Pressure test 8-5/8" on above is true and complete to the best of my knowledged according to NMOCD guidelines , a general permit or an TITLE Reg Analyst	ad of 1450 sx interfill C (wt 11.9 #, yield wt 14.8 #, yield 1.33) + 1% CaCl2. casing to 2000 psi for 30 minutes.  ge and belief. I further certify that any pit or below-grade (attached) alternative OCD-approved plan   DATE November 20, 2007  Telephone No. 469-420-2715