District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Santa Fe, NM 87505 Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes ☐ No ☒ Type of action: Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒		
Operator: Pride Energy Company Telephone: Address: P O Box 701950 Tulsa, OK 74170-1950	918-524-9200 e-mail address: larrym@	@pride-energy.com
Facility or well name: <u>State X #1 </u>		
County: <u>Lea</u> Latitude <u>33-17-28.2</u> Longitude <u>103-27-43.2</u> NAD: 1927 1983		
Surface Owner: Federal State Private Indian I		
Pit	Below-grade tank	(8)
Type: Drilling ⊠ Production ☐ Disposal ☐	Double-walled, with leak detection? Yes If not, explain who not. 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1983 1927 1	
Workover	Construction material:	
Lined 🛛 Unlined 🔲	Double-walled, with leak detection? Yes I If not, explain why got.	
Liner type: Synthetic ☑ Thickness 12 mil Clay ☐	Company of the second of the s	
Pit Volumebbl		Les Andrews
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points) XXX 6582129791
•	50 feet or more, but less than 100 feet	(10 points)
high water elevation of ground water.) GW = 40 °	100 feet or more	(0 points)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(0 points) XXX
water sources, or less than 1000 feet from an other water sources.)	T	(20 points)
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet	1 ` • ′
	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(0 points) XXX
	Ranking Score (Total Points)	20 points
	Tananag Section (Total Totals)	F
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's		<u> </u>
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's your are burying in place) onsite ⊠ offsite □ If offsite, name of facility	relationship to other equipment and tanks. (2) Indicate	te disposal location: (check the onsite box if
your are burying in place) onsite 🛛 offsite 🔲 If offsite, name of facility	relationship to other equipment and tanks. (2) Indicate	te disposal location: (check the onsite box if
	relationship to other equipment and tanks. (2) Indicates the control of the contr	te disposal location: (check the onsite box if
your are burying in place) onsite offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No Y (5) Attach soil sample results and a diagram of sample locations and excavations.	relationship to other equipment and tanks. (2) Indicates (2) Indicates (3) Attach a general decrease (3) If yes, show depth below ground surface (3) ions.	te disposal location: (check the onsite box if escription of remedial action taken includingft. and attach sample results.
your are burying in place) onsite offsite foffsite, name of facility remediation start date and end date. (4) Groundwater encountered: No Y (5) Attach soil sample results and a diagram of sample locations and excavation Additional Comments: All excess drilling fluid will be removed. A burial	relationship to other equipment and tanks. (2) Indicates a general decrease. (3) Attach a general decrease If yes, show depth below ground surface ions.	te disposal location: (check the onsite box if escription of remedial action taken including ft. and attach sample results.
your are burying in place) onsite offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No Y (5) Attach soil sample results and a diagram of sample locations and excavations.	relationship to other equipment and tanks. (2) Indicates a general decrease. (3) Attach a general decrease If yes, show depth below ground surface ions. pit will be excavated and lined with a 20 mil liner. The lidify the mud then placed in the burial pit. After all n	te disposal location: (check the onsite box if escription of remedial action taken including ft. and attach sample results. The drilling mud will be mixed with Elke mud is removed the pit bottoms will be sampled
your are burying in place) onsite offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No Y (5) Attach soil sample results and a diagram of sample locations and excavational Comments: All excess drilling fluid will be removed. A burial Environmental Solidification Product at a 20(mud) to 1(product) ratio to so	relationship to other equipment and tanks. (2) Indicates a general decrease. (3) Attach a general decrease If yes, show depth below ground surface ions. pit will be excavated and lined with a 20 mil liner. The lidify the mud then placed in the burial pit. After all n	te disposal location: (check the onsite box if escription of remedial action taken including ft. and attach sample results. The drilling mud will be mixed with Elke mud is removed the pit bottoms will be sampled
your are burying in place) onsite offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No Y (5) Attach soil sample results and a diagram of sample locations and excavati Additional Comments: All excess drilling fluid will be removed. A burial Environmental Solidification Product at a 20(mud) to 1(product) ratio to so Per NMOCD guidelines. The drilling pit will be backfilled with clean nativ	relationship to other equipment and tanks. (2) Indicates a general decrease. (3) Attach a general decrease If yes, show depth below ground surface ions. pit will be excavated and lined with a 20 mil liner. The lidify the mud then placed in the burial pit. After all n	te disposal location: (check the onsite box if escription of remedial action taken including ft. and attach sample results. The drilling mud will be mixed with Elke mud is removed the pit bottoms will be sampled
your are burying in place) onsite offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No Y (5) Attach soil sample results and a diagram of sample locations and excavati Additional Comments: All excess drilling fluid will be removed. A burial Environmental Solidification Product at a 20(mud) to 1(product) ratio to so Per NMOCD guidelines. The drilling pit will be backfilled with clean nativ	relationship to other equipment and tanks. (2) Indicates a general decrease. (3) Attach a general decrease in the second surface in the second surface in the second surface in the burial pit. After all new soil and contoured to the surrounding area. A final	te disposal location: (check the onsite box if escription of remedial action taken including ft. and attach sample results. The drilling mud will be mixed with Elke mud is removed the pit bottoms will be sampled
your are burying in place) onsite offsite forfsite, name of facility remediation start date and end date. (4) Groundwater encountered: No Y (5) Attach soil sample results and a diagram of sample locations and excavational Comments: All excess drilling fluid will be removed. A burial Environmental Solidification Product at a 20(mud) to 1(product) ratio to so Per NMOCD guidelines. The drilling pit will be backfilled with clean native The job. NMOCD Hobbs will be given 48 hrs notice before start of job and 48 hrs not I hereby certify that the information above is true and complete to the best of	relationship to other equipment and tanks. (2) Indicates a general decrease. (3) Attach a general decrease of the second surface of	te disposal location: (check the onsite box if escription of remedial action taken includingft. and attach sample results. the drilling mud will be mixed with Elkeft. and is removed the pit bottoms will be sampledft. and is removed the pit bottoms will be sampledft.
your are burying in place) onsite offsite foffsite, name of facility remediation start date and end date. (4) Groundwater encountered: No Y (5) Attach soil sample results and a diagram of sample locations and excavati Additional Comments: All excess drilling fluid will be removed. A burial Environmental Solidification Product at a 20(mud) to 1(product) ratio to so Per NMOCD guidelines. The drilling pit will be backfilled with clean native The job.	relationship to other equipment and tanks. (2) Indicates a general decrease. (3) Attach a general decrease of the second surface of	te disposal location: (check the onsite box if escription of remedial action taken includingft. and attach sample results. the drilling mud will be mixed with Elkeft. and is removed the pit bottoms will be sampledft. and is removed the pit bottoms will be sampledft.
your are burying in place) onsite offsite forfsite, name of facility remediation start date and end date. (4) Groundwater encountered: No Y (5) Attach soil sample results and a diagram of sample locations and excavational Comments: All excess drilling fluid will be removed. A burial Environmental Solidification Product at a 20(mud) to 1(product) ratio to so Per NMOCD guidelines. The drilling pit will be backfilled with clean native The job. NMOCD Hobbs will be given 48 hrs notice before start of job and 48 hrs not I hereby certify that the information above is true and complete to the best of	relationship to other equipment and tanks. (2) Indicates a general decrease. (3) Attach a general decrease of the second surface of	te disposal location: (check the onsite box if escription of remedial action taken includingft. and attach sample results. the drilling mud will be mixed with Elkeft. and is removed the pit bottoms will be sampledft. and is removed the pit bottoms will be sampledft.
your are burying in place) onsite offsite foffsite, name of facility remediation start date and end date. (4) Groundwater encountered: No Y (5) Attach soil sample results and a diagram of sample locations and excavation Additional Comments: All excess drilling fluid will be removed. A burial Environmental Solidification Product at a 20(mud) to 1(product) ratio to so Per NMOCD guidelines. The drilling pit will be backfilled with clean native The job. NMOCD Hobbs will be given 48 hrs notice before start of job and 48 hrs not I hereby certify that the information above is true and complete to the best of has been/will be constructed or closed according to NMOCD guidelines.	relationship to other equipment and tanks. (2) Indicates a general decrease. (3) Attach a general decrease of the second surface of	te disposal location: (check the onsite box if escription of remedial action taken includingft. and attach sample results. the drilling mud will be mixed with Elkeft. and is removed the pit bottoms will be sampledft. and is removed the pit bottoms will be sampledft.
your are burying in place) onsite offsite for offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No yes (5) Attach soil sample results and a diagram of sample locations and excavational Comments: All excess drilling fluid will be removed. A burial Environmental Solidification Product at a 20(mud) to 1(product) ratio to so Per NMOCD guidelines. The drilling pit will be backfilled with clean native The job. NMOCD Hobbs will be given 48 hrs notice before start of job and 48 hrs not have certify that the information above is true and complete to the best of has been/will be constructed or closed according to NMOCD guidelines.	relationship to other equipment and tanks. (2) Indicates a general decrease. (3) Attach a general decrease of the second surface of	te disposal location: (check the onsite box if escription of remedial action taken including ft. and attach sample results. The drilling mud will be mixed with Elke find is removed the pit bottoms will be sampled report will be submitted after completion of the above-described pit or below-grade tank ive OCD-approved plan .
your are burying in place) onsite offsite for offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No yes (5) Attach soil sample results and a diagram of sample locations and excavation Additional Comments: All excess drilling fluid will be removed. A burial Environmental Solidification Product at a 20(mud) to 1(product) ratio to so Per NMOCD guidelines. The drilling pit will be backfilled with clean native The job. NMOCD Hobbs will be given 48 hrs notice before start of job and 48 hrs not have certify that the information above is true and complete to the best of has been/will be constructed or closed according to NMOCD guidelines. Date: 12-10-07 Printed Name/Title Logan Anderson - Agent Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the regulations.	relationship to other equipment and tanks. (2) Indicates a general decay and surface ions. pit will be excavated and lined with a 20 mil liner. The lidity the mud then placed in the burial pit. After all now soil and contoured to the surrounding area. A final cotice before testing. of my knowledge and belief. I further certify that the sign, a general permit , or an (attached) alternation of the contents of t	te disposal location: (check the onsite box if escription of remedial action taken including ft. and attach sample results. The drilling mud will be mixed with Elke find is removed the pit bottoms will be sampled report will be submitted after completion of the above-described pit or below-grade tank ive OCD-approved plan .
your are burying in place) onsite offsite for offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No yes (5) Attach soil sample results and a diagram of sample locations and excavation Additional Comments: All excess drilling fluid will be removed. A burial Environmental Solidification Product at a 20(mud) to 1(product) ratio to so Per NMOCD guidelines. The drilling pit will be backfilled with clean native The job. NMOCD Hobbs will be given 48 hrs notice before start of job and 48 hrs not have certify that the information above is true and complete to the best of has been/will be constructed or closed according to NMOCD guidelines. Date: 12-10-07 Printed Name/Title Logan Anderson - Agent Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve the	relationship to other equipment and tanks. (2) Indicates a general decrease. (3) Attach a general decrease of the second surface of	te disposal location: (check the onsite box if escription of remedial action taken including ft. and attach sample results. The drilling mud will be mixed with Elke find is removed the pit bottoms will be sampled report will be submitted after completion of the above-described pit or below-grade tank ive OCD-approved plan .