

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-105 Revised June 10, 2003
		WELL API NO. 30-025-38371
		5. Indicate Type of Lease STATE ☐ FEE ☒
		State Oil & Gas Lease No. N/A
WELL COMPLETION OR RECOMPLETION REPORT AND LOG		
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐		7. Lease Name or Unit Agreement Name EW Walden
b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER ☐		
2. Name of Operator Apache Corporation		8. Well No. #009
3. Address of Operator 6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224		9. Pool name or Wildcat Blinebry O&G, Tubb O&G, Drinkard
4. Well Location Unit Letter <u>K</u> <u>1650</u> Feet From The <u>South</u> Line and <u>2310</u> Feet From The <u>West</u> Line Section <u>15</u> Township <u>22S</u> Range <u>37E</u> NMPM <u>Lea</u> County		
10. Date Spudded 08/05/2007	11. Date T.D. Reached 08/15/2007	12. Date Compl. (Ready to Prod.) 10/19/2007
13. Elevations (DF& RKB, RT, GR, etc.) 3386'		14. Elev. Casinghead
15. Total Depth 6750'	16. Plug Back T.D. 6705'	17. If Multiple Compl. How Many Zones? 3
18. Intervals Drilled By X		Rotary Tools Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name 5464-5700' (Blinebry O&G) / 5850-6108' (Tubb O&G) / 6410-6523' (Drinkard)		20. Was Directional Survey Made No
21. Type Electric and Other Logs Run SD/DSN, DLL-MG, ISAT		22. Was Well Cored No
23. CASING RECORD (Report all strings set in well)		
CASING SIZE	WEIGHT LB./FT.	DEPTH SET
8-5/8"	24#	1176'
5-1/2"	17#	6750'
24. LINER RECORD		25. TUBING RECORD
SIZE	TOP	SIZE
		2-7/8"
BOTTOM	SACKS CEMENT	DEPTH SET
		6632'
26. Perforation record (interval, size, and number) Blinebry: 5464-5700' (2 JSPF, 52 holes) Tubb: 5850-6108' (2 JSPF, 65 holes) Drinkard: 6410-6523' (2 JSPF, 52 holes)		27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.
		DEPTH INTERVAL
		AMOUNT AND KIND MATERIAL USED
		5464-5700 3Kgal 15%HCl, 36Kgal SS-25 + 82K# 20/40
		5850-6108 3Kgal 15%HCl, 36Kgal SS-25 + 82K# 20/40
		6410-6523 3Kgal 15%HCl, 39Kgal SS-35 + 62K# 20/40
28. PRODUCTION		
Date First Production 10/19/2007		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping - Rod Pump
		Well Status (Prod. or Shut-in) Producing
Date of Test 10/21/2007	Hours Tested 24 hours	Choke Size
		Prod'n For Test Period
		Oil - Bbl 50
		Gas - MCF 280
		Water - Bbl. 48
		Gas - Oil Ratio 5600
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate
		Oil - Bbl.
		Gas - MCF
		Water - Bbl.
		Oil Gravity - API - (Corr.) 37.3
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold		Test Witnessed By Apache Corporation
30. List Attachments C-102's, C-103's, C-104's		
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief		
Signature <u>Sophie Mackay</u>		Printed Name Sophie Mackay
E-mail Address <u>sophie.mackay@apachecorp.com</u>		Title Engineering Tech
		Date 10/25/2007

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2568'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2789'	T. Devonian	T. Menefee	T. Madison
T. Queen 3316'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3590'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3857'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5054'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry 5459'	T. Gr. Wash	T. Morrison	T.
T. Tubb 5969'	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6298'	T. Bone Springs	T. Entrada	T.
T. Abo 6526'	T. Rustler 1117'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology