| <u>District I</u> | | |

 | C+- | to of N | lew Mex | 100 | | Form C-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
|---|---|--
--
--
--|--|---|---|--|---|--|---|---|--|---|---|--|---|--|---|--|---|--|--|---
---|--|---|---|--------|--|--|---|--|---|--|--|--|--|--------|--|---|---|--|---|---|--|--|---|--------|--|---|--|---|---|---|--|--|--|--------|--|---|--|---|---|--|---|--|--|--------|--|--
---|--|--|---|---|--|---|--------|--|---|---|--|---|---
---|---|---|--------|--|---|---|---|---|---|---|---|---|--------|--|
| | rench Dr., Hobbs
5)393-6161 Fax: | • |

 | | | · · | | MOOD | Pennit 678 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | ., | | E

 | nergy, Min | | | | irces | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | |

 | | | ation Di | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | |

 | 122 | 0 S. St | Francis | Dr. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | |

 | Sa | nta Fe, | NM 875 | 505 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| AF | PLICATIO | ON FOR | PERMIT

 | TO DRILL, R | E-ENTER | R, DEEPEN | , PLUGBA | CK, OR AI | DD A ZONE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | |

 | ie and Address | | | | 2. OGRID N | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | MA | RBOB EN:
PO Bo

 | ERGY CORP | | | | 14049 |) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | | Artesia , N

 | | | | | | nper | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | | · · · · ·

 | | | | | 30-05-2 | 3 018 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | 4. Property Cod | e |

 | | roperty Nam | | | б. | Well No. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | 36941 | |

 | MAKETRA | ACKS STA | TE COM | | | 001 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | |

 | 7. Sur | face Loca | ation | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| UL - Lot | : Section | Township | o Range

 | e Lot.Idn I | Feet From | N/S Line | Feet From | E/W Line | County | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| D | 35 | 15S | 31E

 | D | 660 | N | 330 | W | CHAVES | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | |

 | 8. Poo | l Inform | ation | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| MLDCA | T WOLFCAI | MP |

 | | , | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | |

 | Additional | <u>Well</u> Inf | ormation | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| 9. Wo | udk Type | 10. Wel | 1 Туре

 | 11. Cable | Rotary | | 12. Lease Type | 13. Grou | nd Level Elevation | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| New | Well | OI | L

 | | | | State | 4372 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| 14. | Multiple | 15. Prope | sed Depth

 | 16. Fe | rmation | | 17. Contractor |] | 18. Spud Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | N | |

 | Wol | fcamp | np 2/16/2008 | | | 2/16/2008 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Dej | pth to Ground w | rater |

 | Distance from | nearest fresh | water well | | Distance to : | nearest surface water | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | 250 | |

 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | |

 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | "Synthetic | <u> </u> | mils thick

 | Clay Pit Vohr | ne. | bbls Drilling
Fresh V | | Diesel/Oil-base | d Gas/Air | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | | × |

 | - | | Fresh V | 7ster Brine | Diesel/Oil-base | d Gw/Air | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close | " Synthetic
ed Loop System | | 19.

 | Proposed Casi | ng and C | Fresh V
Cement Pro | Jater Brine Brine | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| | "Synthetic | X
Casing
13.3 | 19.
Гуре

 | - | ng and C | Fresh V | 7ster Brine | Zement | a Gas/Air C
Estimated TOC
0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type | Synthetic Synthetic Additional Synthetic Regional System | Casing | 19.
Гуре
75

 | Proposed Casi
Casing Weight/ft | ng and C | Fresh V
Cement Pro
ing Depth | 7ster Erine Erine Sacks of C | Cement | Estimated TOC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type
Surf | ∴ Synthetic Г
ed Loop System
Hole Size
175 | Casing
13.3 | 19.
Type
75

 | Proposed Casi
Casing Weight/ft
48 | ng and C | Fresh V
Cement Pro
ing Depth
400 | 7ster Brine Brine Sacks of C | Cement | Estimated TOC
0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type
Surf
Int1 | Hole Size | Casing
13.3
9.62 | 19.
Гуре
75

 | Proposed Casi
Casing Weight/ft
48
40 | ng and C | Fresh V
Cement Pro
ing Depth
400
4000 | Zeter Brine Spring Sacks of C
400
1000 | Cement | Estimated TOC
0
0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Closs
Type
Surf
Int1
Prod | Hole Size
17.5
12.25
7.875 | Casing
13.3
9.62
5.5 | 19.
Гуре 75 85 6 6 6 6 6 7 7 7 7 7 7 7 7 7 7 7 7 7 7

 | Proposed Casi
Casing Weight/ft
48
40
17 | ng and C
Sett | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500 | Jater Brine Degram Sacks of C
400
1100
1100
0 | Cement | Estimated TOC
0
0
8500 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Closs
Type
Surf
Int1
Prod
Int2 | Hole Size
17 5
12.25
7.875
8.75
20se to drill 17 | Casing
13.3
9.62
5.5
5.5 | 19. 7
Type
75
15
5
Casing
18 to 400 ft

 | Proposed Casi
Casing Weight/ft
48
40
17
17
7
/Cement Prog
with fresh water, | ng and C
Sett | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i | Jater Brine D
gram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Type
Surf
Int1
Prod
Int2
We propo | Hole Size
17 5
12.25
7.875
8.75
20se to drill 17
rl 12 1/4 inch | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400 | 19.
Type
75
15
5
5
5
6
6
6
75
15
15
15
15
15
15
15
15
15
1

 | Proposed Casi
Casing Weight/ft
48
40
17
17
/Cement Prog
with fresh water,
ut brine water, rur | ng and C
Sett
ram: Ad
run 48 b I
40 b J-55 | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs | Jater Brine D
gram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d | Hole Size
17 5
12.25
7.875
8.75
bise to drill 17
rl 12 1/4 inch m | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500 | 19.1 Type 75 15 5 6 0 0 ft with cut

 | Proposed Casi
Casing Weight/ft
48
40
17
17
7
/Cement Prog
with fresh water, | ng and C
Sett
Fam: Ad
run 48 b H
40 b J-55
5 1/2 inch 1 | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 cs | Jater Brine
ogram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d | Hole Size
17 5
12.25
7.875
8.75
bise to drill 17
rl 12 1/4 inch m | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500 | 19.1 Type 75 15 15 16 17 18 19.1 19.1 19.1 19.1 19.1 10 11.1 <tr <="" td=""><td>Proposed Casi
Casing Weight/ft
48
40
17
17
(Cement Prog
with fresh water,
ut brine water, run
t brine water, run</td><td>ng and C
Sett
Fam: Ad
run 48 lb H
40 lb J-55
5 1/2 inch 1
I set at 134</td><td>Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 5/8 inch cs
17 lb P-110 cs
150 ft with 11</td><td>Jater Brine
ogram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0</td><td>Cement</td><td>Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to</td></tr> <tr><td>Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d</td><td>Hole Size
17 5
12.25
7.875
8.75
bise to drill 17
rl 12 1/4 inch m</td><td>Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500</td><td>19.7
Type
75
15
5
5
5
6
7
7
7
7
7
7
7
7
7
7
7
7
7</td><td>Proposed Casi
Casing Weight/ft
48
40
17
17
Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 Ib P110 csg and</td><td>ng and C
Sett
Fam: Ad
run 48 lb H
40 lb J-55
5 1/2 inch 1
I set at 134</td><td>Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 5/8 inch cs
17 lb P-110 cs
150 ft with 11</td><td>Veter Brine
Degram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0</td><td>Cement
D
D
t at 400 ft wit
100 ft with 10
500 ft. Drl 7 7
iC 8500'.</td><td>Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to</td></tr> <tr><td>Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft</td><td>Hole Size
17 5
12.25
7.875
8.75
2.55
12.25
7.875
8.75
12.1/4 inch
rl 12 1/4 inch h
with cut brine</td><td>Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500</td><td>19.7
Type
75
15
5
5
5
6
7
7
7
7
7
7
7
7
7
7
7
7
7</td><td>Proposed Casi
Casing Weight/ft
48
40
17
17
(Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 lb P110 csg and</td><td>ng and C
Sett
Fam: Ad
run 48 lb H
40 lb J-55
5 1/2 inch 1
I set at 134</td><td>Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog</td><td>Veter Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0</td><td>Cement</td><td>Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to</td></tr> <tr><td>Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
D</td><td>Hole Size
17 5
12.25
7.875
8.75
Dose to drill 17
rl 12 1/4 inch n
with cut brine
Type
oubleRam</td><td>Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run</td><td>19.7 Type 75 15 15 15 15 15 15 16 10 ft with cu 5 1/2 inch 17 17 17 18 19 19 19 10 ft Work 19 10 ft Work 10 10 ft</td><td>Proposed Casi
Casing Weight/ft
48
40
17
17
/Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 Ib P110 csg and
roposed Blowo
sing Pressure
3000</td><td>ram: Ad
run 48 lb I
140 lb J-55
5 1/2 inch 1
1 set at 134
ut Preven</td><td>Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300</td><td>Veter Brine
Digram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0</td><td>Cement</td><td>Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron</td></tr> <tr><td>Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
D
D</td><td>Hole Size
17 5
12.25
7.875
8.75
Dose to drill 17
rl 12 1/4 inch n
with cut brine
Type
oubleRam</td><td>Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run</td><td>19.7 Type 75 15 15 15 15 15 15 16 10 ft with cu 5 1/2 inch 17 17 17 18 19 19 19 10 ft Work 19 10 ft Work 10 10 ft</td><td>Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7</td><td>ram: Ad
run 48 lb I
140 lb J-55
5 1/2 inch 1
1 set at 134
ut Preven</td><td>Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300</td><td>Veter Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0</td><td>Cement</td><td>Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron</td></tr> <tr><td>Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
3450 ft
D
Chereby cer
of my know
(further of</td><td>Synthetic
ed Loop System
Hole Size
17 5
12.25
7.875
8.75
bose to drill 17
rl 12 1/4 inch n
rl 12 1/4 inch h
with cut brine
Type
oubleRam
tify that the infor
vledge and belief.
erify fhat the de</td><td>Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
billing pit v</td><td>19.1
Type
75
15
5
5
6
75
75
75
75
75
75
75
75
75
75</td><td>Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7</td><td>ng and O
Sett
Sett
ram: Ad
run 48 lb I
40 lb J-55
5 1/2 inch 1
lset at 134
ut Preven</td><td>Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300</td><td>Veter Brine
Digram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0</td><td>Cement</td><td>Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron</td></tr> <tr><td>Closs
Type
Surf
Inti
Prod
Int2
We propo
unface; d
curface; d
3450 ft
D
hereby cer
frmy know
further c
WMOCD g</td><td>Synthetic
ed Loop System
Hole Size
17 5
12.25
7.875
8.75
bose to drill 17
rl 12 1/4 inch n
rl 12 1/4 inch h
with cut brine
Type
oubleRam
tify that the infor
vledge and belief.
erify fhat the de</td><td>Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
billing pit v</td><td>19.1
Type
75
15
5
5
6
75
75
75
75
75
75
75
75
75
75</td><td>Proposed Casi
Casing Weight/ft
48
40
17
17
(Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 lb P110 csg and
roposed Blowo
sing Pressure
3000
e and complete to the</td><td>ng and O
Sett
Sett
ram: Ad
run 48 lb H
A0 lb J-55
5 1/2 inch 1
I set at 134
ut Preves</td><td>Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300</td><td>Veter Brine
Digram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0</td><td>Cement</td><td>Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron</td></tr> <tr><td>Closs
Type
Surf
Int1
Prod
Int2
We propo
wrface; d
wrface; d
ad50 ft
D
hereby cer
f my know
furfher c
WMOCD a
D CD-appr
Printed 1</td><td>Hole Size
17 5
12.25
7.875
8.75
2.75
2.75
3.75
2.75
3.75
2.75
3.75
3.75
2.75
2.75
3.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75</td><td>Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
mation gives
mation gives
mation gives
mation gives</td><td>19.75
Type
75
19.5
19.5
19.5
19.5
19.5
19.5
19.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
1</td><td>Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7</td><td>ng and C
Sett
Sett
ram: Ad
run 48 lb I
1 40 lb J-55
5 1/2 inch 1
l set at 134
ut Preven
best
best
re
Appr
Title:</td><td>Fresh V
Cement Pro-
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pn
300
OIL CO
oved By: Pa
Geologist</td><td>Vater Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0</td><td>Cement</td><td>Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron
7/SION</td></tr> <tr><td>Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
(3450 ft)
D
(hereby cer
of my know
(hereby cer
of my know)
(hereby cer
of my know)
(hereby cer
of my know)</td><td>Hole Size
17 5
12.25
7.875
8.75
2.55
2.55
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75</td><td>Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
billing pit v
general per
nically fileo
yst</td><td>19.7 Type 75 75 75 75 75 75 75 75 75 75 75 75 75</td><td>Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7</td><td>ng and C
Sett
Sett
ram: Ad
run 48 lb I
1 40 lb J-55
5 1/2 inch 1
l set at 134
ut Preven
best
best
re
Appr
Title:</td><td>Fresh V
Cement Pro-
ing Depth
4000
13450
8500
ditional Co
H-40 13 3/8 if
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro-
300
OIL CO
oved By: Pa</td><td>Vater Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0</td><td>Cement</td><td>Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron</td></tr> <tr><td>Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
3450 ft
D
(hereby cer
of my know
Chereby cer
of my know</td><td>Synthetic
ed Loop System
Hole Size
17 5
12.25
7.875
8.75
bese to drill 17
rl 12 1/4 inch h
with cut brine
Type
tify that the infor
veldge and belief
erify fhat the d
rudelinesa
oved plan []
Vame: Electror
oduction Anal
Idress. produc</td><td>Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation give
mation give
paral per
nically fileo
yst
tion@mar</td><td>19.7 Type 75 75 75 75 75 75 75 75 75 75 75 75 75</td><td>Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7</td><td>ng and C
Sett
Sett
ram: Ad
run 48 lb H
run 48 lb H
run 48 lb H
set at 134
ut Preven
best
best
re
Appr
Title:
Appr</td><td>Fresh V
Cement Pro-
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro-
300
OIL CO
oved By: Pa
Geologist
oved Date: 1.</td><td>Vater Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0</td><td>Zement </td><td>Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron
/ISION</td></tr> | Proposed Casi
Casing Weight/ft
48
40
17
17
(Cement Prog
with fresh water,
ut brine water, run
t brine water, run | ng and C
Sett
Fam: Ad
run 48 lb H
40 lb J-55
5 1/2 inch 1
I set at 134 | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 5/8 inch cs
17 lb P-110 cs
150 ft with 11 | Jater Brine
ogram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to | Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d | Hole Size
17 5
12.25
7.875
8.75
bise to drill 17
rl 12 1/4 inch m | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500 | 19.7
Type
75
15
5
5
5
6
7
7
7
7
7
7
7
7
7
7
7
7
7 | Proposed Casi
Casing Weight/ft
48
40
17
17
Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 Ib P110 csg and | ng and C
Sett
Fam: Ad
run 48 lb H
40 lb J-55
5 1/2 inch 1
I set at 134 | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 5/8 inch cs
17 lb P-110 cs
150 ft with 11 | Veter Brine
Degram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement
D
D
t at 400 ft wit
100 ft with 10
500 ft. Drl 7 7
iC 8500'. | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to | Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft | Hole Size
17 5
12.25
7.875
8.75
2.55
12.25
7.875
8.75
12.1/4 inch
rl 12 1/4 inch h
with cut brine | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500 | 19.7
Type
75
15
5
5
5
6
7
7
7
7
7
7
7
7
7
7
7
7
7 | Proposed Casi
Casing Weight/ft
48
40
17
17
(Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 lb P110 csg and | ng and C
Sett
Fam: Ad
run 48 lb H
40 lb J-55
5 1/2 inch 1
I set at 134 | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog | Veter Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to | Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
D | Hole Size
17 5
12.25
7.875
8.75
Dose to drill 17
rl 12 1/4 inch n
with cut brine
Type
oubleRam | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run | 19.7 Type 75 15 15 15 15 15 15 16 10 ft with cu 5 1/2 inch 17 17 17 18 19 19 19 10 ft Work 19 10 ft Work 10 10 ft | Proposed Casi
Casing Weight/ft
48
40
17
17
/Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 Ib P110 csg and
roposed Blowo
sing Pressure
3000 | ram: Ad
run 48 lb I
140 lb J-55
5 1/2 inch 1
1 set at 134
ut Preven | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300 | Veter Brine
Digram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron | Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
D
D | Hole Size
17 5
12.25
7.875
8.75
Dose to drill 17
rl 12 1/4 inch n
with cut brine
Type
oubleRam | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run | 19.7 Type 75 15 15 15 15 15 15 16 10 ft with cu 5 1/2 inch 17 17 17 18 19 19 19 10 ft Work 19 10 ft Work 10 10 ft | Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7 | ram: Ad
run 48 lb I
140 lb J-55
5 1/2 inch 1
1 set at 134
ut Preven | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300 | Veter Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron | Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
3450 ft
D
Chereby cer
of my know
(further of | Synthetic
ed Loop System
Hole Size
17 5
12.25
7.875
8.75
bose to drill 17
rl 12 1/4 inch n
rl 12 1/4 inch h
with cut brine
Type
oubleRam
tify that the infor
vledge and belief.
erify fhat the de | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
billing pit v | 19.1
Type
75
15
5
5
6
75
75
75
75
75
75
75
75
75
75 | Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7 | ng and O
Sett
Sett
ram: Ad
run 48 lb I
40 lb J-55
5 1/2 inch 1
lset at 134
ut Preven | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300 | Veter Brine
Digram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron | Closs
Type
Surf
Inti
Prod
Int2
We propo
unface; d
curface; d
3450 ft
D
hereby cer
frmy know
further c
WMOCD g | Synthetic
ed Loop System
Hole Size
17 5
12.25
7.875
8.75
bose to drill 17
rl 12 1/4 inch n
rl 12 1/4 inch h
with cut brine
Type
oubleRam
tify that the infor
vledge and belief.
erify fhat the de | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
billing pit v | 19.1
Type
75
15
5
5
6
75
75
75
75
75
75
75
75
75
75 | Proposed Casi
Casing Weight/ft
48
40
17
17
(Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 lb P110 csg and
roposed Blowo
sing Pressure
3000
e and complete to the | ng and O
Sett
Sett
ram: Ad
run 48 lb H
A0 lb J-55
5 1/2 inch 1
I set at 134
ut Preves | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300 | Veter Brine
Digram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron | Closs
Type
Surf
Int1
Prod
Int2
We propo
wrface; d
wrface; d
ad50 ft
D
hereby cer
f my know
furfher c
WMOCD a
D CD-appr
Printed 1 | Hole Size
17 5
12.25
7.875
8.75
2.75
2.75
3.75
2.75
3.75
2.75
3.75
3.75
2.75
2.75
3.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75 | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
mation gives
mation gives
mation gives
mation gives | 19.75
Type
75
19.5
19.5
19.5
19.5
19.5
19.5
19.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
1 | Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7 | ng and C
Sett
Sett
ram: Ad
run 48 lb I
1 40 lb J-55
5 1/2 inch 1
l set at 134
ut Preven
best
best
re
Appr
Title: | Fresh V
Cement Pro-
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pn
300
OIL CO
oved By: Pa
Geologist | Vater Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron
7/SION | Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
(3450 ft)
D
(hereby cer
of my know
(hereby cer
of my know)
(hereby cer
of my know)
(hereby cer
of my know) | Hole Size
17 5
12.25
7.875
8.75
2.55
2.55
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75 | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
billing pit v
general per
nically fileo
yst | 19.7 Type 75 75 75 75 75 75 75 75 75 75 75 75 75 | Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7 | ng and C
Sett
Sett
ram: Ad
run 48 lb I
1 40 lb J-55
5 1/2 inch 1
l set at 134
ut Preven
best
best
re
Appr
Title: | Fresh V
Cement Pro-
ing Depth
4000
13450
8500
ditional Co
H-40 13 3/8 if
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro-
300
OIL CO
oved By: Pa | Vater Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron | Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
3450 ft
D
(hereby cer
of my know
Chereby cer
of my know | Synthetic
ed Loop System
Hole Size
17 5
12.25
7.875
8.75
bese to drill 17
rl 12 1/4 inch h
with cut brine
Type
tify that the infor
veldge and belief
erify fhat the d
rudelinesa
oved plan []
Vame: Electror
oduction Anal
Idress. produc | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation give
mation give
paral per
nically fileo
yst
tion@mar | 19.7 Type 75 75 75 75 75 75 75 75 75 75 75 75 75 | Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7 | ng and C
Sett
Sett
ram: Ad
run 48 lb H
run 48 lb H
run 48 lb H
set at 134
ut Preven
best
best
re
Appr
Title:
Appr | Fresh V
Cement Pro-
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro-
300
OIL CO
oved By: Pa
Geologist
oved Date: 1. | Vater Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Zement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron
/ISION |
| Proposed Casi
Casing Weight/ft
48
40
17
17
(Cement Prog
with fresh water,
ut brine water, run
t brine water, run | ng and C
Sett
Fam: Ad
run 48 lb H
40 lb J-55
5 1/2 inch 1
I set at 134 | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 5/8 inch cs
17 lb P-110 cs
150 ft with 11 | Jater Brine
ogram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0

 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d | Hole Size
17 5
12.25
7.875
8.75
bise to drill 17
rl 12 1/4 inch m | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500 | 19.7
Type
75
15
5
5
5
6
7
7
7
7
7
7
7
7
7
7
7
7
7

 | Proposed Casi
Casing Weight/ft
48
40
17
17
Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 Ib P110 csg and | ng and C
Sett
Fam: Ad
run 48 lb H
40 lb J-55
5 1/2 inch 1
I set at 134 | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 5/8 inch cs
17 lb P-110 cs
150 ft with 11 | Veter Brine
Degram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement
D
D
t at 400 ft wit
100 ft with 10
500 ft. Drl 7 7
iC 8500'. | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft | Hole Size
17 5
12.25
7.875
8.75
2.55
12.25
7.875
8.75
12.1/4 inch
rl 12 1/4 inch h
with cut brine | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500 | 19.7
Type
75
15
5
5
5
6
7
7
7
7
7
7
7
7
7
7
7
7
7

 | Proposed Casi
Casing Weight/ft
48
40
17
17
(Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 lb P110 csg and | ng and C
Sett
Fam: Ad
run 48 lb H
40 lb J-55
5 1/2 inch 1
I set at 134 | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog | Veter Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
D | Hole Size
17 5
12.25
7.875
8.75
Dose to drill 17
rl 12 1/4 inch n
with cut brine
Type
oubleRam | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run | 19.7 Type 75 15 15 15 15 15 15 16 10 ft with cu 5 1/2 inch 17 17 17 18 19 19 19 10 ft Work 19 10 ft Work 10 10 ft

 | Proposed Casi
Casing Weight/ft
48
40
17
17
/Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 Ib P110 csg and
roposed Blowo
sing Pressure
3000 | ram: Ad
run 48 lb I
140 lb J-55
5 1/2 inch 1
1 set at 134
ut Preven | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300 | Veter Brine
Digram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
D
D | Hole Size
17 5
12.25
7.875
8.75
Dose to drill 17
rl 12 1/4 inch n
with cut brine
Type
oubleRam | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run | 19.7 Type 75 15 15 15 15 15 15 16 10 ft with cu 5 1/2 inch 17 17 17 18 19 19 19 10 ft Work 19 10 ft Work 10 10 ft

 | Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7 | ram: Ad
run 48 lb I
140 lb J-55
5 1/2 inch 1
1 set at 134
ut Preven | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300 | Veter Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
3450 ft
D
Chereby cer
of my know
(further of | Synthetic
ed Loop System
Hole Size
17 5
12.25
7.875
8.75
bose to drill 17
rl 12 1/4 inch n
rl 12 1/4 inch h
with cut brine
Type
oubleRam
tify that the infor
vledge and belief.
erify fhat the de | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
billing pit v | 19.1
Type
75
15
5
5
6
75
75
75
75
75
75
75
75
75
75

 | Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7 | ng and O
Sett
Sett
ram: Ad
run 48 lb I
40 lb J-55
5 1/2 inch 1
lset at 134
ut Preven | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300 | Veter Brine
Digram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Closs
Type
Surf
Inti
Prod
Int2
We propo
unface; d
curface; d
3450 ft
D
hereby cer
frmy know
further c
WMOCD g | Synthetic
ed Loop System
Hole Size
17 5
12.25
7.875
8.75
bose to drill 17
rl 12 1/4 inch n
rl 12 1/4 inch h
with cut brine
Type
oubleRam
tify that the infor
vledge and belief.
erify fhat the de | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
billing pit v | 19.1
Type
75
15
5
5
6
75
75
75
75
75
75
75
75
75
75

 | Proposed Casi
Casing Weight/ft
48
40
17
17
(Cement Prog
with fresh water,
ut brine water, run
t brine water, run
17 lb P110 csg and
roposed Blowo
sing Pressure
3000
e and complete to the | ng and O
Sett
Sett
ram: Ad
run 48 lb H
A0 lb J-55
5 1/2 inch 1
I set at 134
ut Preves | Fresh V
Cement Pro
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
5 9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro
300 | Veter Brine
Digram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Closs
Type
Surf
Int1
Prod
Int2
We propo
wrface; d
wrface; d
ad50 ft
D
hereby cer
f my know
furfher c
WMOCD a
D CD-appr
Printed 1 | Hole Size
17 5
12.25
7.875
8.75
2.75
2.75
3.75
2.75
3.75
2.75
3.75
3.75
2.75
2.75
3.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75
2.75 | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
mation gives
mation gives
mation gives
mation gives | 19.75
Type
75
19.5
19.5
19.5
19.5
19.5
19.5
19.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
10.5
1

 | Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7 | ng and C
Sett
Sett
ram: Ad
run 48 lb I
1 40 lb J-55
5 1/2 inch 1
l set at 134
ut Preven
best
best
re
Appr
Title: | Fresh V
Cement Pro-
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pn
300
OIL CO
oved By: Pa
Geologist | Vater Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron
7/SION | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
(3450 ft)
D
(hereby cer
of my know
(hereby cer
of my know)
(hereby cer
of my know)
(hereby cer
of my know) | Hole Size
17 5
12.25
7.875
8.75
2.55
2.55
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75
3.75 | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation gives
billing pit v
general per
nically fileo
yst | 19.7 Type 75 75 75 75 75 75 75 75 75 75 75 75 75

 | Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7 | ng and C
Sett
Sett
ram: Ad
run 48 lb I
1 40 lb J-55
5 1/2 inch 1
l set at 134
ut Preven
best
best
re
Appr
Title: | Fresh V
Cement Pro-
ing Depth
4000
13450
8500
ditional Co
H-40 13 3/8 if
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro-
300
OIL CO
oved By: Pa | Vater Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Cement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |
| Close
Type
Surf
Int1
Prod
Int2
We propo
surface; d
surface; d
(3450 ft
3450 ft
D
(hereby cer
of my know
Chereby cer
of my know | Synthetic
ed Loop System
Hole Size
17 5
12.25
7.875
8.75
bese to drill 17
rl 12 1/4 inch h
with cut brine
Type
tify that the infor
veldge and belief
erify fhat the d
rudelinesa
oved plan []
Vame: Electror
oduction Anal
Idress. produc | Casing
13.3
9.62
5.5
1/2 inch ho
hole to 400
ole to 8500
water, run
mation give
mation give
paral per
nically fileo
yst
tion@mar | 19.7 Type 75 75 75 75 75 75 75 75 75 75 75 75 75

 | Proposed Casi
Casing Weight/ft
48
40
17
17
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7
7 | ng and C
Sett
Sett
ram: Ad
run 48 lb H
run 48 lb H
run 48 lb H
set at 134
ut Preven
best
best
re
Appr
Title:
Appr | Fresh V
Cement Pro-
ing Depth
400
4000
13450
8500
ditional Co
H-40 13 3/8 i
9 5/8 inch cs
17 lb P-110 c:
150 ft with 11
ntion Prog
Test Pro-
300
OIL CO
oved By: Pa
Geologist
oved Date: 1. | Vater Brine
pgram
Sacks of C
400
1000
1100
0
0
0
0
0
0
0
0
0
0
0
0 | Zement | Estimated TOC
0
0
8500
0
h 400 sx cmt, circ
00 sx cmt, circ to
7/8 inch hole to
anufacturer
Cameron
/ISION | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
 | | | | | | | | | | | | | | | | | | |

,

÷

District I

1625 N. French Dr., Hobbs, NM 88240 Phone (505) 393-6161 Fax:(505) 393-0720

District II

1301 W. Grand Ave., Artesia, NM 88210 Phone:(505) 748-1283 Fax.(505) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone.(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u>

1220 S. St Francis Dr., Santa Fe, NBA 87505 Phone (505) 476-3470 Fax: (505) 476-3462

é

State of New Mexico **Energy, Minerals and Natural Resources**

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-05-2 8 018	2. Pool Code		3. Pool Name CAT WOLFCAMP
4. Property Code 36941	5. Property Name MAKETRACKS STATE COM		6. Well No. 001
7. OGRID No. 14049			9. Elevation 4372

10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	35	1 <i>5</i> S	31E	D	660	N	330	W	CHAVES

11 Bottom Hole Location If Different From Surface

	11. Dottom Tible Eddatom if Different Fibm bullate								
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	35	15S	31E	A	660	N	330	E	CHAVES
	12. Dedicated Acres 13. Joint or Infill 160.00			14. Consolidation	Codé		15. Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

o O		

OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Diana Briggs Title: Production Analyst Date: 1/16/2008

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. Surveyed By: Ronald Eidson

Date of Survey: 1/3/2008

Certificate Number: 3239

Permit Comments

Operator: MARBOB ENERGY CORP , 14049 Well: MAKETRACKS STATE COM #001 Well:

API: 30-05-29018

Created By	Lomment	Comment Date
MARBOB4	Marbob will be using a closed mud loop system with fresh water pits.	1/16/2008
MARBOB4	Marbob Energy has conducted a review to determine if an H2S contingency plan is required for the above referenced well. We were able to conclude that any potential hazardous volume would be minimal. H2S concentrations of wells in this area from surface to TD are low enough; therefore we do not believe that an H2S Contingency Plan would be necessary.	1/16/2008

Permit Conditions of Approval

Operator: MARBOB ENERGY CORP , 14049 Well: MAKETRACKS STATE COM #001

ı.

API: 30-05-29018

 \cdot

OCD Reviewer	Condition
lokautz	Pit construction and closure must satisfy all requirements of your approved plan, O.C.D. Rule 19.15.2.50, and the Pit and Below-Grade Tank Guidelines