

Submit 3 Copies To Appropriate District

Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103


Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. <u>30-025-36114</u>
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator APACHE CORPORATION		6. State Oil & Gas Lease No.
3. Address of Operator TWO WARREN PLACE, SUITE 1500 6120 S. YALE TULSA, OK 74136-4224		7. Lease Name or Unit Agreement Name: DC HARDY
4. Well Location Unit Letter <u>0</u> : <u>330</u> feet from the <u>SOUTH</u> line and <u>1330</u> feet from the <u>EAST</u> line Section <u>20</u> Township <u>21S</u> Range <u>37E</u> NMPM County <u>LEA</u>		8. Well No. <u>6</u>
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3482' GL		9. Pool name or Wildcat BENROSE SKELLY; GRAYBURG

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPLETION <input type="checkbox"/> OTHER: <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER: CMT SURF CSG; TD; SET PROD CSG. <input type="checkbox"/>

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

PLEASE SEE ATTACHED DRILLING HISTORY.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Larry E. Rader TITLE TECH. COORDINATOR-DRLG. DATE 2/10/03

Type or print name LARRY E. RADER

Telephone No. 918-491-4900

(This space for State use)

APPROVED BY [Signature] TITLE PETROLEUM ENGINEER

DATE FEB 14 2003

Conditions of approval, if any:

WELL:
API#

DC HARDY #6
30-025-36114

2/4/2003 MIRU CAPSTAR RIG #8. SPUD 12-1/4" HOLE @ 11:00 A.M. 2/3/03. DRILL & SURVEY TO 411'. RIH W/ 8-5/8" 24# J55 CASING. CEMENT SHOE @ 411' W/ 325 SX CLASS C + 2% CACL + 0.125 #/SX CELLO FLAKE=78 BBLs 14.8 PPG SLURRY W/ 1.35 CF/SX YIELD. CIRC 79 SX CEMENT TO PIT. WOC.

2/3/03 - 2/7/03 DRILL & SURVEY 411' - 3789'.

2/8/2003 DRILL 3789' - 4100'. RUN LOGS.

2/9/2003 RIH W/ 5-1/2" 17# J55 CASING W/17 CENTRALIZERS. CEMENT SHOE @ 4100' W/ 500 SX 50:50 POZ:CLASS C W/10% GEL + 5% SALT + 0.125#/SX CELLO FLAKE + 0.003 GPS FP-6L=217 BBLs. 11.8 PPG SLURRY W/ 2.44 CF/SX YIELD. TAIL W/ 250 SX 50:50 POZ:CLASS C W/2% GEL + 5% SALT + 0.003 GPS FP-6L=57 BBLs 14.2 PPG SLURRY W/ 1.29 CF/SX YIELD. BUMPED PLUG & HELD. CIRC 157 SX CMT TO PIT. CUT OFF CSG. RELEASE RIG 2/9/03 10:00 A.M.

