

Form 3160-3
(April 2004)

OCD-HOBBS

Split Estate

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED
OMB No 1004-0137
Expires March 31, 2007

5 Lease Serial No
NM-2511

6 If Indian, Allottee or Tribe Name

7 If Unit or CA Agreement, Name and No.

8 Lease Name and Well No
Myer B-28 A Com AC2 #6

9 API Well No.
30-025-38764

10 Field and Pool, or Exploratory
Eumont (Yates-7Rivers-Queen) Gas

11 Sec, T R, M or Blk and Survey or Area

Sec 28, T-20S-R37E

12 County or Parish

Lea

13 State

NM

1a. Type of work: ☒ DRILL ☐ REENTER

1b. Type of Well: ☐ Oil Well ☒ Gas Well ☐ Other ☒ Single Zone ☐ Multiple Zone

2 Name of Operator
EnerVest Operating, Ltd.

3a Address **1001 Fannin, Suite 800
Houston, Texas 77002-6707**

3b Phone No. (include area code)
713/495-6530

4 Location of Well (Report location clearly and in accordance with any State requirements *)

At surface **1880' FSL AND 1980' FEL**

At proposed prod. zone

Unit J

14. Distance in miles and direction from nearest town or post office*

3 miles north of Oil Center, New Mexico

15 Distance from proposed* location to nearest property or lease line, ft (Also to nearest drg. unit line, if any) **1880'**

16 No of acres in lease

1640

17. Spacing Unit dedicated to this well

360

18 Distance from proposed* location to nearest well, drilling, completed, applied for, on this lease, ft **990'**

19 Proposed Depth

3800'

20. BLM/BIA Bond No on file

RLB0010838

NMB000503

1-17-08

21 Elevations (Show whether DF, KDB, RT, GL, etc.)
GL 3505'

22. Approximate date work will start*

03/01/2008

23. Estimated duration

10 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, shall be attached to this form

1. Well plat certified by a registered surveyor.

2. A Drilling Plan

3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office)

4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).

5. Operator certification

6. Such other site specific information and/or plans as may be required by the authorized officer

25 Signature

Name (Printed/Typed)

Gary Miller

Date

01/14/2008

Title

Agent, EnerVest Operating, Ltd

Approved by (Signature)

/s/ James Stovall

Name (Printed/Typed)

/s/ James Stovall

Date

FEB 1 2 2008

Title

FIELD MANAGER

Office

CARLSBAD FIELD OFFICE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on page 2)

Lea County Controlled Water Basin

RECEIVED

FEB 13 2008

CONDITIONS OF APPROVAL BY THE OCD
-- Approval for drilling only, CANNOT produce until OCD Santa Fe approve Simultaneous Dedication of Acreage and Pool/Formation.

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

HOBBS OCD
**APPROVAL SUBJECT TO
GENERAL REQUIREMENTS
AND SPECIAL STIPULATIONS
ATTACHED**

DISTRICT I
1625 N. FRENCH DR., HOBBS, NM 88240

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102

DISTRICT II
1301 W. GRAND AVENUE, ARTESIA, NM 88210

OIL CONSERVATION DIVISION
1220 SOUTH ST. FRANCIS DR.
Santa Fe, New Mexico 87505

Revised October 12, 2005
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV
1220 S. ST. FRANCIS DR., SANTA FE, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number 30-025-38764	Pool Code 76480	Pool Name Eumout (Y-7R-Q) Gas
Property Code 303914	Property Name MYERS B-28 A COM AC 2	Well Number 6
OGRID No. 143199	Operator Name EnerVest Operating	Elevation 3505'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
J	28	20-S	37-E		1880	SOUTH	1980	EAST	LEA


Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedicated Acres 360	Joint or Infill	Consolidation Code	Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

		OPERATOR CERTIFICATION <i>I hereby certify that the information herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</i> Signature: <i>[Signature]</i> Date: 1-14-08 Printed Name: Gay Miller	
SECTION 28 SECTION 33		SURVEYOR CERTIFICATION <i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</i> Date Surveyed: 12/11/07 Signature: <i>[Signature]</i> Professional Surveyor: 3239 Certificate No. 12641 RONALD J. EIDSON 3239	
GEODETIC COORDINATES NAD 27 NME Y=562515.1 N X=832678.2 E LAT.=32 541828" N LONG.=103 253790" W			

LOCATION VERIFICATION MAP



SCALE: 1" = 2000'

CONTOUR INTERVAL:
MONUMENT SOUTH, N.M. - 5'

SEC. 28 TWP. 20-S RGE 37-E

SURVEY N.M.P.M.

COUNTY LEA STATE NEW MEXICO

DESCRIPTION 1880' FSL & 1980' FEL

ELEVATION 3505'

OPERATOR EnerVest Operating

LEASE MYERS B-28 A COM AC


U.S.G.S. TOPOGRAPHIC MAP

MONUMENT SOUTH, N.M.




PROVIDING SURVEYING SERVICES
SINCE 1946
JOHN WEST SURVEYING COMPANY
412 N. DAL PASO
HOBBS, N.M. 88240
(505) 393-3117

VICINITY MAP




SCALE: 1" = 2 MILES

SEC. 28 TWP. 20-S RGE. 37-E
 SURVEY N.M.P.M.
 COUNTY LEA STATE NEW MEXICO
 DESCRIPTION 1880' FSL & 1980' FEL
 ELEVATION 3505'
 OPERATOR EnerVest Operating
 LEASE MYERS B-28 A COM AC





SECTION 28, TOWNSHIP 20 SOUTH, RANGE 37 EAST, N.M.P.M.,
LEA COUNTY, NEW MEXICO



DIRECTIONS TO LOCATION

FROM THE INTERSECTION OF STATE HIGHWAY 8 AND COUNTY ROAD H49 (HILL ROAD), GO EAST ON HILL ROAD APPROX. 0.1 MILE. TURN LEFT AND GO NORTH ON HILL ROAD APPROX. 0.4 MILES. THIS LOCATION IS APPROX. 110 FEET WEST.



EnerVest Operating

MYERS B-28 A COM AC2#6 WELL
LOCATED 1880 FEET FROM THE SOUTH LINE
AND 1980 FEET FROM THE EAST LINE OF SECTION 28,
TOWNSHIP 20 SOUTH, RANGE 37 EAST, N.M.P.M.,
LEA COUNTY, NEW MEXICO

Survey Date: 12/18/07	Sheet 1 of 1 Sheets
W.O. Number: 07.11.1877	Dr By: DSS
Date: 12/28/07	Disk: .
07111877	Scale: 1"=100'



EnerVest Operating, Ltd.

Drilling Plan

Eumont Field

1,880' FSL & 1,980' FEL Sec 28 T20S R37E

Lea County, NM

Rig Telephone #:

Rig FAX #:

GL = 3,519'

Meyer B28 A COM AC #6 - DRILLING PROGRAM

1 Geologic Name of Surface Formation & Directions to Well

Quaternary

Directions to well:

2 Estimated Tops of Important Geologic Markers

MD	SS	Formation	Objective	Rock Type
		Rustler		(Anhydrite)
		Salado Salt		(Salt & Anhydrite)
2,670	832	Yates	Primary	(Sandstone & Dolomite)
2,932	570	Seven Rivers	Primary	(Sandstone & Dolomite)
3,418	84	Queen	Primary	(Anhydrite, SS & Dolomite)
3,529	-27	Penrose	Primary	(Lower Queen)
3,720	-218	Grayburg		(Dolomitic SS)

3 Estimated Depths of Anticipated Fresh Water, Oil and Gas

MD	SS	Formation	Objective	Fluid Type
		Rustler		
		Salado Salt		None
2,670	832	Yates	Primary	(Sandstone & Dolomite)
2,932	570	Seven Rivers	Primary	(Sandstone & Dolomite)
3,418	84	Queen	Primary	(Anhydrite, SS & Dolomite)
3,529	-27	Penrose	Primary	(Lower Queen)
3,720	-218	Grayburg		(Dolomitic SS)

No other formations are expected to give up oil, gas or fresh water in measurable quantities. Setting 8-5/8" casing to 1,250' and circulating cement back to the surface will protect the surface fresh water sand. All zones containing commercial quantities of oil or gas will have cement circulated across them by cementing the 5-1/2" production casing back to at least the 8-5/8" casing shoe. Cement volumes will be pumped to provide cement back to surface.



EnerVest Operating, Ltd.

Drilling Plan

Eumont Field

1,880' FSL & 1,980' FEL Sec 28 T20S R37E

Lea County, NM

GL = 3,519'

Rig Telephone #:

Rig FAX #:

4 Casing Program

Hole Size	Interval	OD Casing	Weight	Grade	Conn./New?	Bur/Col/Tens
11"	0-1,250'	8-5/8"	24#	J-55	STC/New	2.00 / 2.40 / 9.35
7-7/8"	0-3,800'	5-1/2"	15.50#	J-55	LTC/New	1.12 / 2.38 / 4/24

5 Cement Program

8-5/8" Surface Casing
100% XS

LEAD 200 SX, 35/65/6, C/Poz/Gel, 2.00 cf/sk, 12.6 PPG
TAIL 200 SX, Class "C", 1.32 cf/sk, 14.8 PPG

5-1/2" Production Csg

LEAD 300 SX, 35/65, Poz/H, 1.90 cf/sk, 12.5 PPG
TAIL 420 SX, Class H, 1.32 cf/sk, 14.8 PPG

6 Minimum Specifications for Pressure Control & Wellhead Equipment

The blowout preventer equipment (BOPE) shown in Exhibit #9 will consist of a double ram-type (2,000 psi WP) preventer. This unit will be hydraulically operated and the ram type preventer will be equipped with blind rams on bottom and 4-1/2" drill pipe rams on top. The BOPE will be nipped up on the 8-5/8" surface casing and tested to 2,000 psi by a third party. Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment (Exhibit #10) will include a kelly cock and floor safety valve, choke lines and a choke manifold (Exhibit #11) and will have a 2,000 psi WP rating.

A 2,000 psi WP Larkin Type Wellhead will be used.

7 Types and Characteristics of the Proposed Mud System

The surface hole will be drilled with a fresh water mud.

The production hole will be drilled with saturated brine water.

DEPTH	TYPE	WEIGHT	VISCOSITY	WATER LOSS
0-1,250'	FW Mud	8.7	28	N.C.
1,250'-TD	Brine	10	30	12 cc



EnerVest Operating, Ltd.

Drilling Plan

Eumont Field

1,880' FSL & 1,980' FEL Sec 28 T20S R37E

Lea County, NM

GL = 3,519'

Rig Telephone #:

Rig FAX #:

Sufficient mud materials will be kept at the well site to maintain mud properties and meet minimum lost circulation and weight increase requirements at all times.

8 Auxillary Well Control and Monitoring Equipment

- A. Kelly cock will be kept in the drill string at all times.
- B. A full opening drill pipe-stabbing valve with proper drill pipe connections will be on the rig floor at all times.

9 Logging, Testing and Coring Program

- A. The electric logging program will consist of a GR-Dual Laterolog Litho Density log run from TD to the surface casing shoe.
- B. A GR-Neutron will be run to surface.
- C. No mud logger will be used.
- D. No conventional coring is anticipated.
Further testing procedures will be determined after the 5-1/2" production casing has been cemented at TD, based on drill shows and log evaluation.

10 Abnormal conditions, Pressure, Temperatures and Potential Hazards

No abnormal pressures or temperatures are anticipated. The estimated bottom hole at TD is 97°F and the estimated maximum bottom hole pressure is 1,700 psi. Lost returns have been experienced in offset wells. Losses have occurred below 2,700'.

11 Anticipated Starting Date and Duration of Operations

Road and location work will not begin until approval has been received from the BLM. Anticipated Start Date is February 1, 2008.

Once commenced, drilling operations should be finished in approximately 12 days. If the well is productive, an additional 30 days will be required for completion and testing before a decision is made to install permanent facilities.



EnerVest Operating, Ltd.

Drilling Plan

Eumont Field

1,880' FSL & 1,980' FEL Sec 28 T20S R37E

Lea County, NM

GL = 3,519'

Rig Telephone #:

Rig FAX #:

12 Safety

Conduct Tour Safety Meetings with all crews and record topics of these meetings on the IADC and morning reports. Document all personnel in attendance and topics of these Safety Meetings. Keep these documents on file in company representative's office for inspection.

13 Notes

Stamp, Code and Sign all Invoices

H₂S Area? If yes, attach contingency plan.

Inclinations: Survey every 500' or bit trip

Drop Totco every trip out to check the angle. Max inclination = 3°

Call Houston if survey is $\geq 3^\circ$

Mud Disposal: Closed Loop system will be used. Haul off all cuttings and fluids.

BHA #1 **Surface** BIT-2 DC-STAB-DC as needed (60' Pendulum)

BHA #2 **Production** BIT-DC-STAB-DC-STAB-DC as needed (30/60 Pendulum)


BIT PROGRAM


			RPM	WOB
Surface	11"	Smith F29	90	35k
Production	7-7/8"	HC 506ZX	50-75	50-75k

WELL Meyer B28 A COM AC #6				ENERVEST					
TYPE	VERTICAL	RIG	UNION DRILLING TEXAS #201	DATE	1/2/2008				
FIELD	EUMONT	COUNTY	LEA COUNTY, NEW MEXICO	ELEVATION	3,519'				
GAS/OIL	GAS	MUD	TBD	CEMENT	TBN				
LOCATION	1,880' FSL & 1,980' FEL SEC 28 T20S R37E			SBHT	99° F				
COMMENTS. OBJECTIVE FORMATION: QUEEN SANDSTONE & DOLOMITE									
NOTE:									
MUD- LOGGER	SURVEYS	WOB/GPM BIT	FORMATION TOPS HOLE SIZES	VERTICAL DEPTH	MUD WEIGHT	OPEN HOLE LOGS	CEMENT	WELLHEAD	REMARKS
14" CONDUCTOR				40'					
INCLINATIONS 5K/300 400' & 1,250' 10K/350 11" HOLE 15K/450 TYPE 2 INSERT NO MUD LOGGER BHA #1 RED BEDS					8.5 - 8.8 PPG NATIVE				
8-5/8" 24# J55 STC				1,250'	LEAD: 200 Sks 35:65:6 POZ:C:GEL (2.00 Yld, 12 6 PPG) TAIL: 200 Sks Class "C" 2% CaCl2 (1 32 Yld, 14.8 PPG) (100 % Excess) FLOAT COLLAR & TEXAS PATTERN SHOE TOP OUT: IF NEEDED				
INCLINATIONS 1,800', 2,800', 3,800' 10K/350 7-7/8" HOLE OR AS NEEDED HCC 506ZX 15K/500 RUSTLER ANHYD. > BHA #2 NO MUD LOGGER SALADO SALT / ANHYD >					9.8 - 10.1 PPG BRINE				
20K/500				2,000'					
22K/500				2,400'	< ADD STARCH FOR 15 - 20 CC WL				
POS LR - DEPLETION TANSIL (DOLO / ANHYD) >					< POS LOST RETURNS 2,700' - 3,600'				
25K/500 YATES (SS / DOLO) >					OPEN HOLE LOGS: HALLIBURTON TD TO SC: GR / LITHO DENSITY / DUAL LATEROLOG TD TO SURFACE: GR / NEUTRON				
SEVEN RIVERS (SS / DOLO) >					< POSSIBLE LOST RETURNS				
PRIMARY OBJECTIVE QUEEN (ANHYD / SS / DOLO) >					LEAD: 300 SKS 35:65 POZ:H (12.5 PPG 1.90 CF/SK) TAIL: 420 SKS CLASS "H" (14.8 PPG 1.32 CF/SK) (15% EXCESS OVER CALIPER) CEMENT TO SURFACE FLOAT SHOE, 1 JT, FLOAT COLLAR				
PENROSE (LOWER QUEEN) >									
5-1/2 15.50# J55 LTC				3,800'					
					OFFICE		HOME		
AFE #	C0-1107-297	REGULATORY	RONNIE YOUNG		(713) 495-6530	(832) 559-8128			
EV #	45189.001	ENGINEER	EARL WAHRMUND		(713) 495-5367	(281) 360-6494			
API #	30-025-	GEOLOGIST	ROGER TREJO		(713) 495-5317	(281) 265-5973			



BOP DIAGRAM
LEA COUNTY, NEW MEXICO





PECOS DISTRICT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	EnerVest Operating
LEASE NO.:	NM-2511
WELL NAME & NO.:	6-Myer B-28 A Com AC2
SURFACE HOLE FOOTAGE:	1880' FSL & 1980' FEL
BOTTOM HOLE FOOTAGE	' F L & ' F L
LOCATION:	Section 28, T. 20 S., R 37 E., NMPM
COUNTY:	Lea County

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
 - Lesser Prairie Chicken
- ☐ **Construction**
 - Notification
 - Topsoil
 - Reserve Pit
 - Federal Mineral Material Pits
 - Well Pads
- ☐ **Road Section Diagram**
- ☒ **Drilling**
- ☐ **Production (Post Drilling)**
- ☐ **Reserve Pit Closure/Interim Reclamation**
- ☐ **Final Abandonment/Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken: Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 15 through June 15 annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Hobbs Field Station at (505) 393-3612 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

There is no measurable soil on this well pad to stockpile. No topsoil stockpile is required.

C. RESERVE PITS

The operator has applied for a closed-loop system. The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

If the operator elects to surface the access road and/or well pad, mineral materials extracted during construction of the reserve pit may be used for surfacing the well pad and access road and other facilities on the lease.

Payment shall be made to the BLM prior to removal of any additional federal mineral materials from any site other than the reserve pit. Call the Carlsbad Field Office at (505) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation.

The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

VII. DRILLING

A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified a minimum of 4 hours in advance for a representative to witness:

- a. Spudding well
- b. Setting and/or Cementing of all casing strings
- c. BOPE tests

☒ **Lea County**

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240,
(575) 393-3612

- 1. A Hydrogen Sulfide (H₂S) Drilling Plan should be activated 500 feet prior to drilling into the **Yates** formation. **Hydrogen Sulfide has been measured between 300-700 ppm in the gas stream.**
- 2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.

B. CASING

- 1. The **8-5/8** inch surface casing shall be set **at approximately 1250 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt)** and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with a surface log readout will be used or a cement bond log shall be run to verify the top of the cement.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum 18 hours for a water basin, 24 hours in the potash area, or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement). **Please provide WOC times to inspector for cement slurries.**
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, a remedial cement job will be done prior to drilling out that string.

Possible lost circulation in the Glorietta formation.

2. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - ☒ Cement to surface. If cement does not circulate, contact the appropriate BLM office.
4. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

C. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. The tests shall be done by an independent service company.
 - b. The results of the test shall be reported to the appropriate BLM office.
 - c. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
 - d. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug.

D. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

Engineer on call phone (after hours): Carlsbad: (575) 706-2779

WWI 020708

VIII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Containment Structures

The containment structure shall be constructed to hold the capacity of the entire contents of the largest tank, plus 24 hour production, unless more stringent protective requirements are deemed necessary by the Authorized Officer.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color
Shale Green, Munsell Soil Color Chart # 5Y 4/2

IX. INTERIM RECLAMATION & RESERVE PIT CLOSURE

A. INTERIM RECLAMATION

If the well is a producer, interim reclamation shall be conducted on the well site in accordance with the orders of the Authorized Officer. The operator shall submit a Sundry Notices and Reports on Wells (Notice of Intent), Form 3160-5, prior to conducting interim reclamation.

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Operators should work with BLM surface management specialists to devise the best strategies to reduce the size of the location. Any reductions should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

Seed Mixture 2, for Sandy Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law (s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Sand dropseed (<i>Sporobolus cryptandrus</i>)	1.0
Sand love grass (<i>Eragrostis trichodes</i>)	1.0
Plains bristlegrass (<i>Setaria macrostachya</i>)	2.0

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed

X. FINAL ABANDONMENT & REHABILITATION REQUIREMENTS

Upon abandonment of the well and/or when the access road is no longer in service the Authorized Officer shall issue instructions and/or orders for surface reclamation and restoration of all disturbed areas.

On private surface/federal mineral estate land the reclamation procedures on the road and well pad shall be accomplished in accordance with the private surface land owner agreement.