Submit 3 Copies To Appropriate District	State o	f New Me	exico		Form C-103
Office District I	Energy, Minerals and Natural Resources			May 27, 2004	
1625 N. French Dr , Hobbs, NM 88240				WELL API NO.	
District II			30-	-025-01130	
1301 W. Grand Ave , Artesia, NM 88210	CSIA, 1414 60210			5. Indicate Type of	of Lease
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.				₹ FEE □
District IV	Santa I	Fe, NM 87	7505	6. State Oil & G	
1220 S St. Francis Dr , Santa Fe, NM 8750.		,		o. state on a s	us Louise 110.
	ICES AND REPORTS (ON WELLS		7 Lease Name or	Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOS					
DIFFERENT RESERVOIR. USE "APPLIC				New Mexico BG	State NCT 1
PROPOSALS)	·	•			
	Gas Well Othe			8. Well No. 2	
2. Name of Operator		RECI		9. OGRID Numbe	er .
CrownQuest Operating					213109
3. Address of Operator	ELEC			10. Pool name or	
_	TV 70710	JAN 2	4 2008		
PO Box 53310, Midland,	1 X /9/10		- 2000	Saunders: 1	Permo Penn Upper
4. Well Location					
Unit Letter :	660 feet from the		S ding and o		om the West line
Section 14	Township 1		ange 33E	NMPM	County Lea
والمتحال والأراجي والمتعارض والمتعار	11. Elevation (Show w	hether DR,	RKB, RT, GR, etc.,) colum	羅羅書名言 衛門軍人是原衛衛衛門等原
		421	13		
Pit or Below-grade Tank Applica	tion or Closure				
Pit type Depth to Groun		from nearest	fresh water well	Distance from near	rest surface water
	mil Below-Grade Tan			bls; Construction Mater	
12. Check A	Appropriate Box to Ir	ndicate Na	iture of Notice,	Report or Other	Data
	NTENTION TO:	_		BSEQUENT RE	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	٧ 🔲	REMEDIAL WOR		ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS		COMMENCE DRI	LLING OPNS.	P AND A
PULL OR ALTER CASING	MULTIPLE		CASING/CEMEN	T JOB 🔲	
	COMPLETION				
OTHER:			OTHER:		
· · · · · · · · ·					
	ed operations (Clearly s	tate all perti	nent details, and g	ive pertinent dates in	ncluding estimated date of
13. Describe proposed or complete					
13. Describe proposed or complete starting any proposed work). S					
13. Describe proposed or complete starting any proposed work). S recompletion.	SEE RULE 1103. For M	ultiple Com	pletions: Attach v	vellbore diagram of p	proposed completion or
13. Describe proposed or complete starting any proposed work). S recompletion. 1/02/08 MIRU. 1/03/08 ND well	SEE RULE 1103. For M head, NU BOP Rih w/ 1	ultiple Com	spletions: Attach v	vellbore diagram of p	proposed completion or
13. Describe proposed or complete starting any proposed work). S recompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem	SEE RULE 1103. For M head, NU BOP Rih w/ 1 ent plug on top of CIBI	lultiple Com 169 jts. tbg. P @ 9660. I	SDFN. 1/04/08 FOH w/ 80 jts. tbg	wellbore diagram of p RIH w/ tbg. to 9660' s. 1/07/08 POH w/	croposed completion or circulate hole with tbg. ND wellhead and
13. Describe proposed or complete starting any proposed work). Series recompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri	SEE RULE 1103. For Months of the Form of the Months of the	ultiple Com 169 jts. tbg. P @ 9660. I d 130000 lk	SDFN. 1/04/08 F POH w/ 80 jts. tbg os. got slips out. F	wellbore diagram of p RIH w/ tbg. to 9660' i. 1/07/08 POH w/ i ree point csg. Cut c	c. circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ric 2 jts. casing. SDFN. 1/09/08 Laid	SEE RULE 1103. For Months of the Months of t	Multiple Com 169 jts. tbg. P @ 9660. F d 130000 lk w/ jacks. I	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. Faid down 4 jts. w	wellbore diagram of p RIH w/ tbg. to 9660' [. 1/07/08 POH w/ ree point csg. Cut c / Rig. SDFN. 1/10/0	c. circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle l down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi	ultiple Com 169 jts. tbg. P @ 9660. I d 130000 lk w/ jacks. I ng equipme	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. F aid down 4 jts. went. NU wellhead	vellbore diagram of p RIH w/ tbg. to 9660' [. 1/07/08 POH w/ tree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti	c. circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle l down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi	ultiple Com 169 jts. tbg. P @ 9660. I d 130000 lk w/ jacks. I ng equipme	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. F aid down 4 jts. went. NU wellhead	vellbore diagram of p RIH w/ tbg. to 9660' [. 1/07/08 POH w/ tree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti	c. circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement p	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casil lug. POH w/ 50 jts. tbg	ultiple Com 169 jts. tbg. P @ 9660. H d 130000 lt w/ jacks. I ng equipme . SDFN. 1/	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. Fraid down 4 jts. went. NU wellhead 14/08 Tagged plu	wellbore diagram of p RIH w/ tbg. to 9660' g. 1/07/08 POH w/ t ree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ tl g @ 7574'. POH to	roposed completion or c. circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi lug. POH w/ 50 jts. tbg I plug @ 5445'. POH to	(ultiple Com 169 jts. tbg. P @ 9660. H d 130000 lk w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. Faid down 4 jts. went. NU wellhead 14/08 Tagged pluot 50 sx cement pl	RIH w/ tbg. to 9660' 1. 1/07/08 POH w/ tree point csg. Cut cy/ Rig. SDFN. 1/10/0 1. and BOP. RIH w/ tog @ 7574'. POH tog ug. SDFN. 1/15/08	croposed completion or concept complete c
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 4	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi lug. POH w/ 50 jts. tbg I plug @ 5445'. POH to 091'. WOC 4 hrs. Tag	(ultiple Com 169 jts. tbg. P @ 9660. I d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spe plug @ 400	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. Fraid down 4 jts. went. NU wellhead 14/08 Tagged pluot 50 sx cement pl 1'. POH to 2800'.	RIH w/ tbg. to 9660' i. 1/07/08 POH w/ tree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti g @ 7574'. POH to ug. SDFN. 1/15/08 Spot 75 sx cement	proposed completion or c. circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement RIH and tag plug @ plug to 2524. POH to
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pul	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi lug. POH w/ 50 jts. tbg 1 plug @ 5445'. POH to 091'. WOC 4 hrs. Tag j Il out of cement. SDFN.	(ultiple Com 169 jts. tbg. P @ 9660. H d 130000 lk w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. Fraid down 4 jts. went. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. lag plug @ 266'. l	RIH w/ tbg. to 9660' i. 1/07/08 POH w/ tree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti g @ 7574'. POH to ug. SDFN. 1/15/08 Spot 75 sx cement	proposed completion or c. circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement RIH and tag plug @ plug to 2524. POH to
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 4	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi lug. POH w/ 50 jts. tbg 1 plug @ 5445'. POH to 091'. WOC 4 hrs. Tag j Il out of cement. SDFN.	(ultiple Com 169 jts. tbg. P @ 9660. H d 130000 lk w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. Fraid down 4 jts. went. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. In moved off.	RIH w/ tbg. to 9660' i. 1/07/08 POH w/ i. ree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti g @ 7574'. POH to ug. SDFN. 1/15/08 Spot 75 sx cement POH to 50 ft. Spot 1	coroposed completion or coroposed completion of coroposed co
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pul	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi lug. POH w/ 50 jts. tbg 1 plug @ 5445'. POH to 091'. WOC 4 hrs. Tag j Il out of cement. SDFN.	(ultiple Com 169 jts. tbg. P @ 9660. H d 130000 lk w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. Fraid down 4 jts. went. NU wellhead 14/08 Tagged plu ot 50 sx cement plus 1'. POH to 2800'. In moved off.	RIH w/ tbg. to 9660' i. 1/07/08 POH w/ if ree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti reg @ 7574'. POH to reg word for plusping of welcomes	coroposed completion or coroposed coro
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pul	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi lug. POH w/ 50 jts. tbg 1 plug @ 5445'. POH to 091'. WOC 4 hrs. Tag j Il out of cement. SDFN.	(ultiple Com 169 jts. tbg. P @ 9660. H d 130000 lk w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. Fraid down 4 jts. went. NU wellhead 14/08 Tagged plu ot 50 sx cement plus 1'. POH to 2800'. In moved off.	RIH w/ tbg. to 9660' i. 1/07/08 POH w/ if ree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti reg @ 7574'. POH to ug. SDFN. 1/15/08 Spot 75 sx cement POH to 50 ft. Spot 1 roved for plugging of well title under bond is retain	coroposed completion or coroposed completion coroposed completion or coroposed completion or coroposed coroposed completion or coroposed corop
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pul	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi lug. POH w/ 50 jts. tbg 1 plug @ 5445'. POH to 091'. WOC 4 hrs. Tag j Il out of cement. SDFN.	(ultiple Com 169 jts. tbg. P @ 9660. H d 130000 lk w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. F aid down 4 jts. w ent. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. lag plug @ 266'. In moved off.	wellbore diagram of partial with with the control of the control o	proposed completion or c. circulate hole with the ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement RIH and tag plug @ plug to 2524. POH to 15 sx cement surface
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pul	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi lug. POH w/ 50 jts. tbg 1 plug @ 5445'. POH to 091'. WOC 4 hrs. Tag j Il out of cement. SDFN.	(ultiple Com 169 jts. tbg. P @ 9660. H d 130000 lk w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. F aid down 4 jts. went. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. lag plug @ 266'. In moved off. Application	wellbore diagram of particles of the wellbore diagram of wellbore diagram of the wellbore diagram	proposed completion or c. circulate hole with the ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement RIH and tag plug @ plug to 2524. POH to 15 sx cement surface
13. Describe proposed or complete starting any proposed work). Serecompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pul	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi lug. POH w/ 50 jts. tbg 1 plug @ 5445'. POH to 091'. WOC 4 hrs. Tag j Il out of cement. SDFN.	(ultiple Com 169 jts. tbg. P @ 9660. H d 130000 lk w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T	SDFN. 1/04/08 FPOH w/ 80 jts. tbg os. got slips out. F aid down 4 jts. went. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. lag plug @ 266'. In moved off. Application	wellbore diagram of partial with with the control of the control o	proposed completion or c. circulate hole with the ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement RIH and tag plug @ plug to 2524. POH to 15 sx cement surface
13. Describe proposed or complete starting any proposed work). Serious recompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement plug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pulplug. Cut off wellhead and weld	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casi lug. POH w/ 50 jts. tbg I plug @ 5445'. POH to 091'. WOC 4 hrs. Tag j Il out of cement. SDFN. on Dry Hole Marker. R	dultiple Com 169 jts. tbg. P @ 9660. H d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T kigged down	SDFN. 1/04/08 FOH w/ 80 jts. tbg os. got slips out. For aid down 4 jts. went. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. ag plug @ 266'. In moved off. Application of the control	RIH w/ tbg. to 9660' (1. 1/07/08 POH w/ (1. 1/07/08 POH w/ (1. 1/07/08 POH w/ (1. 1/10/08 (2. 1/10/08 (3. 1/10/08 (4. 1/10/08 (5. 1/10/08 (5. 1/10/08 (5. 1/10/08 (5. 1/10/08 (5. 1/10/08 (5. 1/10/08 (5. 1/10/08 (5. 1/10/08 (5. 1/10/08 (5. 1/10/08 (5. 1/10/08 (5. 1/10/08 (6. 1/10/08 (proposed completion or c. circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement RIH and tag plug @ plug to 2524. POH to 15 sx cement surface
13. Describe proposed or complete starting any proposed work). Serious recompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement plug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pulplug. Cut off wellhead and weld	head, NU BOP Rih w/ 1 ent plug on top of CIBl g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casilug. POH w/ 50 jts. tbg I plug @ 5445'. POH to 1091'. WOC 4 hrs. Tag Jul out of cement. SDFN. on Dry Hole Marker. R	dultiple Com 169 jts. tbg. P @ 9660. It d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T tigged down	SDFN. 1/04/08 FOH w/ 80 jts. tbg os. got slips out. Found down 4 jts. went. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. ag plug @ 266'. In moved off. Application of County y knowledge and bel	wellbore diagram of particles of the wellbore diagrams of wellbore of the wellb	proposed completion or c. circulate hole with the completion of th
13. Describe proposed or complete starting any proposed work). Serious recompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement plug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pulplug. Cut off wellhead and weld	head, NU BOP Rih w/ 1 ent plug on top of CIBl g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casilug. POH w/ 50 jts. tbg I plug @ 5445'. POH to 1091'. WOC 4 hrs. Tag Jul out of cement. SDFN. on Dry Hole Marker. R	dultiple Com 169 jts. tbg. P @ 9660. It d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T tigged down	SDFN. 1/04/08 FOH w/ 80 jts. tbg os. got slips out. Found down 4 jts. went. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. ag plug @ 266'. In moved off. Application of County y knowledge and bel	wellbore diagram of particles of the wellbore diagrams of wellbore of the wellb	proposed completion or c. circulate hole with the completion of th
13. Describe proposed or complete starting any proposed work). Service recompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Puplug. Cut off wellhead and weld	head, NU BOP Rih w/ 1 ent plug on top of CIBl g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casilug. POH w/ 50 jts. tbg I plug @ 5445'. POH to 1091'. WOC 4 hrs. Tag Jul out of cement. SDFN. on Dry Hole Marker. R	dultiple Com 169 jts. tbg. P @ 9660. It d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T tigged down	SDFN. 1/04/08 FPOH w/ 80 jts. tbg ps. got slips out. Fr. aid down 4 jts. went. NU wellhead 14/08 Tagged plu pt 50 sx cement pl 1'. POH to 2800'. ag plug @ 266'. In moved off. App Liak of C whi For y knowledge and bel general permit or	RIH w/ tbg. to 9660' i. 1/07/08 POH w/ tree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti g. @ 7574'. POH to ug. SDFN. 1/15/08 Spot 75 sx cement POH to 50 ft. Spot 1 roved for plugging of well fillit under bond is retain 103 (Subsequent Report the may be found at OCI) ms, www.effified.state.nm. ief. I further certify the an (attached) alternative	proposed completion or c. circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement 3 RIH and tag plug @ plug to 2524. POH to 15 sx cement surface I here only ted pending receipt of Well Plugaing? Web Page under tusyoed. at any pit or below-grade tank we OCD-approved plan
13. Describe proposed or complete starting any proposed work). Serious recompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement plug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pulplug. Cut off wellhead and weld	head, NU BOP Rih w/ 1 ent plug on top of CIBl g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casilug. POH w/ 50 jts. tbg I plug @ 5445'. POH to 1091'. WOC 4 hrs. Tag Jul out of cement. SDFN. on Dry Hole Marker. R	dultiple Com 169 jts. tbg. P @ 9660. It d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T tigged down	SDFN. 1/04/08 FPOH w/ 80 jts. tbg ps. got slips out. Fr. aid down 4 jts. went. NU wellhead 14/08 Tagged plu pt 50 sx cement pl 1'. POH to 2800'. ag plug @ 266'. In moved off. App Liak of C whi For y knowledge and bel general permit or	RIH w/ tbg. to 9660' i. 1/07/08 POH w/ tree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti g. @ 7574'. POH to ug. SDFN. 1/15/08 Spot 75 sx cement POH to 50 ft. Spot 1 roved for plugging of well fillit under bond is retain 103 (Subsequent Report the may be found at OCI) ms, www.effified.state.nm. ief. I further certify the an (attached) alternative	proposed completion or c. circulate hole with the completion of th
13. Describe proposed or complete starting any proposed work). Service recompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Puplug. Cut off wellhead and weld	head, NU BOP Rih w/ 1 ent plug on top of CIBl g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casilug. POH w/ 50 jts. tbg I plug @ 5445'. POH to 1091'. WOC 4 hrs. Tag Jul out of cement. SDFN. on Dry Hole Marker. R	dultiple Com 169 jts. tbg. P @ 9660. It d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T tigged down	SDFN. 1/04/08 FOH w/ 80 jts. tbg os. got slips out. Found down 4 jts. went. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. ag plug @ 266'. In moved off. Application of County y knowledge and bel	RIH w/ tbg. to 9660' i. 1/07/08 POH w/ tree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti g. @ 7574'. POH to ug. SDFN. 1/15/08 Spot 75 sx cement POH to 50 ft. Spot 1 roved for plugging of well fillit under bond is retain 103 (Subsequent Report the may be found at OCI) ms, www.effified.state.nm. ief. I further certify the an (attached) alternative	proposed completion or c. circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement 3 RIH and tag plug @ plug to 2524. POH to 15 sx cement surface I here only ted pending receipt of Well Plugaing? Web Page under tusyoed. at any pit or below-grade tank we OCD-approved plan
13. Describe proposed or complete starting any proposed work). Service recompletion. 1/02/08 MIRU. 1/03/08 ND well mud laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement pplug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Puplug. Cut off wellhead and weld	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casilug. POH w/ 50 jts. tbg I plug @ 5445'. POH to 091'. WOC 4 hrs. Tag jul out of cement. SDFN. on Dry Hole Marker. Reserve is true and complete to according to NMOCD guide	dultiple Com 169 jts. tbg. P @ 9660. It d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ o 4200'. Spo plug @ 400 1/16/08 T tigged down	SDFN. 1/04/08 FOH w/ 80 jts. tbg os. got slips out. For aid down 4 jts. went. NU wellhead 14/08 Tagged plust 50 sx cement plust 50 sx cement plust 7. POH to 2800'. In moved off. Application of the seneral permit of the	RIH w/ tbg. to 9660' i. 1/07/08 POH w/ ree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti reg @ 7574'. POH to reg. SDFN. 1/15/08 Spot 75 sx cement POH to 50 ft. Spot 1 roved for plugging of wel fillity under bond is retain 103 (Subsequent Report the may be found at OCD ms, www.effified.state.mm. ief. I further certify tha an (attached) alternative	proposed completion or c. circulate hole with the composed and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement RIH and tag plug @ plug to 2524. POH to 15 sx cement surface There only the property of Well Plugaing Web Page under 1990's de la policie
13. Describe proposed or complete starting any proposed work). Starting and proposed work and starting and sta	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casilug. POH w/ 50 jts. tbg I plug @ 5445'. POH to 091'. WOC 4 hrs. Tag jul out of cement. SDFN. on Dry Hole Marker. Reserve is true and complete to according to NMOCD guide	dultiple Com 169 jts. tbg. P @ 9660. I d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ 0 4200'. Spo plug @ 400 1/16/08 T tigged down the best of m elines X, a g TITLE -mail addre	SDFN. 1/04/08 FOH w/ 80 jts. tbg os. got slips out. F. aid down 4 jts. w ent. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. ag plug @ 266'. In moved off. App Liak of C whi For y knowledge and bel general permit or Wir · Speciel of SSS:	RIH w/ tbg. to 9660' 3. 1/07/08 POH w/ 3. 1/07/08 POH w/ 3. 1/107/08 POH w/ 3. 1/10/08 POH w/ 4. Rig. SDFN. 1/10/08 4. And BOP. RIH w/ tl 5. Bopt 75 To See Common POH to 50 ft. Spot 1 5. Toved for plugging of well will be under bond is retain 1/10/3 (Subsequent Report in may be found at OCI) 5. Bopt 1/10/10/10/10/10/10/10/10/10/10/10/10/10	proposed completion or circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement 3 RIH and tag plug @ plug to 2524. POH to 15 sx cement surface There only ted pending receipt of Well Plugaing? DATE
13. Describe proposed or complete starting any proposed work). Service a starting any proposed work). Seven and laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement plug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pul plug. Cut off wellhead and weld SIGNATURE Type or print name For State Use Only	head, NU BOP Rih w/ 12 ent plug on top of CIBI g up casing jacks. Pulle l down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casis lug. POH w/ 50 jts. tbg l plug @ 5445'. POH to 091'. WOC 4 hrs. Tag j ll out of cement. SDFN. on Dry Hole Marker. R	dultiple Com 169 jts. tbg. P @ 9660. I d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ 0 4200'. Spo plug @ 400 1/16/08 T tigged down the best of m elines X, a g TITLE -mail addre	SDFN. 1/04/08 FOH w/ 80 jts. tbg os. got slips out. F. aid down 4 jts. w ent. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. ag plug @ 266'. In moved off. App Liak of C whi For y knowledge and bel general permit or Wir · Speciel of SSS:	RIH w/ tbg. to 9660' 3. 1/07/08 POH w/ 3. 1/07/08 POH w/ 3. 1/107/08 POH w/ 3. 1/10/08 POH w/ 4. Rig. SDFN. 1/10/08 4. And BOP. RIH w/ tl 5. Bopt 75 To See Common POH to 50 ft. Spot 1 5. Toved for plugging of well will be under bond is retain 1/10/3 (Subsequent Report in may be found at OCI) 5. Bopt 1/10/10/10/10/10/10/10/10/10/10/10/10/10	proposed completion or circulate hole with the ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement RIH and tag plug @ plug to 2524. POH to 15 sx cement surface I have only led pending receipt of Well Plugaing? Web Page under surface. It any pit or below-grade tank we OCD-approved plan DATE 21 08 DATE 21 08 DATE 12 08 DATE 13 08 DATE 14 08 DATE 15 08
13. Describe proposed or complete starting any proposed work). Starting and proposed work). Starting and start	head, NU BOP Rih w/ 12 ent plug on top of CIBI g up casing jacks. Pulle l down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casis lug. POH w/ 50 jts. tbg l plug @ 5445'. POH to 091'. WOC 4 hrs. Tag j ll out of cement. SDFN. on Dry Hole Marker. R	dultiple Com 169 jts. tbg. P @ 9660. I d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ 0 4200'. Spo plug @ 400 1/16/08 T tigged down the best of m elines X, a g TITLE -mail addre	SDFN. 1/04/08 FOH w/ 80 jts. tbg os. got slips out. F. aid down 4 jts. w ent. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. ag plug @ 266'. In moved off. App Liak of C whi For y knowledge and bel general permit or Wir · Speciel of SSS:	RIH w/ tbg. to 9660' i. 1/07/08 POH w/ ree point csg. Cut c / Rig. SDFN. 1/10/0 and BOP. RIH w/ ti reg @ 7574'. POH to reg. SDFN. 1/15/08 Spot 75 sx cement POH to 50 ft. Spot 1 roved for plugging of wel fillity under bond is retain 103 (Subsequent Report the may be found at OCD ms, www.effified.state.mm. ief. I further certify tha an (attached) alternative	proposed completion or circulate hole with the ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement RIH and tag plug @ plug to 2524. POH to 15 sx cement surface I have only led pending receipt of Well Plugaing? Web Page under surface. It any pit or below-grade tank we OCD-approved plan DATE 21 08 DATE 21 08 DATE 12 08 DATE 13 08 DATE 14 08 DATE 15 08
13. Describe proposed or complete starting any proposed work). Service a starting any proposed work). Seven and laiden fluid. Spot 25 sx. cem dig out cellar. SDFN. 1/08/08 Ri 2 jts. casing. SDFN. 1/09/08 Laid csg. SDFN. 1/11/08 Laid down 3 hole w/ mud. Spot 50 sx cement plug @ 5600. WOC 4 hrs. Tagged 4091. Spot 25 sx cement plug @ 400'. Spot 35 sx cement plug. Pul plug. Cut off wellhead and weld SIGNATURE Type or print name For State Use Only	head, NU BOP Rih w/ 1 ent plug on top of CIBI g up casing jacks. Pulle I down 44 jts. 5 1/2 csg. 9 jts. 5 1/2 csg. RD casilug. POH w/ 50 jts. tbg I plug @ 5445'. POH to 091'. WOC 4 hrs. Tag jul out of cement. SDFN. on Dry Hole Marker. Reserve is true and complete to according to NMOCD guide	dultiple Com 169 jts. tbg. P @ 9660. I d 130000 lt w/ jacks. I ng equipme . SDFN. 1/ 0 4200'. Spo plug @ 400 1/16/08 T tigged down the best of m elines X, a g TITLE -mail addre	SDFN. 1/04/08 FOH w/ 80 jts. tbg os. got slips out. F. aid down 4 jts. w ent. NU wellhead 14/08 Tagged plu ot 50 sx cement pl 1'. POH to 2800'. ag plug @ 266'. In moved off. App Liak of C whi For y knowledge and bel general permit or Wir · Speciel of SSS:	RIH w/ tbg. to 9660' 3. 1/07/08 POH w/ 3. 1/07/08 POH w/ 3. 1/107/08 POH w/ 3. 1/10/08 POH w/ 4. Rig. SDFN. 1/10/08 4. And BOP. RIH w/ tl 5. Bopt 75 To See Common POH to 50 ft. Spot 1 5. Toved for plugging of well will be under bond is retain 1/10/3 (Subsequent Report in may be found at OCI) 5. Bopt 1/10/10/10/10/10/10/10/10/10/10/10/10/10	proposed completion or circulate hole with tbg. ND wellhead and sg. @ 7700'. Laid down 08 POH w 160 jts. 5 1/2 bg to 7800'. Circulate 5600'. Spot 35 sx cement 3 RIH and tag plug @ plug to 2524. POH to 15 sx cement surface There only ted pending receipt of Well Plugaing? DATE