

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N French Dr., Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S St Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources RECEIVED Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 FEB 26 2008 HOBBS OGD	Form C-105 Revised June 10, 2003 WELL API NO. 30-025-38684 5. Indicate Type of Lease STATE ☐ FEE ☒ State Oil & Gas Lease No. N/A
WELL COMPLETION OR RECOMPLETION REPORT		
1a Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____ b Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. _____ WELL OVER BACK RESVR. ☐ OTHER _____		7 Lease Name or Unit Agreement Name Gill Deep
2. Name of Operator Apache Corporation		8. Well No. 006
3. Address of Operator 6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224		9 Pool name or Wildcat Blinebry Oil & Gas (Oil)
4. Well Location Unit Letter <u>K</u> <u>1370</u> Feet From The <u>South</u> Line and <u>1300</u> Feet From The <u>West</u> Line Section <u>31</u> Township <u>21S</u> Range <u>37E</u> NMPM Lea County		
10 Date Spudded 01/22/2008	11. Date T.D. Reached 01/28/2008	12. Date Compl. (Ready to Prod.) 02/20/2008
13. Elevations (DF& RKB, RT, GR, etc.) 3469' GR		14. Elev. Casinghead
15. Total Depth 6875'	16. Plug Back T.D. 6150' RBP	17. If Multiple Compl. How Many Zones? NA
18 Intervals Drilled By X		Rotary Tools Cable Tools
19 Producing Interval(s), of this completion - Top, Bottom, Name 5588-5652' (Blinebry O&G)		20. Was Directional Survey Made No
21. Type Electric and Other Logs Run SD/DSN, DLL-MG, BSAT		22. Was Well Cored No
23. CASING RECORD (Report all strings set in well)		
CASING SIZE	WEIGHT LB./FT.	DEPTH SET
8-5/8"	24#	1173'
5-1/2"	17#	6875'
HOLE SIZE		CEMENTING RECORD
12-1/4"		650 sx / circ
7-7/8"		1150 sx / circ
AMOUNT PULLED		
24. LINER RECORD		25. TUBING RECORD
SIZE	TOP	BOTTOM
SACKS CEMENT	SCREEN	SIZE
		2-7/8"
DEPTH SET	PACKER SET	
		5748'
26. Perforation record (interval, size, and number) Blinebry: 5588-5652' (2 JSPF, 27 holes) Tubb: 6196-6278' (2 JSPF, 40 holes) RBP @ 6150' Drinkard: 6542-6676' (2 JSPF, 53 holes) RBP @ 6518'		27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 5588-5652 3Kgal 15%HCl, 34Kgal SS-25 + 70K# 20/40 6196-6278 3Kgal 15%HCl, 36Kgal SS-25 + 82K# 20/40 6542-6676 3Kgal 15%HCl, 39Kgal SS-35 + 62K# 20/40
28. PRODUCTION		
Date First Production 02/20/2008		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping - Rod Pump
Well Status (Prod. or Shut-in) Producing		
Date of Test 02/24/2008	Hours Tested 24 hours	Choke Size
Prod'n For Test Period	Oil - Bbl 24	Gas - MCF 80
Water - Bbl 93	Gas - Oil Ratio 3333	
Flow Tubing Press	Casing Pressure	Calculated 24-Hour Rate
Oil - Bbl.	Gas - MCF	Water - Bbl
Oil Gravity - API - (Corr) 35.7		
29 Disposition of Gas (Sold, used for fuel, vented, etc) Sold		Test Witnessed By Apache Corporation
30. List Attachments Inclination Report, C-102, C-103, C-104 (Logs mailed 2/8/08)		
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.		
Signature <i>Sophie Mackay</i> E-mail Address sophie.mackay@apachecorp.com		Printed Name Sophie Mackay Title Engineering Tech Date 02/20/2008

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2669'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2903'	T. Devonian	T. Menefee	T. Madison
T. Queen 3396'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3673'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3954'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5136'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry 5660'	T. Gr. Wash	T. Morrison	T.
T. Tubb 6127'	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6437'	T. Bone Springs	T. Entrada	T.
T. Abo 6678'	T. Rustler 1147'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology