

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N French Dr., Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Santa Fe, NM 87505	Form C-105 Revised June 10, 2003 WELL API NO. 30-025-38455 5. Indicate Type of Lease STATE ☒ FEE ☐ State Oil & Gas Lease No. BH-1533
---	--	--

RECEIVED
 JAN 30 2008
 HOBBS OCD

WELL COMPLETION OR RECOMPLETION REPORT AND LOG							
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐ b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. ☐ WELL OVER BACK RESVR. ☐ OTHER ☐	7. Lease Name or Unit Agreement Name North Monument G/SA Unit						
2. Name of Operator Apache Corporation	8. Well No 359						
3. Address of Operator 6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224	9. Pool name or Wildcat Eunice Monument; Grayburg-San Andres						
4. Well Location Unit Letter D 1170 Feet From The North Line and 180 Feet From The West Line Section 30 Township 19S Range 37E NMPM Lea County							
10. Date Spudded 11/27/2007	11. Date T.D. Reached 12/01/2007						
12. Date Compl. (Ready to Prod) 01/04/2008	13 Elevations (DF& RKB, RT, GR, etc) 3651' GR						
14 Elev. Casinghead 							
15. Total Depth 4088'	16. Plug Back T.D. 4038'						
17 If Multiple Compl. How Many Zones? N/A	18. Intervals Drilled By X						
19. Producing Interval(s), of this completion - Top, Bottom, Name Eunice Monument; Grayburg-San Andres 3686' - 3846'							
20. Was Directional Survey Made NO	21. Type Electric and Other Logs Run SD/DSN, DLL-MG, ISAT						
22. Was Well Cored NO							
23. CASING RECORD (Report all strings set in well)							
CASING SIZE	WEIGHT LB /FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED		
8-5/8"	24#	1265'	12-1/4"	950 sx / circ			
5-1/2"	17#	4088'	7-7/8"	900 sx / TOC 1690' CBL			
24. LINER RECORD			25. TUBING RECORD				
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-7/8"	3811'	
26. Perforation record (interval, size, and number) G/SA 3686-3716' 2 JSPF, 39 holes G/SA 3748-3846' 2 JSPF, 76 holes G/SA 3866-3919' 2 JSPF, 85 holes (CIBP @ 3853') G/SA 3930-3969', 2 JSPF, 61 holes (CIBP @ 3925')				27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 3686-3716' 2000 gals 15% HCl 3748-3846' 4000 gals 15% HCl 3866-3919/3930-69' 2000 gals 15% HCl / 2000 gals 15% HCl			
28. PRODUCTION							
Date First Production 01/04/2008		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping			Well Status (Prod. or Shut-in) Producing		
Date of Test 01/23/2008	Hours Tested 24	Choke Size 	Prod'n For Test Period 	Oil - Bbl 8	Gas - MCF 20	Water - Bbl. 26	Gas - Oil Ratio 2500
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl	Oil Gravity - API - (Corr) 33.7	
29 Disposition of Gas (Sold, used for fuel, vented, etc.) Sold						Test Witnessed By Apache	
30. List Attachments Inclination Report, Logs, C-102, C-103, C-104							
31 I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief							
Signature	Printed Name Sophie Mackay	Title Engineering Tech	Date 01/28/2008				
E-mail Address sophie.mackay@apachecorp.com							

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2559'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2809'	T. Devonian	T. Menefee	T. Madison
T. Queen 3301'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3650'	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T. Rustler 1216'	T. Wingate	T.
T. Wolfcamp	T. Penrose 3417'	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology