

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr, Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Form C-144
June 1, 2004

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes ☒ No ☐

Type of action Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒

Operator Chevron USA Telephone: 505 396 4414 e-mail address: lduke@chevron.com		
Address HCR 60 P.O. Box 423 Lovington, New Mexico 88260		
Facility or well name: CVU #49 API #: 30-025-02958 Unit Letter (UL): C Qtr/Qtr: NW¼ NE¼ Section 31, T17S, R35E		
County: Lea Latitude 32°47'49 87"N Longitude: 103°29'57 76"W NAD: 1927 <input type="checkbox"/> 1983 <input type="checkbox"/> WGS 84 <input checked="" type="checkbox"/>		
Surface Owner. Federal <input type="checkbox"/> State <input checked="" type="checkbox"/> Private <input type="checkbox"/> Indian <input type="checkbox"/>		
Pit		Below-grade tank
Type. Drilling <input checked="" type="checkbox"/> Production <input type="checkbox"/> Disposal <input type="checkbox"/> Workover <input type="checkbox"/> Emergency <input type="checkbox"/>		Volume. bbl Type of fluid
Lined <input checked="" type="checkbox"/> Unlined <input type="checkbox"/>		Construction material.
Liner type Synthetic <input checked="" type="checkbox"/> Thickness 12 mil Clay <input type="checkbox"/>		Double-walled, with leak detection? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Pit Volume. ~3,000 bbl		
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water) ~105'bgs	Less than 50 feet	(20 points) <input type="checkbox"/>
	50 feet or more, but less than 100 feet	(10 points) <input type="checkbox"/>
	100 feet or more	(0 points) <input checked="" type="checkbox"/>
Wellhead protection area (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes	(20 points) <input type="checkbox"/>
	No	(0 points) <input checked="" type="checkbox"/>
Distance to surface water. (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses)	Less than 200 feet	(20 points) <input type="checkbox"/>
	200 feet or more, but less than 1,000 feet	(10 points) <input type="checkbox"/>
	1,000 feet or more	(0 points) <input checked="" type="checkbox"/>
Ranking Score (Total Points)		0

If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks (2) Indicate disposal location. (check the onsite box if you are burying in place) onsite ☐ offsite ☒ If offsite, name of facility CRI (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered. No ☒ Yes ☐ If yes, show depth below ground surface ft and attach sample results (5) Attach soil sample results and a diagram of sample locations and excavations.

Additional Comments. This pit has been closed consistent with the "ChevronTexaco Drilling and Reserve Pit Closure General Plan, December 2004" and the NMOCD Pit and Below-Grade Tank Guidelines, November 1, 2004 as promulgated under NMOCD Rule 50 (19 15.2.50 NMAC)
Pit Status. Liner intact <input checked="" type="checkbox"/> Liner punctured or torn <input type="checkbox"/>
Method of Closure. Original pit contents were stiffened and transported to a disposal facility; drill pit was excavated to approximately three (3) feet bgs with ~ 1,020 yds ³ of impacted soil removed and disposed at a State approved facility; excavation bottom and sidewalls were tested for acceptable TPH, BTEX, and chloride concentrations; excavation bottom was leveled and a one (1) foot layer of cushion sand installed; 40 mil polyethylene liner was installed on bottom extending two and one-half (2 1/2) feet vertically up sidewalls, excavation was backfilled with approximately ~994 yds ³ of clean soil and entire disturbed areas contoured for natural drainage; disturbed areas will be seeded with a blend preferred by the NMSLO in late spring 2008 when moisture levels are high and survival of newly emerged grass is greater.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank will be closed according to NMOCD guidelines <input checked="" type="checkbox"/> , a general permit <input checked="" type="checkbox"/> , or an (attached) alternative OCD-approved plan <input type="checkbox"/> .		
Date. 2/14/08	Printed Name/Title Jim Duke, Construction Representative	Signature [Signature]
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations		
Approval. [Signature]		
Printed Name/Title	Signature ENVIRONMENTAL ENGINEER	Date 3.19.08

RBC - 40 MIL LINER PLACED @ 3 1/2'
DUE TO ADJACENT TRANSITE LINE.
SOME CONTAM LEFT IN EXCAVATION.