Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED
OMB No. 1004-0135
Expires July 31, 1996

Lease Serial No

N	M	-2	41	65

If Indian, Allottee or Tribe Name

abai	ndoned well. Use form 3766	-3-(ARD) for such br	oposals)	
	U			7 If Unit or CA/Agreement, Name and/or No.
SUBMIT IN TR	RIPLICATE - Other instruction	ons on reverse side		
. Type of Well		FEB - 4 2008	}	
X Oil Well Gas Well	Other .	-		8 Well Name and No.
Name of Operator		DRAST	MIN	Mescalero B 29 Federal No. 1
Cimarex Energy Co. of Colorac	do			9 API Well No.
. Address		3b Phone No (includ	de area code)	30-025-38677
PO Box 140907; Irving, TX 750	014-0907	972-401-3111		10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T, R, M	M , or Survey Description)			Quail Ridge; Bone Spring, South
330' FSL & 660' FWL				11. County or Parish, State
- 29-19S-34E				Lea County, NM
12. CHECK API	PROPRIATE BOX(ES) T	O INDICATE NAT	URE OF NOTIC	CE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION		Ţ	YPE OF ACTION	
V Nagaragus				UD
X Notice of Intent	Acidize	Deepen	Production (Star	, <u>–</u>
	X Alter Casing	Fracture Treat	Reclamation	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	Other
	Change Plans	Plug and Abandon	Temporarily Aba	andon
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal	
following completion of the involved oper testing has been completed. Final Aban determined that the site is ready for final	ndonment Notices shall be filed only a if inspection.)	after all requirements, includ	ling reclamation, have b	een completed, and the operator has
testing has been completed. Final Aban determined that the site is ready for final The 8-5/8" 32# HCK-55 LTC capurchase. Instead, Cimarex would like to Safety factor based on anticip	ndonment Notices shall be filed only a al inspection.) asing we chose for our inter o drill 12 1/4" hole and run pated pressures of .4 psi per POZ-C + 5% D-44 (BWOW) +	efter all requirements, includ remediate string on the 9 5/8" 40# N-80 LTC r foot with 8.6# mud + 10% D-20 + 5# D-24	ne Mescalero B 25 C casing to 5380'.	Peen completed, and the operator has 9 Federal No. 1 well is unavailable to Burst rating is 3090 psi 8.6 = 2406. 3090/2406 is 1.3
testing has been completed. Final Aban determined that the site is ready for final The 8-5/8" 32# HCK-55 LTC capurchase. Instead, Cimarex would like to Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FTail: 240 sx (47.4 bbl) Class C-	ndonment Notices shall be filed only a il inspection.) esing we chose for our inter to drill 12 1/4" hole and run pated pressures of .4 psi per POZ-C + 5% D-44 (BWOW) + + 2% S-1 (wt 14.8, yld 1.34)	efter all requirements, includ remediate string on the 9 5/8" 40# N-80 LTC r foot with 8.6# mud + 10% D-20 + 5# D-24	ne Mescalero B 25 C casing to 5380'.	Peen completed, and the operator has 9 Federal No. 1 well is unavailable to Burst rating is 3090 psi 8.6 = 2406. 3090/2406 is 1.3
testing has been completed. Final Aban determined that the site is ready for final The 8-5/8" 32# HCK-55 LTC capurchase. Instead, Cimarex would like to Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FTail: 240 sx (47.4 bbl) Class C	ndonment Notices shall be filed only a il inspection.) esing we chose for our inter to drill 12 1/4" hole and run pated pressures of .4 psi per POZ-C + 5% D-44 (BWOW) + + 2% S-1 (wt 14.8, yld 1.34)	efter all requirements, includ remediate string on the 9 5/8" 40# N-80 LTC r foot with 8.6# mud + 10% D-20 + 5# D-24	ne Mescalero B 25 C casing to 5380'.	Peen completed, and the operator has 9 Federal No. 1 well is unavailable to Burst rating is 3090 psi 8.6 = 2406. 3090/2406 is 1.3
testing has been completed. Final Aban determined that the site is ready for final The 8-5/8" 32# HCK-55 LTC capurchase. Instead, Cimarex would like to Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT ail: 240 sx (47.4 bbl) Class Contains and the same statements of the same statemen	ndonment Notices shall be filed only a il inspection.) esing we chose for our inter to drill 12 1/4" hole and run pated pressures of .4 psi per POZ-C + 5% D-44 (BWOW) + + 2% S-1 (wt 14.8, yld 1.34)	rifter all requirements, includ remediate string on the 9 5/8" 40# N-80 LTC r foot with 8.6# mud + 10% D-20 + 5# D-24	ne Mescalero B 2 C casing to 5380'. I is 5380 x .052 x 4 + 0.125# D-130	Peen completed, and the operator has 9 Federal No. 1 well is unavailable to Burst rating is 3090 psi 8.6 = 2406. 3090/2406 is 1.3
testing has been completed. Final Aban determined that the site is ready for final The 8-5/8" 32# HCK-55 LTC capurchase. Instead, Cimarex would like to Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FTail: 240 sx (47.4 bbl) Class Complete Co	ndonment Notices shall be filed only a il inspection.) esing we chose for our inter to drill 12 1/4" hole and run pated pressures of .4 psi per POZ-C + 5% D-44 (BWOW) + + 2% S-1 (wt 14.8, yld 1.34)	Title Mgr Operat	ne Mescalero B 2 C casing to 5380'. I is 5380 x .052 x 4 + 0.125# D-130	Peen completed, and the operator has 9 Federal No. 1 well is unavailable to Burst rating is 3090 psi 8.6 = 2406. 3090/2406 is 1.3
testing has been completed. Final Aban determined that the site is ready for final The 8-5/8" 32# HCK-55 LTC capurchase. Instead, Cimarex would like to Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Completed Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 915	ndonment Notices shall be filed only a il inspection.) esing we chose for our inter to drill 12 1/4" hole and run pated pressures of .4 psi per POZ-C + 5% D-44 (BWOW) + + 2% S-1 (wt 14.8, yld 1.34)	rifter all requirements, includ remediate string on the 9 5/8" 40# N-80 LTC r foot with 8.6# mud + 10% D-20 + 5# D-24	ne Mescalero B 2 C casing to 5380'. I is 5380 x .052 x 4 + 0.125# D-130	Peen completed, and the operator has 9 Federal No. 1 well is unavailable to Burst rating is 3090 psi 8.6 = 2406. 3090/2406 is 1.3
testing has been completed. Final Aban determined that the site is ready for final The 8-5/8" 32# HCK-55 LTC capurchase. Instead, Cimarex would like to Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Completed Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Completed Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Completed Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Completed Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (47.4 bbl) Class Complete Safety factor based on anticip S	and correct and correct and correct and correct and inspection.) asing we chose for our interval inspection. asing we chose for our interval inspection. asing we chose for our interval inspection. and correct and correct	Title Mgr Operat January 18,	ing reclamation, have being me Mescalero B 2.5 C casing to 5380'. d is 5380 x .052 x 4 + 0.125# D-130	Peen completed, and the operator has 9 Federal No. 1 well is unavailable to Burst rating is 3090 psi 8.6 = 2406. 3090/2406 is 1.3
testing has been completed. Final Aban determined that the site is ready for final The 8-5/8" 32# HCK-55 LTC capurchase. Instead, Cimarex would like to Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Completed Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Completed Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 91	and correct and correct and correct and correct and inspection.) asing we chose for our interval inspection. asing we chose for our interval inspection. asing we chose for our interval inspection. and correct and correct	rmediate string on the string	ing reclamation, have being me Mescalero B 2.5 C casing to 5380'. d is 5380 x .052 x 4 + 0.125# D-130	Peen completed, and the operator has 9 Federal No. 1 well is unavailable to Burst rating is 3090 psi 8.6 = 2406. 3090/2406 is 1.3
testing has been completed. Final Aban determined that the site is ready for final The 8-5/8" 32# HCK-55 LTC capurchase. Instead, Cimarex would like to Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Completed Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Completed Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 240 sx (47.4 bbl) Class Complete Safety factor based on anticip Lead: 915 sx (336 bbl) 50/50 FT Tail: 91	and correct and correct and correct and correct and inspection.) asing we chose for our interval inspection. asing we chose for our interval inspection. asing we chose for our interval inspection. and correct and correct	Title Mgr Operat January 18,	ing reclamation, have being me Mescalero B 2.5 C casing to 5380'. d is 5380 x .052 x 4 + 0.125# D-130	Peen completed, and the operator has 9 Federal No. 1 well is unavailable to Burst rating is 3090 psi 8.6 = 2406. 3090/2406 is 1.3