Submit 3 Copies To Appropriate District Office State of New Mexic	
District I Energy, Minerals and Natural 1625 N French Dr. Hobbs, NM 88240	Resources May 27, 2004 WELL API NO.
District II	20.025.09(5)
1301 W. Grand Ave , Artesia, NM 88210 OIL CONSERVATION D District III	I VISION 5 Indicate Type of Laure
1000 Rio Brazos Rd , Aztec, NM 87410	STATE FEE X
District IV 1220 S St Francis Dr., Santa Fe, NM 87505	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG	7 Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR S PROPOSALS.)	SUCH COME STANDARY THE STOOT CHIL
1. Type of Well: Oil Well X Gas Well Other	8. Well Number 802
Name of Operator Melrose Operating Company	9. OGRID Number 184860
3. Address of Operator	10. Pool name or Wildcat
. c/o P.O Box 953, Midland, TX 79702	Jalmat, Tansil Yates 7 Rivers
4. Well Location	
Unit Letter D : 660 feet from the North line	and660 feet from theWest line
Section 25 Township 22S Range 35E NMPM Lea County	
11. Elevation (Shorr whether DR, RI	KB, RT, GR, etc.) 3570° GR
Pit or Below-grade Tank Application or Closure	,
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water	
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls: Construction Material	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
107107 07 117101 01171	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON X REMEDIAL WORK ALTERING CASING CO	
ALI ENING CASING [
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PAND A DEPULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB	
	ITHER:
13. Describe proposed or completed operations. (Clearly state all pert of starting any proposed work). SEE RULE 1103. For Multiple (or recompletion.	inent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion
Propose to Plug and Abandon as follows: Plan to set CIBP @ 3700' w/35' Cl C, 2% CaCl cement, above perfora Plan to set 100' plug using 35 sx cement, Cl C 2% CaCl,inside 5 1/2" (1600-1700'-tag. 1650'-1750'Cas 705 TW- 2 Plan to set 100' plug inside/outside 8 5/8" shoe @ 306' from 260-360' Set 10 sx surface plug. Set P & A marker.	casing (set @ 3955, cemented w/1940 sx to surface) from
•	
I hereby certify that the information above is true and complete to the best of grade tank has been/will be constructed or closed according to NMOCD guidelines X, a	of my knowledge and belief. I further certify that any pit or below-
aran man (III) ATT	gulatory AgentDATE4-1-08
Type or print name: Ann E. Ritchie E-mail address: ann.ritchie@wtor.r	Telephone No.432 684-6381
APPROVED BY: Mus Wellism OC DISTRICT SI Conditions of Approval (if any):	JEERVISOR/GENERAL MANAGER APRO3 200