

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
May 27, 2004

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-03732
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator Energen Resources Corporation		6. State Oil & Gas Lease No.
3. Address of Operator 3300 North A Street, Bldg. 4, Ste. 100 Midland, TX 79705		7. Lease Name or Unit Agreement Name: Snyder E
4. Well Location Unit Letter <u>B</u> : <u>1016</u> feet from the <u>North</u> line and <u>1980</u> feet from the <u>East</u> line Section <u>6</u> Township <u>16S</u> Range <u>36E</u> NMPM County <u>Lea</u>		8. Well Number <u>1</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) GR 3956'		9. OGRID Number 162928
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/> Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____		10. Pool name or Wildcat Townsend; Permo Upper Penn

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

See attached procedure

See changes - CW 4/4/08

RECEIVED

FEB 29 2008

HOBBS OCD

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been will be constructed or closed according to NMOCD guidelines ☒ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Carolyn Larson TITLE Regulatory Analyst DATE 2/27/08

Type or print name Carolyn Larson

E-mail address: clarson@energen.com

Telephone No. 432/684-3693

For State Use Only

APPROVED BY Chris Williams

OCD DISTRICT SUPERVISOR/GENERAL MANAGER
TITLE _____

DATE _____

Conditions of Approval, if any:

THE OIL CONSERVATION DIVISION MUST
BE NOTIFIED 24 HOURS PRIOR TO THE
BEGINNING OF PLUGGING OPERATIONS

APR 04 2008

ENERGEN RESOURCES CORPORATION

Snyder "E" #1
1016' FNL, 1980' FEL,
Sec 6, T-16-S, R-36-E
Lea, Co. NM
Townsend Permo-Penn Field
P&A Well

Date: February 25, 2008

AFE No: PB023108

Cost: \$42,000

WI: 100% NRI: 76.78125%

See Attached Wellbore Diagrams:

Plugging Procedure:

1. Spot 30 sx cement on CIBP @ 10,380', WOC, tag. Circulate w/ MLF.
2. Spot 30sx cement plug @ 7500'. Circulate MLF to 4650'.
3. Perforate casing @ 4779' with 4 squeeze holes.
4. Squeeze 60 sx cement through perfs @ 4779'.
5. Tag cement plug. Circulate MLF to ~~1600'~~ 1800'.
6. Spot 50 sx cement @ ~~1700'~~ 1800-1700'.
7. Tag cement plug. Circulate MLF to 250'
8. Perforate casing @ 414' with 4 squeeze holes.
9. Squeeze 60 sx cement through perfs.
10. Tag cement plug. Circulate MLF to surface.
11. Circulate cement plug @ 70' to surface.
12. Cut off wellhead 3' from surface and weld on P&A marker.

Energen Resources
Snyder "E" #1 (P&A)
Lea County, New Mexico

Elevation KB: 3967'
 Elevation GL: 3956'
 Location: 1016' FNL, 1980' FEL, Sec 6, T-16-S, R-36-E
 Spudded: 55-20-19586 Completed: 7-15-1958
 API #: 30-025-03732

PROPOSED P&A

